

Microwave Logic packetBERT PB200
Transceiver Bit Error Rate Test Set



**Limited Availability
Used and in Excellent Condition**

Open Web Page

<https://www.artisanTG.com/54548-1>

All trademarks, brandnames, and brands appearing herein are the property of their respective owners.



Your **definitive** source
for quality pre-owned
equipment.

Artisan Technology Group

(217) 352-9330 | sales@artisanTG.com | artisanTG.com

- Critical and expedited services
- In stock / Ready-to-ship
- We buy your excess, underutilized, and idle equipment
- Full-service, independent repair center

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

Bit Error Rate Test Set



packetBERT PB200

[Features](#)

[> Specs](#)

packetBERT™ PB200

This product is discontinued.
View [alternative products](#).

CHARACTERISTICS

GENERATOR

Clock -

External clock input:

Frequency: DC to 200 MHz.
Amplitude: 0.5 to 5.0 V p-p.
Connector: BNC.
Termination select: 50 Ohm to -2 V, +3 V, AC or GND.
Input range: ECL, TTL, PECL compatible.
Threshold resolution: 10 mV step.

External clock reference input:

Frequency: 10 MHz, ± 100 ppm maximum.
Amplitude: 0.5 to 2.0 V p-p, AC coupled.
Termination: 50 Ohm.
Connector: BNC.

Internal synthesized clock source:

Frequency: 1 Hz to 200 MHz.
Resolution: 1 Hz.
Accuracy: 10 ppm.

BURST clock:

Programmable gap: 16 Kbits maximum, 8-Bit resolution.

Pattern Generator -

PRBS: $2^N - 1$, $N = 31, 23, 15, 11, 10, 9, 7$.
Programmable word: 256 Kbits maximum, 8-Bit resolution.
Mark density: PRBS $2^{10} 1$ (1/8, 1/4, 1/2, 3/4, 7/8).
Mixed mode frame: 256 Kbits maximum, 8-Bit resolution.
Error injection:

Error: Single, Rate, External (TTL).
Field select: Overhead, payload or both.
Error rates: Error rate of 10^{-n} , $n = 3, 4, 5, 6, 7$.

Outputs -

Data and clock outputs:

Format: NRZ.
Configurations: Differential (True/Complement).
Source impedance: 50 Ohm.
Connector: BNC.
Amplitude: 0.5 V to 2.0 V, 10 mV step.

Offset, 50 Ohm to GND: -2.0 V to +1.8, 10 mV step
(termination to 50 Ohm will increase the range for PECL).
Data delay range: ± 1.0 ns, 20 ps resolution.
Rise/fall time: 300 ps typical, 500 ps maximum (20 to 80%).

Pattern sync output:

Signal level: 250 mV_{p-p} into 50 Ohm load.

Auxiliary -

Data inhibit input: ECL, 50 Ohm to -2 V, BNC.
Clock disable input: ECL, 50 Ohm to -2 V, BNC.

ANALYZER

Data and Clock -

Data and clock inputs:

Clock input: External or internal from generator.
Data polarity: True/invert selectable.
Input mode select: Single-ended or differential.
Termination select: 50 Ohm to -2 V, +3 V, AC or GND.
Input range: ECL, TTL, PECL compatible.
Threshold resolution: 10 mV step.
Threshold resolution: 10 mV step.

Synchronization -

Auto search: Clock and data threshold, clock and data timing skew, data pattern and polarity.

Measurements -

Frequency: 1 Hz to 200 MHz.
Bit errors: Window, Totalize, Timed Test, Simultaneous 1's, 0's and All Errors.
BER test field: Overhead, payload or both.
Propagation delay: Up to 128 Kbits.
Eye-width: Up to 32 ns.

Reference Data Patterns -

Identical to Pattern Generator but independent.
Startup delay: 0 to 64 Kbits programmable.

Auxiliary Signals (BNC Connectors) -

Error count inhibit input: ECL, 50 Ohm to -2 V.
Error detect output: RZ, TTL, 50 Ohm source.
Analyzer clock disable: ECL, 50 Ohm to -2 V.
Data delay output: ECL, 50 Ohm source.

Common Characteristics

Pattern -

Controls: Start/Stop, Pause/Resume or Single Step.
Save/Load:

Floppy disk: 3.5 in.
Internal storage: 2 Mbits.

Pattern Editor Software requires PC running Windows 3.1 or above.

Remote Interface -

GPIB: IEEE 488.2 compatible.
 RS-232C: DB9 connector.
 Parallel printer: DB25 connector.
 Monitor: DB15, VGA Analog Output.

Environmental -

Operating temperature: 5 to 40°C.
 Storage temperature: -10 to 60°C.
 Meets European Community EMC Directive 89/336/EEC for electromagnetic compatibility.

Safety -

UL1244, CSA231, EN61010-1, IEC61010-1.

Power -

AC line: 100 to 120 V AC, 200 to 240 V AC.
 Power consumption: 300 W maximum.

Physical Characteristics

Dimensions	mm	in.
Height	203.2	8
Width	355.6	14
Depth	508	20
Weight	kg	lbs.
Net	13.6	30

 [Top of Page](#)

[Features](#)

[> Specs](#)



Product(s) complies with IEEE Standard 488.2-1987.



Tektronix Measurement products are manufactured in ISO registered facilities.



49A-10733-3p350, 06/1997, 09/01/1999

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at [artisanTG.com](https://www.artisanTG.com) for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisanTG.com | [artisanTG.com](https://www.artisanTG.com)

