

Warner Power OT30

## Rugged Industrial Handheld Terminal



**\$1095.00**

**In Stock**

**Qty Available: 1**

**Used and in Excellent Condition**

**Open Web Page**

<https://www.artisanng.com/80282-1>

All trademarks, brandnames, and brands appearing herein are the property of their respective owners.



Your **definitive** source  
for quality pre-owned  
equipment.

**Artisan Technology Group**

(217) 352-9330 | [sales@artisanng.com](mailto:sales@artisanng.com) | [artisanng.com](http://artisanng.com)

- Critical and expedited services
- In stock / Ready-to-ship
- We buy your excess, underutilized, and idle equipment
- Full-service, independent repair center

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

# OT30

## Rugged, Industrial Handheld Terminal



### Rugged, Operator Interface

The new compact OT30 handheld terminal with an all new architecture is built to address those complex applications that are required to meet today's challenges. The new OT30, like all Termiflex terminals, is built to withstand rugged use. The OT30 is engineered to withstand repeated drops to hard surfaces, such as concrete and to resist liquid and other contaminants, without sacrificing ergonomic detail. For protection in extremely harsh environments, Termiflex offers a rubber boot, extended temperature components, conformal coating and additional moisture resistance.

### Rugged Features Include:

**New H8/300H Hitachi CPU with 32-bit architecture**

**20, 30, 40, or 45-key sealed membrane keypad with tactile and audible response, and optional backlight**

**42-key elastomeric keypad with tactile and audible response**

**Lexan® case (chemically resistant, mechanically durable)**

**Variety of serial communication interfaces, cables, input voltages, and display options available**

**Built-in power surge protection**

### Factory Set Options

- White Electroluminescent Backlight Display/Keypad
- Keyboard LED Indicators
- Interface Cable Configuration
- Custom Logo Graphics
- Custom Keypad Graphics
- Custom Serial Number Label
- Custom Optional Label
- Emergency Stop Switch
- Wide Range Power
- VFD 4x20 Display

### Extensive Options

- Extended Temperature Operation
- Water Resistance
- EMI/RFI Operation
- Custom Cabling to your Specifications with choice of Vendor Preferred Connectors
- Custom Software and Default Settings

### Accessories

- Carrying Case
- Rubber Protective Boot
- Mounting Bracket
- Hanging Clip



COTS Military Options



COTS Military Option  
w/ E-stop



Custom Keypads

# OT30

Standard & Optional Features	Specifications
<p><b>Display</b></p> <p>4x20 STN LCD <input checked="" type="checkbox"/></p> <p>4x20 VFD <input type="checkbox"/></p> <p>8x26 STN LCD <input type="checkbox"/></p> <p>EL Backlight <input type="checkbox"/></p> <p><b>Keypad</b></p> <p>20-key Membrane <input type="checkbox"/></p> <p>30-key Membrane <input checked="" type="checkbox"/></p> <p>40-key Membrane <input type="checkbox"/></p> <p>42-key Elastomeric <input type="checkbox"/></p> <p>45-key Membrane <input type="checkbox"/></p> <p>EL Backlight (membrane only) <input type="checkbox"/></p> <p><b>Interface</b></p> <p>RS 232 <input checked="" type="checkbox"/></p> <p>RS 422 <input type="checkbox"/></p> <p><b>Power</b></p> <p>+5 VDC ± 5% <input checked="" type="checkbox"/></p> <p>+8 to +28 VDC <input type="checkbox"/></p> <p><b>Cable/Connector</b></p> <p>Case-Mounted</p> <p>RJ-12 <input checked="" type="checkbox"/></p> <p>DE-9 <input type="checkbox"/></p> <p>DA-15 <input type="checkbox"/></p> <p>Integral Cable (10 ft, 3 m)</p> <p>6-conductor, coiled <input type="checkbox"/></p> <p>6-conductor, straight <input type="checkbox"/></p> <p>10-conductor, coiled <input type="checkbox"/></p> <p>10-conductor, straight <input type="checkbox"/></p> <p>Cable Connector</p> <p>DE-9P <input type="checkbox"/></p> <p>BD-25 <input type="checkbox"/></p> <p>Custom <input type="checkbox"/></p> <p><b>Environmental</b></p> <p>32°F to 122°F (0°C to 50°C) <input checked="" type="checkbox"/></p> <p>4°F to 158°F (-20°C to 70°C) <input type="checkbox"/></p> <p>Moisture Resistance <input type="checkbox"/></p> <p><b>Other Options</b></p> <p>E-stop Switch <input type="checkbox"/></p> <p>VFD 4x20 Display <input type="checkbox"/></p> <p><input checked="" type="checkbox"/> Basic Unit</p> <p><input type="checkbox"/> Optional*</p>	<p><b>CPU</b></p> <p>New Hitachi H8/300H CPU with 32-bit internal architecture</p> <p>16-bit general registers</p> <p>Optimized instruction set designed for speed</p> <p>On-chip flash memory can be added for user programming</p> <p><b>Display</b></p> <p>(STN LCD technology, dot matrix alphanumeric, 5x7 pixel characters, blue, on a light gray background)</p> <p>Character Size            4x20; 0.187"H x 0.116"W (4.8mm x 3.0mm)</p> <p>                                  8x26; 0.120"H x 0.086"W (3.0mm x 2.2mm)</p> <p>User-Defined Characters 3 (4x20 Display only)</p> <p>Visual Indicators        Flashing characters</p> <p>Backlight                 White electroluminescent, optional</p> <p><b>Keypad</b></p> <p>(Sealed membrane or elastomeric)</p> <p>Number of keys            20, 30, 40 or 45 membrane, 42 elastomeric</p> <p>Programmable Keys       4, up to 16 characters each</p> <p>Key Legends                Catalog, Blank or Custom</p> <p>Response                  Tactile, Audible, Visual (local echo)</p> <p>Repeat Rate                None, Slow, Fast, Make-Break</p> <p>Backlight                 White electroluminescent, optional.</p> <p><b>Memory</b></p> <p>EEPROM storage for Configuration Parameters</p> <p><b>Interface</b></p> <p>(RS 232 or RS 422)</p> <p>Baud Rate                 150 to 19200</p> <p>Parity                      Even, Odd, Space, Mark, None</p> <p>Word Format                7 or 8 data bits, 1 or 2 stop bits</p> <p>Connector                 Unit-mounted modular 6-pin jack, DE-9P or DA-15P connector</p> <p>Cable                      Optional integral cable up to 20 ft., straight or coiled, 6-conductor (10-conductor with E-stop option), round, shielded, terminating with either stripped-and-tinned ends or a DE-9P (DB-25P with E-Stop option) connector</p> <p><b>Mechanical</b></p> <p>(Lexan® case, gray or black)</p> <p>Dimensions                6.41" x 4.3" x 1.0" (162.8mm x 107.5 mm x 25.4 mm)</p> <p>Weight                      10 oz (283.5 g)</p> <p><b>Environmental</b></p> <p>Operating Temperature    32°F to 122°F (0°C to 50°C)</p> <p>Extended Range Option    -4°F to 158°F (-20°C to 70°C)</p> <p>Storage Temperature       -22°F to 158°F (-30°C to 80°C)</p> <p>Humidity                  95% noncondensing</p> <p>Moisture/Dust Resistance   Optional</p> <p><b>Agency Compliance</b></p> <p>EN55022</p> <p>CENELEC (CISPR 22)</p> <p>FCC Class A, Part 15</p> <p>ROHS Compliant</p>
<p>*Termiflex provides full customization service for OEM customers.</p> <p>Specifications are subject to change without notice.</p>	<p>Lexan® is a registered trademark of General Electric Corporation.</p>



40 Depot Street, Warner, NH 03278 USA Tel. (603)456-4443 • Fax (603)456-3754 • info@termiflex.com • www.termiflex.com



# Artisan Technology Group is an independent supplier of quality pre-owned equipment

## Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

## We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

## Learn more!

Visit us at [artisanng.com](http://artisanng.com) for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | [sales@artisanng.com](mailto:sales@artisanng.com) | [artisanng.com](http://artisanng.com)

