

Optical Multimeter Expansion Frame



In Stock

Used and in Excellent Condition

Open Web Page

<https://www.artisanng.com/63857-1>

All trademarks, brandnames, and brands appearing herein are the property of their respective owners.



Your **definitive** source
for quality pre-owned
equipment.

Artisan Technology Group

(217) 352-9330 | sales@artisanng.com | artisanng.com

- Critical and expedited services
- In stock / Ready-to-ship

- We buy your excess, underutilized, and idle equipment
- Full-service, independent repair center

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.



(For use with the AQ2141 Optical Multimeter Expansion Frame)

ASE Unit AQ4310

- A light source unit providing high power output and high stability across a wide spectral bandwidth



General

The AQ4310 utilizes the ASE (amplified spontaneous emission) from EDF (erbium doped fiber) to provide +10dBm (typ.) high power output for a spectral of 40nm or more.

The AQ4310 is perfect for evaluation of passive optical devices with high crosstalk.


Application

- Evaluation of loss wavelength characteristics for passive optical devices (FBG, etc.).
- Polarization dependency loss (PDL) for passive optical devices (FBG, etc.).

*FBG: Fiber Bragg grating

Features


- High output level: +10dBm (typ.)
- Superlative stability: ± 0.005 dB
- Unit type can be mounted on the AQ2141



Luminous characteristics of ASE unit

Application Example

The ASE Unit is mounted in the AQ2141 Optical Multimeter Expansion Frame and used to evaluate loss wavelength characteristics for passive optical devices.



Specifications

Model	AQ4310 (155)
Center frequency [1],[2]	1550±20nm
Spectral bandwidth [1],[3]	40nm or more
Optical output level [1],[4]	+8dBm or more (+10dBm typ.)
Output level stability	
Temperature stability [5]	0.3dB or less
Time stability	Within ±0.005dB [1],[6] Within ±0.05dB[1],[7]
Optical modulation mode [8]	CW
Simple optical attenuation function [9]	0 to 6.0dB (0.1dB steps)
Polarized light blocking ratio	0.1dB typ.
Optical connector	AQ9434 [*] Universal Connector (option)
Applicable fiber	10/125 SM fiber
GP-IB [9]	Complies with IEEE-488
Operating temperature range	0 to 40°C
Dimensions	Approx. 125(W) × 72(H) × 324(D)mm
Mass	Approx. 2.5kg
Accessories	Connector protective cap: one, instruction Manual: one

- The AQ2141 optical Multimeter Expansion Frame is required to use this unit.

NOTES:

- [1] CW light, 0.0dB attenuation, SM fiber (10/125) 2m emission end.
- [2] At 25°C. Center frequency indicated for RMS (2σ, -20dB)
- [3] At 25°C. Spectral bandwidth indicated for -10dB from peak wavelength.
- [4] At 25°C.
- [5] 0 to 40°C (8 hours), 0.0dB attenuation, CW light, connector emission end.
- [6] Constant temperature, 5 minutes (one temperature between 20 and 30°C).
- [7] ± 1°C between 0 and +40°C (one hour)
- [8] Controlled by AQ2141. Chopped light output is possible, but output characteristics are not assured. Chopped light output is not square wave. The chop frequency is set at the AQ2141 to 270Hz. Settings of 1kHz and 2kHz are possible, but optical signal strength may be extremely weak.
- [9] Controlled by AQ2141.
- [10] * Is connector type. Specify FC, SC, ST, DIN or HSM-10/A. Consult your vendor or our sales office for other types.

Options

AC9434(*) Universal Adapter

Note:* is connector type. Specify FC, SC, ST, DIN or HSM-10/A. Consult your vendor or our sales office for other types.

Specifications are subject to change without notice.

ANDO ELECTRIC CO.,LTD.

19-7, KAMATA 4-chome, Ota-ku, Tokyo, 144 Japan Phone: (03)3733-1151 Fax (03)3739-7310

ANDO CORPORATION

HEADQUARTERS: 2021 N. Capital Avenue, San Jose, CA 95132, U.S.A. Phone: (408)941-0100 Fax: (408)941-0103

EAST OFFICE: 7617 Standish Place, Rockville, MD 20855, U.S.A. Phone: (301)294-3365 Fax: (301)294-3359

ANDO EUROPE B.V.

HEADQUARTERS: "Vijverdam", Dalsteindreef 57, 1112XC Diemen, The Netherlands Phone: 020-6981441 Fax: 020-6998938

NIEDERLASSUNG DEUTSCHLAND: Dachauer StraBe 340,1. OG, D-80993 Muenchen, Germany Phone: 089-1438150 Fax: 089-14381555

ANDO ELECTRIC SINGAPORE PTE.LTD.

19 Kim Keat Road #05-03, Jumbo Industrial Building, Singapore 328804 Phone: 251-1391 Fax: 251-1987

ANDO ELECTRIC INCORPORATION

5F-2, No 81, Nan-ta Road, Hsin-chu City, Taiwan Phone: (35)614131 Fax: (35)614130

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at [artisanng.com](https://www.artisanng.com) for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisanng.com | [artisanng.com](https://www.artisanng.com)

