ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Abaco Systems / SBS ASF-PCM2-1/R* at our website: ***Click HERE***



ASF-PCMCIA2

MIL-STD-1553 Interface

ASF-PCMCIA2 is a flexible interface providing a single function, dual redundant MIL-STD-1553 interface for PCMCIA. This Advanced Single Function (ASF) architecture provides independent operation as a Bus Controller (BC), Remote Terminal (RT), or dual function Bus Monitoring (BM). The MRT option allows multiple RT capability. The ASF-PCMCIA2 interface equips the PC bus system with a complete 1553 interface. This includes 1553A/1553B selections, pointer-driven transmit and receive buffers and extensive programmable event interrupts.

BC simulation structures consist of linked lists of 1553 command messages: BC-to-RT, RT-to-BC, RT-to-RT, mode code, broadcast and time delay block transmissions. We define RT simulation as a simple series of pointers to RT definition tables. The RT definition tables in turn point to control data buffers. We define the bus activity we want to monitor in both the Map and Sequential monitoring modes. This provides user defined linked lists of data buffers and sequential 1553 activity. The user can time stamp and/or double buffer the 1553 activity. Both monitoring modes perform broad error monitoring. They also provide a comprehensive error table that the host processor can read at any time.

Hardware Overview

Abaco bases the ASF interface upon an advanced high-speed DSP, programmable logic and dual port RAM. It delivers a highly reliable hardware platform that is feature rich and user friendly. Through the 128 kB of dual port RAM, the host processor has access to set up, monitor, and change the 1553 interface data structures at any time. Link-list memory architecture allows the user to structure interface memory usage for the maximum in flexibility and usefulness.

Software Support Overview

Abaco distributed software includes host processor device drivers to the dual port control and data structures as well as an application layer to these structures. Abaco also provides low-level drivers for most operating systems, and the Integrated Avionics Library with source code, with the interface at no additional cost.

FEATURES:

- 1 dual redundant 1553 channel featuring 100% independent operation as one of the following:
  - Bus Controller
  - Remote Terminal
  - Dual Function Bus Monitor
- Bus Controller
  - Programmable frame lists
  - BC-RT, RT-BC, RT-RT
  - Mode codes, broadcasts, and time delays
- RT Functionality
  - RT level protocol selection
  - RT definition tables
  - Programmable response time
  - Optional multiple RT support
- Bus Monitor
  - Map monitoring
  - Sequential monitoring
  - Time stamped
  - Double buffered
  - Error tables
  - Definable monitoring
- Architecture
  - On-the-fly data structures
  - BC and RT linked lists
  - High-speed DSP
  - Flexible memory structure
- Software Support
  - Complimentary drivers for most operating systems
  - Integrated Avionics Library, including source code

abaco SYSTEMS

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

ASF-PCMCIA2 *MIL-STD-1553 Interface*

Specifications

ASF Functionality: Bus Controller (BC)
- BC retry
- Minor frame timing and message scheduling
- Intermessage gap selectable
- Programmable delay gaps and null BC blocks
- Multiple BC data buffers in a linked list structure
- Programmable RT no-response time-out

Remote Terminal (RT)
- RT and all subaddresses supported
- Transmit/Receive buffers for each subaddress
- Multiple RT data buffers in a linked list structure
- Programmable RT response time and no-response selection

Map Monitoring
- Multiple linked buffers for each transmit/receive subaddress
- Mapped buffers read by host processor as time permits
- Number of buffers per transmit/receive subaddress is programmable or user definable to account for various host speeds

Sequential Monitoring
- Host driver selected messages are double buffered
- Messages time stamped with a 1 µs 32-bit clock or optional 48-bit IRIG-B clock
- Standard firmware performs broad error monitoring
- Comprehensive error table readable at any time by host processor

Self Test
- Power-up test with status register report
- BIT-RAM and encoder/decoder test
- Run-time health status register
- Unit Test application for 1553 bus functionality

PCMCIA Functionality
- PCMCIA bus
- D16 transfer modes
- Memory mapped
- Port addressing
- Selectable interrupt request

Interface Connections
- Coupling harness
- Coupling harness to bus and I/O connectors
- BJ77F Triax connector to 1553 bus
- Strain relief connector included

Interface Card Specifications
- Maximum power consumption:
  - 5 V @ 750 mA
- Standard commercial operating temperature: 0°C to +60°C; ≤ 95% rH non-condensing
- Mechanical: Type II PCMCIA
  - Levngth 3.38" Height 2.12"
  - Thickness 0.2"

Software and Documentation Support
- Low-level drivers for most operating systems
- Integrated Avionics Library with source code
- Borland and Microsoft® C Compiler compatible
- Hardware and Integrated Avionics Library documentation included on CD. Hard copies of the documentation are available upon request.

Customer Support
- Two-year warranty
- Extended warranties available
- Driver and library upgrades
- Over 18 operating systems supported on various platforms

Configurations

Model Number	Configuration
ASF-PCM2-1/R	Single Channel 1553 to PMC interface
MRT	Multiple RT capability (add /MRT to product number)

WE INNOVATE. WE DELIVER. YOU SUCCEED.

Americas: 866-OK-ABACO or +1-866-652-2226 **Asia & Oceania:** +81-3-5544-3973
Europe, Africa, & Middle East: +44 (0) 1327-359444
Locate an Abaco Systems Sales Representative visit: abaco.com/products/sales
abaco.com @AbacoSys

©2016 Abaco Systems. All Rights Reserved. All other brands, names or trademarks are property of their respective owners. Specifications are subject to change without notice.

01/10 A-DS-1393

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP