ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions


Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Abaco Systems / VMIC VMIVME-2200-100* at our website: ***Click HERE***

VMIVME-2200
32-Channel Mercury-Wetted/Dry Reed Relay Output Board

- Optional mercury-wetted relays
  - — 32 relays per board
  - — Contact ratings
    - – One form A per relay
    - – Power: 50 VA maximum
    - – Voltage: 350 VDC or peak AC maximum
    - – Current: 0.5 A maximum switched; 2.0 A maximum carry
- Supports 8- or 16-bit data transfers
- Nonprivileged or supervisory short I/O access
- Optional dry reed relays
  - — 32 relays per board
  - — Contact ratings
    - – One form A
    - – Power: 10 VA maximum
    - – Voltage: 200 VDC or peak AC maximum
    - – Current: 0.75 A maximum switched; 2.00 A maximum carry
- DIP switch board address selection
- Optional contact protection electronics



FUNCTIONAL CHARACTERISTICS

Compatibility: VMEbus specification compatible. Double height form factor.

Output Connector Type: Dual 64-pin connectors (DIN 41612)

Output Organization: Four output ports, 8 bits wide. Addressable to any address within short supervisory or short nonprivileged I/O map.

Addressing Scheme: Four ports individually addressable on 8- or 16-bit boundaries. Fourteen DIP switches provide unlimited short data I/O address map selection.

Data Polarity: Order as positive true or negative true

Output Circuit: One Form A contact

MERCURY-WETTED CONTACT RATINGS

Power: 50 VA maximum

Voltage: 350 VDC or peak AC maximum

Current: 0.5 A maximum switched, 2 A carry

Contact Circuit Resistance: 70 mΩ, maximum stable within ±2 mΩ over life

Life Expectancy: 1 x 10^9 operations (with proper contact protection)

Insulation Resistance: 100 MΩ, minimum over open contacts, 10,000 MΩ between coil and contacts at 100 VDC

Breakdown Voltage: 1,000 VAC, RMS, minimum 50/60 Hz across open contacts, 500 VAC, RMS, 50/60 Hz, between all other mutually insulated terminals.

Timing:
Operate: 3 ms, maximum
Release: 3 ms, maximum with nominal voltage coil suppression

DRY REED CONTACT RATINGS

Power: 10 VA maximum

Voltage: 200 VDC or peak AC maximum

Current: 0.75 A maximum switched, 2 A carry

Contact Resistance (On Impedance): 250 mΩ, maximum, initial total circuit, measured at 10 mA, 1,000 Hz

Ordering Options

June 7, 1999 800-002200-000 G	A	B	C	–	D	E	F
VMIVME-2200 –				–			

A = Data Polarity
1 = Positive True
2 = Negative True
B = Contact Protection (kΩ)
0 = No Protection
1 = 50 V at 1 A
2 = 100 V at 0.5 A
3 = 200 V at 0.25 A
C = Relay Type
0 = Mercury Wetted [1]
1 = Dry Reed

Note

1. Mercury-wetted relays are position sensitive. They must be operated in the upright position.

Connector Data

Compatible Cable Connector	Panduit No. 120-964-435
Strain Relief	Panduit No. 100-000-072
PC Board Connector	Panduit No. 120-964-033A

Note

Panduit is also known as ITW/Pancon.

For Ordering Information, Call:
1-800-322-3616 or 1-256-880-0444 • FAX (256) 882-0859
E-mail: info@vmic.com Web Address: www.vmic.com
Copyright © January 1986 by VMIC
Specifications subject to change without notice.

Life Expectancy: 100 x 10^6 operations at signal levels, 10 x 10^6 operations at full rated load

Insulation Resistance (Off Impedance): 10^{10} Ω minimum between all insulated points at 100 VDC +25 °C, 40 percent relative humidity

Dielectric Withstanding Voltage: 250 VAC, RMS, 50/60 Hz or 350 VDC across open contacts maximum, 500 VDC all other mutually insulated points.

Timing (At Nominal Voltage):
Operate: Less than one ms including bounce
Release: Less than one ms with nominal voltage Zener clamping

PHYSICAL/ENVIRONMENTAL

Temperature Range: 0 to 55 °C, operating -20 to 85 °C, storage

Relative Humidity Range: 20 to 80 percent, noncondensing

Cooling: Convection

Power Requirements: Typical 1.35, maximum 2.9

MTBF: VMIVME-2200-AB0 (mercury wetted) 56,974 hours (217E)

MTBF: VMIVME-2200-AB1 (dry reed) 40,332 hours (217E)

WARNING: Mercury-wetted relays are position sensitive. They must be operated in the upright position.

POSITIVE/NEGATIVE TRUE ORDERING INFORMATION — This board may be ordered with positive or negative true I/O options. The data conversion (inversion) is determined by the selection of data transceivers. A positive true output option causes a VMEbus logical *one* to turn the corresponding output relay on, which supplies the user with a closed contact. A negative true output option causes a VMEbus logical *one* to turn the corresponding output relay off, which supplies the user with an open contact.

TRADEMARKS

The VMIC logo is a registered trademark of VMIC. Other registered trademarks are the property of their respective owners.





Figure 1. Functional Block Diagram

VMIVME-2200
32-Channel Mercury-Wetted/Dry Reed Relay Output Board

- Optional mercury-wetted relays
  - — 32 relays per board
  - — Contact ratings
    - – One form A per relay
    - – Power: 50 VA maximum
    - – Voltage: 350 VDC or peak AC maximum
    - – Current: 0.5 A maximum switched; 2.0 A maximum carry
- Supports 8- or 16-bit data transfers
- Nonprivileged or supervisory short I/O access
- Optional dry reed relays
  - — 32 relays per board
  - — Contact ratings
    - – One form A
    - – Power: 10 VA maximum
    - – Voltage: 200 VDC or peak AC maximum
    - – Current: 0.75 A maximum switched; 2.00 A maximum carry
- DIP switch board address selection
- Optional contact protection electronics



FUNCTIONAL CHARACTERISTICS

Compatibility: VMEbus specification compatible. Double height form factor.

Output Connector Type: Dual 64-pin connectors (DIN 41612)

Output Organization: Four output ports, 8 bits wide. Addressable to any address within short supervisory or short nonprivileged I/O map.

Addressing Scheme: Four ports individually addressable on 8- or 16-bit boundaries. Fourteen DIP switches provide unlimited short data I/O address map selection.

Data Polarity: Order as positive true or negative true

Output Circuit: One Form A contact

MERCURY-WETTED CONTACT RATINGS

Power: 50 VA maximum

Voltage: 350 VDC or peak AC maximum

Current: 0.5 A maximum switched, 2 A carry

Contact Circuit Resistance: 70 mΩ, maximum stable within ±2 mΩ over life

Life Expectancy: 1 x 10^9 operations (with proper contact protection)

Insulation Resistance: 100 MΩ, minimum over open contacts, 10,000 MΩ between coil and contacts at 100 VDC

Breakdown Voltage: 1,000 VAC, RMS, minimum 50/60 Hz across open contacts, 500 VAC, RMS, 50/60 Hz, between all other mutually insulated terminals.

Timing:
Operate: 3 ms, maximum
Release: 3 ms, maximum with nominal voltage coil suppression

DRY REED CONTACT RATINGS

Power: 10 VA maximum

Voltage: 200 VDC or peak AC maximum

Current: 0.75 A maximum switched, 2 A carry

Contact Resistance (On Impedance):
250 mΩ, maximum, initial total circuit, measured at 10 mA, 1,000 Hz

Ordering Options								
June 7, 1999 800-002200-000 G	A	B	C	–	D	E	F
VMIVME-2200	–				–			

A = Data Polarity
1 = Positive True
2 = Negative True
B = Contact Protection (kΩ)
0 = No Protection
1 = 50 V at 1 A
2 = 100 V at 0.5 A
3 = 200 V at 0.25 A
C = Relay Type
0 = Mercury Wetted [1]
1 = Dry Reed

Note

1. Mercury-wetted relays are position sensitive. They must be operated in the upright position.

Connector Data

Compatible Cable Connector	Panduit No. 120-964-435
Strain Relief	Panduit No. 100-000-072
PC Board Connector	Panduit No. 120-964-033A

Note

Panduit is also known as ITW/Pancon.

For Ordering Information, Call:
1-800-322-3616 or 1-256-880-0444 • FAX (256) 882-0859
E-mail: info@vmic.com Web Address: www.vmic.com
Copyright © January 1986 by VMIC
Specifications subject to change without notice.

Life Expectancy: 100 x 10^6 operations at signal levels, 10 x 10^6 operations at full rated load

Insulation Resistance (Off Impedance): 10^{10} Ω minimum between all insulated points at 100 VDC +25 °C, 40 percent relative humidity

Dielectric Withstanding Voltage: 250 VAC, RMS, 50/60 Hz or 350 VDC across open contacts maximum, 500 VDC all other mutually insulated points.

Timing (At Nominal Voltage):
Operate: Less than one ms including bounce
Release: Less than one ms with nominal voltage Zener clamping

PHYSICAL/ENVIRONMENTAL

Temperature Range: 0 to 55 °C, operating -20 to 85 °C, storage

Relative Humidity Range: 20 to 80 percent, noncondensing

Cooling: Convection

Power Requirements: Typical 1.35, maximum 2.9

MTBF: VMIVME-2200-AB0 (mercury wetted) 56,974 hours (217E)

MTBF: VMIVME-2200-AB1 (dry reed) 40,332 hours (217E)

WARNING: Mercury-wetted relays are position sensitive. They must be operated in the upright position.

POSITIVE/NEGATIVE TRUE ORDERING INFORMATION — This board may be ordered with positive or negative true I/O options. The data conversion (inversion) is determined by the selection of data transceivers. A positive true output option causes a VMEbus logical *one* to turn the corresponding output relay on, which supplies the user with a closed contact. A negative true output option causes a VMEbus logical *one* to turn the corresponding output relay off, which supplies the user with an open contact.

TRADEMARKS

The VMIC logo is a registered trademark of VMIC. Other registered trademarks are the property of their respective owners.




Figure 1. Functional Block Diagram

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP