

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*

The APC8621 offers high channel density and modular flexibility in a half-length PCI carrier card.

PC Carriers

APC8621
PCI Bus Half-Length
IP Carrier Card

Printable PDF Version

This board interfaces industry-standard Industrial I/O Pack (IP) modules to a PCI bus on a PC-based computer system. The half-length card is ideal for use in smaller PC chassis.

Three IP module slots give you the freedom to mix a variety of I/O functions (A/D, D/A, digital in, digital out, serial I/O, etc.) on a single board. Or, combine modules of the same type for dozens of channels on a single card. Either way, the APC8621 saves your precious card slots and reduces your costs.

Select I/O modules from Acromag's offering of more than forty models or use any third-party IP mezzanine ANSI/VITA 4 modules.

Features

- Half-length card for smaller PC chassis
- Three industry-standard IP module slots
- Board resides in memory space
- Supports IP module I/O and ID spaces
- Plug-and-play carrier configuration and interrupt support
- Two interrupt channels per IP module
- Supervisory circuit reset generation
- Individually filtered and fused power

Benefits

- Quickly create custom I/O boards by mixing and matching I/O functions.
- Conveniently configure and control the I/O modules through software with full IP module register/data access.
- Easily integrate IPs with your software using OLE controls for Windows® 95/98/NT® and its object-oriented programming interface to numerous function routines.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Specifications

IP Module Compliance (ANSI/VITA 4)

Meets or exceeds all written IP specifications per ANSI/VITA 4-1995 for 8MHz operation, only.
Supports Type I and Type II ID space formats.

Electrical/mechanical interface: Supports three single-size IP modules (A-C), or one double and one single-size IP module. 32-bit IP modules are not supported.

IP module I/O space: 16 and 8-bit; supports 128 byte values per IP module.

IP module ID space: 16 and 8-bit; Supports Type I 32 bytes per IP (consecutive even byte addresses) and Type II 32 words per IP via D16 data transfers.

IP module Memory space: Not supported.
Interrupts: Supports two interrupt requests per IP and interrupt acknowledge cycles via access to IP INT space.

PCI Bus Compliance

This device meets or exceeds all written PCI local bus specifications per rev. 2.1 dated June 1995.

System base address: This board operates in memory space. It consumes 1K of memory space which includes mapping for the IP modules.

Data transfer bus: Slave with 32, 16, and 8-bit data transfer operation. 32-bit read or write accesses implemented as two 16-bit transfers to IP modules.

APC8621 write complete time:
(time from FRAME# active until LRDYi# active)
650nS typical carrier register write.
750nS typical 8-bit and 16-bit IP module write.

APC8621 read complete time:
(time from FRAME# active until LRDYi# active)
500nS typical carrier register read.
650nS typical 8-bit and 16-bit IP module read.

Interrupts (PCI bus INTA# interrupt signal):
Up to two requests sourced from each IP mapped to INTA#. Interrupt vectors come from IP modules via access to IP module INT space.

Environmental

Operating temperature: 0 to 70°C

Storage temperature: -25 to 85°C

Relative humidity: 5-95% non-condensing

Isolation: Non-isolated

Radiated field immunity (RFI): Designed to comply with EN50082-1, IEC1000-4-3 Level 3.

Electromagnetic interference immunity (EMI):
No digital upset under the influence of EMI.

Electrostatic discharge immunity (ESD):
EN50082-1, IEC1000-4-2 Level 1.

Surge immunity: EN50082-1, IEC1000-4-5 Level 2.

Electrical fast transient immunity EFT:
EN50082-1, IEC1000-4-4 Level 2.

Radiated emissions: EN50081-1 Class A.

Physical
Physical configuration: PCI 5V Card
Length: 6.600 inches (167.64 mm)
Height: 4.200 inches (106.68 mm)
Board thickness: 0.062 inches (1.59 mm)
Maximum component height: 0.380 in. (9.65 mm)
Max. height under IP modules: 0.180 in. (4.57 mm).

Connectors:
A-C (carrier field I/O): 50-pin male header

Power: +5 Volts (±5%): 110mA, typical; 150mA, max.
±12 Volts to each IP module.

Ordering Information

Terms & Conditions
Delivery

APC8621
Non-intelligent PCI bus carrier board.
Holds three IP modules.

APC8621E
Same as above plus extended temperature range (-40° to + 85°C)

Software, termination panels, cables, adapters, signal conditioning

Windows and NT are registered trademarks of Microsoft Corp.

Get Catalogs by Mail

email: sales@acromag.com
phone: 248/624-1541
fax: 248/624-9234

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP