ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions


Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Acromag / Xembedded / Xycom AcPC4620CC* at our website: *Click HERE*

Acromag
THE LEADER IN INDUSTRIAL I/O

AcPC4620 CompactPCI Non-intelligent PMC Carrier Card (air/conduction-cooled)



This board is offered in air cooled (shown above) and conduction-cooled versions for interfacing two PMC modules to a CompactPCI system.

Description

These boards provide an easy and low cost solution that enables use of a PMC mezzanine I/O module in a standard 6U CompactPCI computer system. The carrier card acts simply as an adapter to route PCI bus signals to and from the PMC module through the CompactPCI card slot edge connector. All Acromag PMC modules and those from other vendors are supported.

A PLX Technology PCI6540 transparent PCI/PCI bridge handles data transactions from the PCI bus (system host) to two PMC sites. The bridge device provides a 32/64-bit PCI interface with 33/66MHz bus frequencies.

Front-panel field I/O signal access is accommodated on air-cooled models. The carrier card's front panel cut-out provides access to a PMC module's front I/O connector. Alternatively, all I/O signals can be routed through the carrier card's rear J3 and J5 connectors

A heat frame enables conduction cooling in applications where ambient or forced air can't provide adequate cooling. This unit is ideal for airborne systems, deployment in battleground equipment, and other situations with advanced thermal management requirements.

Features

- 6U CompactPCI card
- Air and conduction-cooled models
- Holds two PMC cards
- 32 or 64-bit PCI Interface at 33 or 66 MHz
- Transparent PCI/PCI bridge for data transactions from the PCI bus to PMC module
- Rear connection I/O access
- Rear transition module available
- Supports both 5V and 3.3V signalling
- Conduction-cooled or -40 to 85°C

All trademarks are the property of their respective owners.

Specifications

Environmental

Operating temperature: -40 to 85°C for conduction cooled.

Storage temperature: -55 to 100°C.

Relative humidity: 5-95% non-condensing.

American National Standard for 2mm Connector Equipment Practice on Conduction Cooled Euroboards: ANSI/VITA 30.1-2002.

American National Standard for Conduction Cooled PMC: ANSI/VITA 20-2001(R2005).

Power (received from the CompactPCI 3U Back Plane):
3.3V DC (±5%)*: 135mA typical, 150mA max.
5.0V DC (±5%)*: 50mA typical, 70mA max.
+12V DC (+5%)**: Per PMC module.
* With no PMC module installed, +12V DC not used.
** Max. power 7.5W (total all supplies) per PMC standard.

MTBF: Call factory.

Physical: CompactPCI Carrier Cards

Configuration: 6U CompactPCI Card. 233.35 x 160mm.

Rear CompactPCI connectors: 2mm J1, J2, J3, J5 connectors.

PMC connectors: Eight 1mm connectors.

The air-cooled model (AcPC4620E) uses the standard front panel assembly with a PMC bezel cutout. The conduction-cooled model (AcPC4620CC) uses a conduction-cooled frame with wedge loks and thermo bars.

Physical: Transition Module

Configuration: Half length 6U cPCI Card. 233.35 x 80mm.

Connectors: 2mm RJ2 connector maps rear I/O signals to a SCSI-3 connector. This model also uses a standard rear front panel assembly with a SCSI-3 connector cutout.

PMC and CompactPCI bus Compliance

Meets PCI specification version 2.3, CompactPCI specification PICMG 2.3 R1.0, and PMC specification P1386.1.

Meets PCI specification version 2.3, CompactPCI specification PICMG 2.3 R1.0, and PMC specification P1386.1.

Data transfer bus: Slave with 32 bit, 16 bit, and 8 bit data transfer operation.

Interrupts: CompactPCI bus INTA# interrupt signal.

PCI interface: PLX Technology PCI6540 transparent PCI/PCI bridge for data transactions from PCI bus (system host) to PMC site. Bridge provides 32 bit 33/66 MHz PCI interface.

Ordering Information

Carrier Cards

AcPC4620CC
Conduction-cooled cPCI carrier holds two PMC modules.


AcPC4620E
Air cooled cPCI carrier holds two PMC modules.


Accessories (see accessories documentation for details)

TRANS-C4620: Transition module.

5028-432: Shielded cable, SCSI-3 68-pin connector, 2m.

5025-288: Termination panel, DIN rail mount, 68 screw terminals, SCSI-3 connector.






AcPC4620CC conduction cooled model

Acromag, Inc. • PO Box 437, Wixom, MI 48393 • Phone: 248-295-0310 • Fax: 248-624-9234 • e-mail: solutions@acromag.com • www.acromag.com


8400-515 Printed in USA 12/08 Copyright © 2008 Acromag, Inc. Data subject to change without notice


TRANS-C4620 Transition Module






5028-432 SCSI-3 Cable





5025-288 Termination Panel



8400-515 Printed in USA 12/08 Copyright © 2008 Acromag, Inc. Data subject to change without notice

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP