ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *ACTIS Computer VSBC-6872/FHE-A* at our website: ***Click HERE***

VSBC – 6872/450

SINGLE BOARD COMPUTER WITH POWERQUICC II

VME

Features

- PowerQUICC II® MPC8270
- VMEbus interface 32bits
- 128 MByte SDRAM
- 16 MByte FLASH
- 1 MByte SRAM
- 3 x Fast Ethernet ports
- 4 x multi-protocol serial ports
- One 32-bit PMC slot
- RTC & 32 kByte SRAM battery backed up
- CompactFlash
- 2 x S-ATA hard disk drive



VSBC-6872 VME PowerQUICC II Single Board Computer is based on the MPC8270 processor. This processor is rated at 855 DMIPS @ 450 MHz and includes a very efficient SDRAM controller.

One of the key features of this device is the availability of a Quad Integrated Communications Controller (QUICC). It provides a dedicated module containing a RISC CPU and DMA channels for efficiently handling a wide range of standard or proprietary communications protocols.

VME interface

The VSBC-6872 board includes a 32-bit VME interface (rev C) :

- Master : A32/A24/A16/D32/D16/D8, RMW
- Requester : RWD, ROR, FAIR, programmable request level
- Slave : A24/A16/D32/D16/D8, RMW
- Arbiter : SGL, PRI, RRS.prog. timeout
- Handler : D8(O), IH(1-7)
- Interrupter : D8(O), ROAK, I(1-7)
- Bus Timer : BTO(16 to 112)
- Mailbox functionality
- 1 MByte - SRAM shared
- DMA channel[1]

Storage features

The VSBC-6872 board provides two media storage possibilities :

- A dual S-ATA hard disk drive. [2]
- A CompactFlash extension.

Network and serial communication links

The VBSC-6872 offers a variety of on-board I/O:

- Three integrated Fast Ethernet ports (10BASE-T / 100BASE-TX).
- One RS-232 console is available for user general purpose operations.
- One RS-232, one SPI bus, and one I^2C serial links are available on an internal connector.
- Four RS-232 or RS422/485/V.35 serial ports available on the front panel.

Flexible I/O

The board also contains one 32-bit, 33/66MHz PMC[3] (PCI Mezzanine Card) site. This site can be used for system I/O, supporting industry-standard PMC cards as interfaces to a wide variety of devices

Software


Developers can take advantage of the VSBC-6872's power and performance when running major real-time operating systems (RTOS) or when deploying applications based on the low-cost, open-source Linux ™ operating system. RTOS supported by the VSBC-6872 include VxWorks® and others on request.

Note 1 : The VME DMA channel is a functionality developed by Actis Computer. It allows data transfer between the shared SRAM and an address on the VME bus.
Note 2 : Not available in industrial temperature.
Note 3 : Dependant on the MPC8270 settings

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

VSBC-6872/450

VME



Features

- Motorola PowerQUICC II® MPC8270
- 855 DMIPS @ 450 MHz
- Up to 256 MByte SDRAM
- Up to 32 MByte FLASH
- Up to 2MByte shared SRAM

Communication

- Three Fast Ethernet ports on the front panel
- One RS-232 console port on the front panel
- One RS-232 auxiliary serial port on an internal connector.
- Four high-speed serial port supporting RS-232/422/485 mode on the front panel.

Storage

- CompactFlash
- Dual S-ATA hard disk interface (S-ATA 1.0)

Peripherals

- Real-time clock & 32 kByte SRAM battery backed up
- I2C memory

JTAG port

One internal connector for direct access to the processor with third party tool.

VME interface

- Master : A32/A24/A16/D32/D16/D8
- Requester : RWD, ROR, FAIR, programmable request level
- Slave : A24/A16/D32/D16/D8
- Arbiter : SGL, PRI, RRS
- Handler : IH(1-7)
- Interrupter: I(1-7)
- Bus Timer : BTO()
- Mailbox functionality
- One DMA channel [1]

IEEE1386.1 slot

- One 32-bit PMC slot
- Up to 66 MHz compatible [3]

Environmental

Operating
- Commercial : 0 to +70 °C
- Industrial : -25°C to +85°C

Non-operating : -40°C to 85 °C

Airflow requirement	10 CFM
Relative Humidity	0 to 90 % (non-cond.)
Altitude	0 to 10'000 ft

Environmental

Dimensions	6.3 in x 9.2 in
Power	TBD
Vibration	0.5G RMS 20-2000 Hz random
Shock	20 G, 11 ms, ½ sine

ACTIS Computer SA
19 ch. Du Champ-des-Filles
CH - 1228 Plan-Les-Ouates, Switzerland
Tel: +41 (22) 706 1830
Fax: +41 (22) 794 4391

ACTIS Computer Inc
6202 South Maple Ave, Suite 120
Tempe, Arizona 85283,USA
Tel: (480) 838 1799
Fax: (480) 838 4477

Distributed by:

For ordering information, please visit our web site at www.actis-computer.com

PowerQUICC® is a registered trademark of Motorola Corp. Other products mentioned may be trademarks or registered trademarks of their respective holders. ACTIS Computer believes this information is accurate as of its publication date and is not responsible for any inadvertent errors. The information contained herein is subject to change without notice.
Copyright © 2003 ACTIS Computer.

Edition 1.8

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP