ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *ADInstruments ML119* at our website: ***Click HERE***

Octal Bridge Amp

Model No. ML119



The **Octal Bridge Amp** offers 8 bridge amplifiers in one enclosure. It is suitable for use with multiple-chamber organ baths. It provides a fast software or switch-initiated zeroing capability. Each input consists of a software-controlled, non-isolated, low-noise bridge amplifier suitable for use with strain gauges, and force and pressure transducers.

Applications:

Multichannel cardiac and smooth muscle studies *in vitro*, arterial or venous pressures.

Options available:

/D 8 pin DIN connectors
/G Grass connectors
/F Full width enclosure

Specifications:

Inputs:	8 non-isolated inputs, with differential to single-ended conversion
Input ranges:	±20 µV to ±200 mV full scale in 2:5:10 steps (combined PowerLab and Bridge Amp)
Accuracy:	0.25% with 0 - 5000 ohm input source unbalance (0.1% after calibration)
Input impedance:	>100 megohm for signals up to ±0.5 V
Low-pass filters:	2 - 100 Hz in 6 steps 4th-order Bessel
AC Coupling:	None
Noise:	<1.5 μV_{rms} referred to input, 0 - 100 Hz <0.25 μV_{rms} referred to input, 0 - 2 Hz
Temperature drift:	<0.3 µV/°C at 1 mV range

Excitation:	25 mA maximum overload indication ±4 V fixed, for /D option ±3 V fixed, for /G option
Transducer impedance:	350 - 2500 ohm for /D option 250 - 2500 ohm for /G option
Zeroing:	16-bit resolution, ±150 mV, external contact or software-controlled
Safety:	CE Meets EN60601-1 standard

Artisan Scientific - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisan-scientific.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP