

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions


Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*

CM2-SXi

CoreModule™/3SXi • *Low Cost PC/AT-compatible PC/104™ compliant CPU module*



The CoreModule/3SX*i* provides cost-effective 386SX processing power and PC/AT compatibility in a compact, preconfigured subsystem module. Within just 14 square inches of space, the CoreModule/3SX*i* includes the equivalent functions of a PC/AT motherboard plus several additional expansion cards. Cost-sensitive embedded applications that formerly required chip-based custom designs can now benefit from an off-the-shelf module powered by a 25 MHz 386SX-compatible CPU, along with hardware and software standards like PC/AT and MS-DOS compatibility.

The CoreModule/3SX*i* is designed to meet the demands of embedded systems through its extremely compact design, low power consumption, +5V-only operation, wide operating temperature range, and high reliability.

CONFIGURATION FLEXIBILITY

The CoreModule/3SX*i* can be used as a macrocomponent, plugged into a proprietary application board, or it can be combined with PC/104-compatible expansion products to form compact, highly integrated control subsystems. Multiple modules can be stacked together without the cost and space penalties of additional mounting hardware.

www.ampro.ru

CM2-SXi

SPECIFICATIONS

PC MOTHERBOARD FUNCTIONS

CPU	• 386SX-compatible, 25 MHz internal clock rate
MEMORY	• 2 or 4 Mbytes directly surface-mounted. Additional 4 Mbytes via plug-in DRAM module
SYSTEM CONTROLLERS	• 7 DMA channels (8237 equivalent) • 14 interrupt channels (8259 equivalent) • 3 programmable counter/timers (8254 equivalent)
KEYBOARD	• PC/AT-compatible keyboard port • Speaker port with 0.1 watt drive
REAL TIME CLOCK	• CMOS RAM (MC146818 equivalent); requires external 3.0 - 3.6V battery (Tadiran TL-5242/W or equivalent)
BIOS	• Award BIOS with Ampro embedded-PC enhancements

ADDITIONAL ONBOARD FUNCTIONS

SERIAL	• Two RS232 serial ports with full handshaking • One port is jumper-configurable for RS232 or RS485 • Both ports implemented using 16C550 equivalent with 16 byte data FIFOs
PARALLEL	• EPP/ECP compatible bidirectional parallel printer port
IDE	• Support for 1 or 2 IDE hard disk drives • Low profile 44 pin compact 2mm connector
FLOPPY	• Supports 1 or 2 drives
BYTEWIDE SOCKET	• Usable with 32K - 1 Mbyte EPROMs, 32K - 512K Flash EPROMs, 32K - 512K SRAMs, or 32K - 512K NOVRAMs • SRAM backup using off-board battery • Configurable as 64K, or 128 Kbyte window, addressed in the range D0000-EFFFFh • Usable with DiskOnChip2000™ read/write Flash SSD device
OEM FLASH OPTION	• Onboard 1 Mbyte OEM Flash • 960 Kbytes available for OEM use (balance used by system BIOS) • Configurable as 64 Kbyte window, addressed in the range D0000-DFFFFh or E0000-EFFFFh • SSD 5.31 Support Software converts into an in-system programmable, read-only SSD devices • OEM Flash TFFS software converts into a full read/write SSD drive (not usable simultaneously with DiskOnChip2000™)
CONFIG EEPROM	• 2K bit configuration EEPROM, with 512 bits for OEM use • Supports battery-free boot capability
WATCHDOG TIMER	• Utilizes real-time clock alarm function • Timeout triggers hardware reset or non-maskable interrupt

MECHANICAL

SIZE	• 3.6 x 3.8 x 0.9 in. (90 x 96 x 23mm); PC/104 compliant form factor (Includes stackthrough pins. Please refer to PC/104 specification for stacking and other dimensions.)
BUS	• 16-bit PC/104 bus
POWER	• Requirements (typical 25 MHz with 4 Mbytes RAM): +5V ±5% — 500 mA active / 160 mA sleep
ENVIRONMENTAL	• Operating temperature: 0° to 70° C standard; –40° to +85° C extended (special order) • 5% to 95% relative humidity, non-condensing • Storage temperature: –55° to +85° C • Weight: 3.0 oz. (85 gm)

NOTE: Contact Ampro regarding custom configurations and special order options.

www.ampro.ru

Производитель оборудования:
Ampro Computers, Inc.
5215 Hellyer Avenue, Suite 110, San Jose, California 95138, USA
Phone: +1 408-360-0200
Fax: +1 408-360-0222
Internet: www.ampro.com

Дистрибьютор в России и странах СНГ:
MicroMax Computer Intelligence, Inc.
Россия, 117638, Москва, улица Азовская, дом 6, корпус 3
Телефоны: +7 (495) 310-7666, 310-7427
Факс: +7 (495) 310-2502
Интернет: www.micromax.ru

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP