ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Adlink cPCI-6760D/P8-207* at our website: *Click HERE*

CH-04 1/25/03 3:26 PM 頁面 22

cPCI-6760D series

Fully Integrated Dual Bridge 6U CompactPCI Single Slot Low Power Pentium-III System Host CPU Module



cPCI-6760D

Highly integration design makes cPCI-6760D provides fully functionality within only single slot space. User can access plenty I/Os with Dual Ethernet ports and one PMC expansion slot on the front panel. The cPCI-R6760S superior rear I/O transition module (RTM) extends the functionality with Ultra-160 SCSI and quad-LAN, makes it as the single slot system host with maximum I/O connectivity.

Features

- PICMG 2.7 CompactPCI Dual System Slot Compliant
- Standard 6U form factor, 1-slot (4HP) wide
- Design for low power Pentium-III CPU running at FSB 100MHz
- Two 144-pin SO-DIMM sockets support up to 512MB SDRAM with optional ECC support
- Build-in housing for 2.5" low profile HDD
- Supports 14 bus-master PCI devices on CompactPCI bus by PICMG 2.7 architecture
- On-board one single size 32-bit PMC module slot
- Up to four 10/100Mb Ethernet ports with cPCI-R6760S
- External Ultra-160 SCSI interface with cPCI-R6760S
- Supports CompactFlash type-II socket via removable daughter board
- Supports self-hot-swap operation by soft triggering system power off
- WDT status indication
- Self-hot-swap status indication

Specifications

CompactPCI Standards	PICMG 2.0 R3.0; PICMG 2.1 Hot Swap R2.0; PICMG 2.7 Dual System Slot R1.0
Form Factor	6U cPCI (233.33x160mm), 1 slots (4HP) wide
CPU/Cache	Intel BGA2 mobile Pentium-III up to 850MHz with 256K on-die L2 cache
Front Side Bus Speed	100MHz
Chipset	440BX
BIOS	Award 2Mb flash memory
RAM	Two 144-pin SO-DIMM sockets, up to 512MB SDRAM with optional on-board ECC support
cPCI Bus Interface	32-bit/33MHz, support 14 bus-mastering devices, Dual TI PCI2050 PCI to PCI bridge
VGA	SMI-721 AGP-2X VGA with 4MB VRAM
LAN	10/100Mbps Ethernet by Intel 82559: dual ports on front board and additional dual ports on cPCI-R6760S rear board
IDE	UDMA-33, dual channels; built-in 2.5" ATA HDD housing on front board
Floppy	Standard 34-pin connector on RTM
Flash Disk	Flash2000 2.5" flash drive or CF Card by removable adaptor
USB	USB 1.1, 2 ports (1 for front, 1 for rear)
SCSI	LSI 53C1000R; External Ultra-160 SCSI with LVD (cPCI-R6760S)

Front Panel I/Os	COM1 (RS-232), PS2 KB+MS (combo), USB, LAN1, LAN2, VGA, PMC
Backplane (rear) I/O	J3: COM1, LPT, KB, MS, FDD, IDE1, LAN1, LAN2, Buzzer; J4/J5: cPCI Bus B (PICMG 2.7); J5: COM2, IDE2, USB, VGA
Rear I/O Module Options	cPCI-R6760D; cPCI-R6760S
Watchdog Timer	1~255 sec or 1~255 min software programmable, can generate system reset
Other Features	Intel PXE pre-boot on Ethernet Remote Console On-board LAN, H/W Monitor disable
Operating Temp.	0 to 55˚C (inside-chassis temp, CPU type dependant; external air-flow required)
Storage Temp.	-20 to 80˚C
Shock	15G peak-to-peak, 11ms duration, non-operation
Vibration	Non-operation: 1.88Grms, 5-500Hz, each axis Operation: 0.5Grms, 5-500Hz, each axis, with 2.5" HDD
Measured Power Consumption	Low Power P-III-700 & 256MB RAM: 3.8A @ +5V; 4.5A @ +3.3V; 228mA @ +12V (w/o HDD) Mobile P-III-850 & 512MB RAM with cPCI-R6760S: 6.4A @ +5V; 4.5A @ +3.3V; 228mA @ +12V (w/o HDD)
Certificate or Test	CE; FCC class B; HALT

Rear I/O Transition Modules

Model number	Board Depth	Faceplate I/O	On-board I/O
cPCI-R6760D	80 mm	COM2 (RS-232/422/485), LPT, KB, MS, USB, VGA, LAN1, LAN2	COM1 (10-pin), FDD (34-pin), IDE1 & IDE2 (40-pin), Buzzer
cPCI-R6760S	80 mm	COM2 (RS-232/422/485), KB&MS, USB, LAN1~4, SCSI (external 68-pin)	COM1 & COM2 (10-pin), LPT (26-pin), FDD (34-pin), IDE1 & IDE2 (40-pin), Buzzer, VGA (15-pin

Ordering Information

Model number	Description/Configuration
cPCI-6760D/P7	6U cPCI Single Slot Low Power P-III-700 System Host CPU Module with VGA, Dual LAN, PMC Slot and DB-6760CF
cPCI-6760D/P8	6U cPCI Single Slot Low Power P-III-850 System Host CPU Module with VGA, Dual LAN, PMC Slot and DB-6760CF
cPCI-R6760D	Standard Rear I/O Transition Module for cPCI-6760D
cPCI-R6760S	Superior Rear I/O Transition Module for cPCI-6760D with Ultra-160 SCSI and Additional Dual LAN
DB-6760CF	Removable CompactFlash Type-II Socket Adaptor for cPCI-6760D

Note 1: Front CPU modules and rear I/O transition modules are sold separately
Note 2: CPU is soldered, RAM or HDD are not included

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP