ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Adlink cPCI-3840AMT/PM16/M1G-2110* at our website: *Click HERE*

cPCI-3840 Series

3U CompactPCI® Intel® Pentium® M Processor Module



Features

- *Low power consumption Intel® Pentium® M Celeron® M Processor up to 2 MB L2 cache*
- *Up to 2 GB PC2700 DDR-SDRAM*
- *Dual Gigabit Ethernet ports, USB 2.0*
- *Multiple storage interfaces: IDE, CompactFlash® Serial ATA*
- *Multiple display interfaces: CRT and DVI on RTM*
- *AC'97 audio line out and microphone input*

Ordering Information

cPCI-3840/P16/M512/H40G	3U cPCI Pentium® M 1.6 GHz CPU module with 512 MB DDR RAM and 40 GB HDD
cPCI-3840/P16/M1G/H40G	3U cPCI Pentium® M 1.6 GHz CPU module with 1 GB DDR RAM and 40 GB HDD
cPCI-R3840	Rear Transition Module for cPCI-3840, 50 mm

Note: Contact us for more CPU, memory and HDD options.

Peripheral Connectivity

Function	cPCI-3840		cPCI-R3840	
	Face-plate	On-Board	Face-plate	On-Board
Serial Port	Y (DB-9)	--	Y (DB-9)	--
USB	Y x 2	--	Y	--
Gigabit Ethernet	Y (RJ-45)	--	Y (RJ-45)	--
IDE	--	Y (44-pin)	--	--
General Purpose LED	Y	--	--	--
Reset button	Y	--	--	--
Speaker Out	Y	--	--	--
MIC In	Y	--	--	--
VGA	Y	--	--	--
SATA	Y	Y	--	--
SATA Power Connector	Y	--	--	--
CF Socket	--	Y	--	--
DVI-D	--	--	Y	--

Specifications

CPU / Chipset / RAM

CPU	Intel® Pentium® M processor 1.8 GHz with 2 MB L2 cache
	Low Voltage Intel® Pentium® M processor 1.1 GHz or 1.6 GHz with 1 MB L2 cache
	Intel® Celeron® M processor 1.3 GHz with 512 KB L2 cache
	Ultra Low Voltage Intel® Celeron® M Processor 600 MHz with 512 KB L2 cache
FSB	400 MHz
Chipset	Intel® 855GME with 6300ESB I/O Controller Hub
RAM	Two 200-pin SODIMM sockets for PC2700 DDR-SDRAM. Up to 2 GB

Bus

Standards	PICMG® 2.0 R3.0, PICMG® 2.1 R2.0
CompactPCI® Bus	32-bit/33 MHz PCI™ bus

I/O Interfaces

Display	Intel® 855GME Integrated Graphics with 32 MB UMA
	DB15 VGA interface on front panel
	DVI on the cPCI-R3840 RTM
Ethernet	Intel® 82546EB Dual-Port Gigabit Ethernet Controller
	One GbE port is on front panel
	Second GbE port is on J2 for rear I/O
IDE	Ultra ATA100/66/33, primary IDE 44-pin IDE connector and CompactFlash socket
Serial ATA	One on-board S-ATA 150 connector
USB	Four USB 2.0 ports: Two USB 2.0 ports on front panel, one on-board
	One USB 2.0 port on J2 for rear I/O
Serial COM	RS-232 DB-9 connector (COM1) on front panel
	RS-232 DB-9 connector (COM2) on J2 for rear I/O
Audio	Line out and Microphone input audio jacks

Other Features

Watchdog Timer	Two stages, SMI/SCI before RESET
LED	Four LEDs: Power, IDE, Hot-swap/GP LED, and WDT/GP LED
Hardware Monitoring	CPU temperature monitoring, over-temperature throttling, +5 V, +3.3 V, +12 V, Vcore voltages monitoring
Operating System Compatibility	Windows® 2000/XP/XP Embedded, Red Hat® Linux® 9.0

Mechanical and Environmental

Form Factor	3U CompactPCI®
Dimensions	100 mm x 160 mm (L x W), dual-slot width
Operating Temp.	0˚C to 55˚C (internal chassis temp, external air flow required)
Storage Temp.	-20˚C to 80˚C
Shock	15 G peak-to-peak, 11ms duration, non-operation
Vibration	Non-operation: 1.88 Grms, 5-500 Hz, each axis
	Operation: 0.5 Grms, 5-500 Hz, each axis
Measured Power Consumption	24 W (5 V @ 3.16 A, 3.3 V @ 2.4 A) (1.6 GHz Pentium® M CPU, 512 MB RAM, 40 GB HDD)
Compliance	CE, FCC Class A

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP