ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

**Artisan Technology Group**
(217) 352-9330 | sales@artisantg.com | artisantg.com

**Full-service, independent repair center**
with experienced engineers and technicians on staff.

**We buy your excess, underutilized, and idle equipment**
along with credit for buybacks and trade-ins.

**Custom engineering**
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

**Expert team | Trust guarantee | 100% satisfaction**

All trademarks, brand names, and brands appearing herein are the property of their respective owners.


Find the *Adlink PCIe-7296* at our website: ***Click HERE***


# PCI/PCIe-7296/7248, PCI-7224

## 96/48/24-CH Opto-22 Compatible DIO Cards


PCI-7224


PCI-7296


PCI-7248


PCIe-7296


PCIe-7248

## Features

- **Supports a 32-Bit 5 V PCI bus (PCI-7224/7248/7296)**
- **x1 PCI Express® interface (PCIe-7248/7296)**
- **96-CH digital TTL/DTL inputs/outputs (PCI/PCIe-7296)**
- **48-CH digital TTL/DTL inputs/outputs (PCI/PCIe-7248)**
- **24-CH digital TTL/DTL inputs/outputs (PCI-7224)**
- **Emulates 4/2/1 industry standard 8255 PPI (mode 0)**
- **Direct interface with OPTO-22 compatible I/O modules**
- **Output status read back**
- **Onboard 8254 timer/counter chip**
- **One 32-Bit timer for timed interrupt generation**
- **One 16-Bit event counter to generate event interrupt**
- **Programmable interrupt sources**
- **+12 V and +5 V power available on OPTO-22 connectors**
- **Onboard resettable fuses for power output protection**
- **Compact, half-size PCB**

Supported Operating System

- Windows 2008 R2, 7/8 x64/x86, Linux

Driver and SDK

- LabVIEW, MATLAB, C/C++, Visual Basic, Visual Studio.NET

Software Utility

- AD-Logger

## Specifications

### Digital I/O

- Number of channels
  - 96 inputs/outputs (PCI/PCIe-7296)
  - 48 inputs/outputs (PCI/PCIe-7248)
  - 24 inputs/outputs (PCI-7224)
- Compatibility: 5 V/TTL
- Digital logic levels
  - Input high voltage: 2-5.25 V
  - Input low voltage: 0-0.8 V
  - Output high voltage: 2.4 V minimum
  - Output low voltage: 0.5 V maximum
- Output driving capacity
  - Source current: 2.6 mA for port A & B, and 15 mA for port C.
  - Sink current: 24 mA
- Data transfers: programmed I/O

### General Specifications

- I/O connector
  - 50-pin ribbon male x 1 (PCI-7224)
  - 50-pin ribbon male x 2 (PCI/PCIe-7248)
  - 50-pin ribbon male x 4 (PCI/PCIe-7296)
- Operating temperature: 0°C to 60°C (32°F to 140°F)
- Storage temperature: -20°C to 80°C (-4°F to 176°F)
- Relative humidity: 5% to 95%, non-condensing
- Power requirements

| Device | Power Consumption |
|---|---|
| PCI-7296 | 860 mA @ 5 VDC Typical |
| PCI-7248 | 500 mA @ 5 VDC Typical |
| PCI-7224 | 330 mA @ 5 VDC Typical |
| PCIe-7248 | 350 mA @ 12 VDC Typical |
| | 280 mA @ 3.3 VDC Typical |
| PCIe-7296 | 590 mA @ 12 VDC Typical |
| | 280 mA @ 3.3 VDC Typical |

- Dimensions (not including connectors)
  - 148 mm x 102 mm (5.77" x 3.97") (PCI-7248 and PCI-7224)
  - 166 mm x 102 mm (6.55" x 3.97") (PCI-7296)
  - 168 mm x 112 mm (6.55" x 4.36") (PCIe-7248/7296)

## Terminal Boards

- TB-24R-01*
  Terminal Board with 24-CH Relay Outputs
- TB-24P-01*
  Terminal Board with 24-CH Isolated Digital Inputs
- TB-16P8R-01*
  Terminal Board with 16-CH Isolated DI & 8-CH Relay Outputs
- DIN-24R-01*
  Terminal Board with 24-CH Relay Outputs
- DIN-24P-01*
  Terminal Board with 24-CH Isolated Digital Inputs and DIN-Rail Mounting

* **For more information on mating cables, please refer to P3-48/49.**

## Ordering Information

- **PCI-7296**
  96-CH Opto-22 Compatible DIO Card
- **PCI-7248**
  48-CH Opto-22 Compatible DIO Card
- **PCI-7224**
  24-CH Opto-22 Compatible DIO Card
- **PCIe-7248**
  48-CH Opto-22 Compliant PCIe DIO Card
- **PCIe-7296**
  96-CH Opto-22 Compliant PCIe DIO Card

**Note:**
**The PCI-7224 is the 24-CH version of the PCI-7248. The software drivers of the PCI-7224 are exactly the same as those of the PCI-7248**

Updated September 23, 2014. ©2014 ADLINK Technology, Inc. All Rights Reserved. All specifications are subject to change without further notice.

**Artisan Technology Group** is an independent supplier of quality pre-owned equipment

## Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

## We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

## Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP