

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*

PCIe-7350

50 MHz 32-CH High-Speed Digital I/O Card



Features

- **x1 lane PCI Express® Interface**
- **Maximum 50 MHz clock rate from internal timer or 100 MHz from external clock**
- **200 MB/s maximum throughput**
- **Software selectable voltage level of 1.8 V, 2.5 V, and 3.3 V**
- **16-steps phase shift in external clock mode**
- **Per group (8-Bit) input/output direction selectable**
- **Supports I^2C and SPI programmable serial interfaces for external device communication**
- **Scatter-gather DMA support**
- **Flexible handshaking and external digital trigger modes**
- **8-channel auxiliary programmable I/O**

Supported Operating System

- Windows 7/8 x64/x86, Linux

Driver and SDK

- LabVIEW, MATLAB, C/C++, Visual Basic, Visual Studio.NET

Specifications

Digital I/O

- Number of channels:
  32, per group (8-channel) input/output direction selectable
- Logic levels: 1.8 V, 2.5 V, 3.3 V (software selectable)
- Power-up status: All digital inputs
- Impedance:
  - Input: 10 kΩ
  - Output: 50 Ω
- Input protection: -1 to 6 V
- Data transfer: Programmable I/O, bus-mastering DMA with scatter-gather
- Maximum data transfer rate: 200 MB/s
- Digital logic levels:

Logic Levels		1.8 V	2.5 V	3.3 V
Digital Input	Min. input high voltage	1.2 V	1.6 V	2 V
	Max. input low voltage	0.63 V	0.7 V	0.8 V
Digital Output	Min. output high voltage	1.6 V	2.3 V	3.1 V
	Max. output low voltage	0.2 V	0.2 V	0.2 V
	Max. output driving current	8 mA	16 mA	32 mA

Clocking mode

- Internal clock: Max. 50 MHz (100 MHz / N; 2<N<65535)
- External clock: Max. 100 MHz (support 8/16-Bit data width only, data throughput must be less than 200 MB/s)
- Handshaking
- Burst handshaking

Trigger sources

- Software trigger
- External digital trigger: AFI[0…7]

Trigger modes

- Post trigger, Retrigger, Pattern match, Handshaking

Change of State Interrupt

- Interrupt sources: Any of 32 channels or a pre-define channel Change-of-State

Application Function I/O

- Number of channels: 8
- Supporting modes: static I/O, I^2C or SPI master node, external clock input/output, external digital trigger input, handshaking

Terminal Boards & Cables

DIN-68H-01

Terminal Board with One 68-pin SCSI-VHDCI Connector and 0 or 50 Ω Jumper Selectable Impedance (Cables are not included.

ACL-10279

68-pin SCSI-VHDCI Cable with 50 Ω Impedance

SMB-SMB-1M

SMB to SMB Cable, 1M

* **For more information about mating cables, please refer to P3-48/49.**

Ordering Information

PCIe-7350
50 MHz 32-CH High-Speed Digital I/O PCI Express® Card

Updated September 23, 2014. ©2014 ADLINK Technology, Inc. All Rights Reserved. All specifications are subject to change without further notice.

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP