

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*

PCIe-8560/PXI-8565

PCI Express Control of PXI/CompactPCI



PCIe-8560



PXI-8565

Introduction

The PCI Express-to-PXI/CompactPCI expansion kit provides control of PXI/CompactPCI modules installed in a PXI/CompactPCI expansion system using high-bandwidth PCI Express technology. With comprehensive hardware and software transparency, the expansion kit enables fast and convenient detection of any installed PXI/CompactPCI cards in the expansion system, without requiring additional drivers or software installation.



Controlling PXI™/CompactPCI® with PCI Express®

The PCIe-8560 and PXI-8565 PCI Express-to-PXI/CompactPCI expansion kit provides additional PXI slots to the host computer by implementing a PCI Express-based control of PXI/CompactPCI modules. The technology consists of a PCIe-8560 card installed in the host computer, a shielded cable, and the expansion system with the 3U (Eurocard) PXI-8565 expansion module. The PCIe-8560 comes in a PCI Express x1 footprint and converts PCI Express signals to a PCI bridge that supports seven 32-bit/66 MHz PXI/CompactPCI modules.

Controlling 6U CompactPCI®/PXI™ Modules

For applications requiring control of 6U PXI or CompactPCI modules through PCI Express, ADLINK provides the PXI-8565/6U, the 6U version of PXI-8565. The PXI-8565/6U provides the exact same features as PXI-8565 but in a 6U CompactPCI/PXI form factor. The product package includes one PCIe-8560 to plug into a host PC, one PXI-8565/6U for the remote 6U CompactPCI/PXI chassis, and one ACL-EXPRESS-1/3/7 expansion cable.



PCIe-8560



PXI-8565



PXI-8565/6U

Features

- **PCI Express-based control of PXI/CompactPCI**
- **High-speed PCI Express x1 interface**
- **Direct control of PXI/CompactPCI systems**
- **Supports 32-bit/66 MHz PCI™ interface**
- **Expansion distance of up to 7 meters (expansion cables at 1 M, 3 M, and 7 M)**
- **Comprehensive hardware and software transparency**
- **Compliant with**
  - **PCI Express® Base Specifications Rev. 1.0a**
  - **PXI™ Specifications Rev. 2.2**
  - **PCI-to-PCI Bridge Architecture Specifications Rev. 1.2**
  - **PCI™ Local Bus Specifications Rev. 3.0**

General Specifications

- Operating temperature: 0°C to 50°C (32°F to 122°F)
- Storage temperature: -20°C to 80°C (-4°F to 176°F)
- Relative humidity: 10% to 90%, non-condensing

Certification

- EMC/EMI: CE, FCC Class A

Ordering Information

- **PCI Express-to-PXI Expansion Kit**
  Includes One PCIe-8560, One PXI-8565, and One ACL-EXPRESS-3 Cable
- **PCIe-8560**
  PCI Express-to-PXI Expansion Interface Card for host PC
- **PXI-8565**
  PCI Express-to-PXI Expansion Interface Card for 3U CompactPCI/PXI Chassis
- **PXI-8565/6U**
  PCI Express-to-PXI Expansion Interfce Card for 6U CompactPCI/PXI Chassis
- **ACL-EXPRESS-1**
  High-speed Expansion Cable, 1 M
- **ACL-EXPRESS-3**
  High-speed Expansion Cable, 3 M
- **ACL-EXPRESS-7**
  High-speed Expansion Cable, 7 M

Specifications

PCIe-8560

- PCI Express Base Specifications Rev. 1.0a compliant
- PCI Express x1 link with 250 MB/s data throughput
- Extended distance of up to 7 meters
- Dimension: Low-profile PCI Express card 69 mm (H) x 87 mm (W) (2.69" x 3.39")
- Power requirement:

Device	+3.3 V
PCIe-8560	210 mA (max)

PXI-8565, PXI-8565/6U

- PXI™ Specifications Rev. 2.2 compliant
- PCI-to-PCI Bridge Architecture Specifications Rev. 1.2 compliant
- PCI™ Local Bus Specifications Rev. 3.0 compliant
- Supports 32-bit/66 MHz PCI™ interface
- Internal arbiter supports up to 7 external masters
- Up to seven PCI clock/bus requests
- Extended distance of up to 7 meters
- Dimensions: PXI-8565: 175 mm (W) x 107 mm (H) (6.82" x 4.17")
  PXI-8565/6U: 175 mm (W) x 233.35 mm (H) (6.82" x 9.1")
- Power requirement:

Device	+3.3 V
PXI-8565, PXI-8565/6U	720 mA

ACL-EXPRESS-1/-3/-7

- Length: 1 M, 3 M, 7 M

Updated September 23, 2014. ©2014 ADLINK Technology, Inc. All Rights Reserved. All specifications are subject to change without further notice.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

ADLINK Technology:

PCIe-8560

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP