

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Adlink PXI-3800/PM18+* at our website: ***Click HERE***

PXI-3800 Series

3U PXI Intel® Pentium® M System Controllers with VGA/GbE/CF



Introduction

The ADLINK PXI-3800 series system controller complies with PXI specifications Rev. 2.2 and features up to 1.8 GHz Pentium® M CPU support, hot swappable CompactFlash card, USB 2.0 ports, and Gigabit Ethernet. By using an Intel® Embedded Pentium® M CPU and Intel® 855GME chipset, the PXI-3800 provides both long life and excellent driver support to meet the majority of industrial applications. In addition to its rugged, industrial package, the PXI-3800's extraordinary reliability, high computing performance, and low power consumption make it ideal for test and measurement applications in harsh environments.

■ Notice:

These PXI™ controllers implement rear I/O. PXI™ controllers with rear I/O are designed to operate with a matching rear transition module which provides internal or external chassis I/O.

■ Warning:

If these PXI™ controllers are used with a chassis that contains a rear transition module that does not match the controller, the rear I/O functionality may not operate and may cause damage to the PXI™ controller or the rear transition module.

Features

- **PXI specifications Rev. 2.2 compliant**
- **Intel® Pentium® M processor, FSB 400 MHz, CPU frequency up to 1.8 GHz**
- **Two 200-pin DDR SO-DIMM sockets supporting up to 2 GB RAM**
- **One 44-pin EIDE (primary IDE) with build-in 2.5 low-profile HDD (40 GB, min.)**
- **Two CompactFlash interfaces for HDD and FDD replacement; CF2 supports hot swappable CF card functionality**
- **I/O interface**
  - **One 10/100/1000 Mb Ethernet port**
  - **Two USB 2.0 Ports**
  - **Two RS-232/422/485 ports**
  - **One parallel port**
  - **VGA output supporting 1280 x 1024 resolution**
  - **One AC97 stereo audio output**
  - **Trigger I/O for advanced PXI trigger functions**
- **Programmable watchdog timer**

Ordering Information

- **PXI-3800/PM18+**
  3U PXI Pentium® M 1.8 GHz System Controller with 2 GB Memory & 80 GB HDD
- **PXI-3800/PM18**
  3U PXI Pentium® M 1.8 GHz System Controller with 512 MB Memory & 40 GB HDD
- **PXI-3800**
  3U PXI Pentium® M 1.6 GHz System Controller with 512 MB Memory & 40 GB HDD
- **PXI-3800/CM13**
  3U PXI Celeron® M 1.3 GHz System Controller with 512 MB Memory & 40 GB HDD

Specifications

Model Name	PXI-3800/CM13	PXI-3800	PXI-3800/PM18	PXI-3800/PM18+
Core Features				
CPU	Intel® Celeron® M 320 1.3 GHz	Intel® Pentium® M 747 1.6 GHz	Intel® Pentium® M 745 1.8 GHz	Intel® Pentium® M 745 1.8 GHz
FSB	400 MHz			
Chipset	Intel® 855 GME Graphic Memory Control HUB Intel® 6300ESB I/O Controller Hub			
Memory	512 MB DDR RAM (Two 200-pin SO-DIMM sockets support up to 2 GB memory)			2GB DDR RAM
Display				
CRT	Analog CRT route to VGA connector on the faceplate up to 1280 x 1024 resolution			
LVDS (For rear I/O only)	Single channel LVDS via DVO to LVDS controller up to 1280x1024 resolution			
Interface	One analog VGA DB-15 connector on the faceplate			
I/O Connectivity				
Hard Drive	40 GB IDE hard drive, 5400 RPM			80 GB IDE hard drive, 5400 RPM
IDE port	One 44-pin ATA-33 EIDE interface for external IDE device			
Ethernet	On board Intel® 82545EM Gigabit Ethernet controller One RJ-45 connector with speed/link/active LED on the faceplate			
USB	Two USB 2.0 ports on the faceplate			
Serial Port	Two 16C550 UART compatible COM ports on the faceplate COM1 is RS-232/422/485 jumper selectable			
LPT port	One high-speed bi-directional SPP/EPP/ECP parallel port			
PS2 Keyboard/Mouse	One PS2 KB/MS connector on the faceplate			
Audio	AC97 audio output on faceplate			
Trigger I/O	SMB connector on the faceplate to route an external trigger signal to/from PXI™ trigger bus			
CompactFlash Socket	Two CompactFlash type II sockets. CF1 is based on internal primary IDE interface. CF2 is hot-swappable interface on the faceplate			
Mechanical and Environmental				
Dimensions	3U PXI™ module 60.5 mm x 128.7 mm x 213.2 mm			
Slot Requirements	1 system slot plus 2 controller expansion slots			
Weight	0.9 kg			
Operating Temp.	0 to 55°C			
Storage Temp.	-20 to 80°C			
Relative Humidity	5 to 95%, non-condensing			
Shock	30 G, half-sine, 11 ms pulse duration			
Vibration	Operating: 5 to 500 Hz, 0.5 G_{RMS}, 3 axes			
	Non-operating: 5 to 500 Hz, 2.46 G_{RMS}, 3 axes			
Emissions Compliance	EN 55022 FCC Class A			
CE Compliance	Immunity: EN 55024			

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP