

E-Z Arm II

Features & Benefits

4-in. dia. arm in 5- or 8-foot lengths:

Provides for high-efficiency collection and maneuverability in tight spaces.

Strong HDPE flat base joint: Easy to install; HDPE bearing material works to seal base without collars or fittings.

Large 8-in. dia. inlet hood with 360° flange handle: Easier hood positioning than single-handle designs.

Durable rounded duct constructed of 21-ga. aluminum:

Withstands industrial use, yet lightweight for easy operation.

Hi-Flow spiral wire-reinforced hose. Provides superior strength and resistance to sparks and embers.



Options

35 Watt Halogen Light Kit: Improves worker visibility and productivity.

Damper: Shut off air flow when not in use.

Silencer: Reduces air flow noise for quieter operation.

Blowers: Several sizes available.

Wall Brackets: Maximizes installation versatility.

Adjustable Height Floor Stand: Maximum height of 120 inches adds installation versatility.

Filtration Units: HEPA, cartridge, and odor-control filter systems available based on application.

Boom Extensions: System includes aluminum boom arm, boom arm wall bracket, tube kit, and flex hose.

Specifications

Construction: 21 ga. aluminum tube with spiral wire-reinforced Hi-Flow hose

Blower Pkgs (HP): 0.75, 1.5, 3.0, 5.0, 7.5

Nominal Air Flow (CFM): 200 to 600

Weight (lbs.): E-Z Arm® II 4E05 - 9 lbs.; E-Z Arm® II 4E08 - 11 lbs.

E-Z Arm II

[View Specs & Drawings](#)

[Extraction Arms »](#)

[E-Z Arm](#)

[E-Z Arm II](#)

[E-Z Arm 2.5](#)

[Telescoping Collection Arm](#)

[Stainless Telescoping Collection Arm](#)

