



Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

*InstraView*SM REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at www.instraview.com ↗

WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. www.artisanng.com/WeBuyEquipment ↗

LOOKING FOR MORE INFORMATION?


Visit us on the web at www.artisanng.com ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

Contact us: (888) 88-SOURCE | sales@artisanng.com | www.artisanng.com



TM900

Transition Module for the C900 cPCI SBC



- **Provides Standard Connection for the C900 G4+ PowerPC® 3U cPCI SBC I/O Interfaces**
- **80 mm Module Depth Fully Compliant with IEEE 1101.11**
- **Supports Both Front Only and Front/Rear Plug-in Units Subracks**
- **Direct Rear Plug-in Unit for Subracks Supporting Rear I/O Plug-in Units**
- **Double Slot Front Transition Module Providing All C900 I/O Interfaces**
- **Single Slot Front Transition Module Providing Most C900 I/O Interfaces**
- **Complete Two Unit Kit (Rear Backplane Adapter Unit and Front Panel Transition Module Unit) With Cables for Subracks Supporting Front Plug-in Units Only**
- **High Quality Twisted Pair Flat Cable for Transition Module and Rear I/O Adapter Connection**
- **Includes no Active Components**
- **Configuration Jumpers Available for I/O Routing Configuration**

Aitech Defense Systems, Inc.

A member of the Ai-Rugged Group

9301 Oakdale Ave, Chatsworth, Ca 91311

Tel: (888) Aitech-8 (248-3248) Fax: (818) 718-9787 e-mail: sales@rugged.com web: www.rugged.com



TM900 Transition Module

Aitech's TM900 is provided as a complement to the C900 G4+ PowerPC® 3U CPCI SBC.

The transition module provides standard direct connection to all the C900 I/O interfaces and is intended for use in commercial air-cooled chassis. The TM900 eliminates the need for any harnessing and complex cabling fixtures in order to connect to the C900.

The TM900 transition module fully complies with the IEEE 1101.11 specification and supports subracks capable of front and rear plug-in units as well as subracks capable of front plug-in units only. Two kits are available supporting rear plug-in and front plug-in attachment.

The same module with different assembly options is used as the rear I/O adapter connecting to the C900 rear I/O at the backplane as well as the transition module providing all I/O connectors at the front/rear panel.

I/O connectors include: two Gigabit Ethernet ports (one port only in the single slot version), two USB ports, two serial I/O ports (one port only in the single slot version) and 8 single-ended / 4 differential Discrete I/O channels.

In addition, the transition module provides a header for each of the PMC sites of the C900 allowing attachment of cables to the PMC I/O.

Two slot size options are available for the transition module – single slot and double slot. The double slot transition module provides all C900 I/O interfaces while the single slot transition module provides all C900 I/Os with the exception of one serial port and one Gigabit Ethernet port.

The transition module also provides jumpers to allow I/O routing for the C900 shared I/O pins as well as interface type customization for serial I/O interfaces.

The following figures illustrate the TM900 location in the system. These illustrations include both the rear plug-in and front-plug in configurations.




Figure 1. TM900 Rear Plug-in Configuration




Figure 2. TM900 Front Plug-in Configuration



Functional Description

System Support

The TM900 supports both front/rear plug-in units subracks as well as subracks capable of front plug-in units only.

When using subracks capable of rear plug-in units installation, a single transition module kit is needed. In such case, it performs both as the rear I/O adapter at the backplane and the I/O connectors panel. Additional standard expansion units may be used to connect the transition module to the rear of the backplane when subracks are deeper than 80mm.

When using subracks capable of front plug-in units a complete kit is mandatory. This kit includes two transition module units (in different assembly configuration) and high quality twisted pair flat cable.

The rear I/O adapter is assembled only with 3U CPCI rear I/O connectors and flat cable headers. The transition module itself is assembled with flat cable headers and front panel standard I/O connectors.

Two form factor transition modules are available, single slot and double slot. The single slot transition module provides connectors to all C900 I/O interfaces with the exception of one serial I/O port (only serial port 0 is available) and one Gigabit Ethernet port (only LAN 0 is available). The double slot transition module provides connectors for all C900 I/O interfaces.

I/O Connectors

The transition module provides standard connectors for all the C900 I/O interfaces. These connectors include the following:

- Two USB 2.0 type A connectors
- Two modular RJ45 jacks for the two Gigabit Ethernet ports
- Two 8-pin 90° headers for 8 discrete I/O channels (4 differential pairs)
- Two 9-pin D-type connectors for the two serial I/O ports

Configuration Jumpers

Since some of the C900 I/O signals share the same I/O pins at the P2 I/O connector, the TM900 transition module provides the option to route these signals accordingly.

These shared I/O signals may be routed to the C900 I/O flat cable headers as well as front panel connectors when the SBC is configured to route its local resources to the shared I/O pins (Ethernet, Serial I/O or Discrete I/O). When the SBC is configured to route these shared I/O pins to the PMC I/O, the transition module may be configured to route these signals to the PMC I/O flat cable headers.

Mechanical Features


The TM900 fully complies with IEEE 1101.11.

Dimensions

- Backplane Adapter- per IEEE 1101.11 80mm depth type.
- Single Slot Transition Module – per IEEE 1101.1 Single slot front panel.
- Double Slot Transition Module – per IEEE 1101.1 Double slot front panel.



Ordering Information for the TM900



Example: TM900-11-00

For more information about the TM900 or any Aitech product, please contact Aitech Defense Systems sales department at (888) Aitech-8 (248-3248).



www.dpie.com

Diamond Point International (Europe) Ltd

Suite 13, Ashford House, Beaufort Court

Sir Thomas Longley Road, Rochester, Kent, ME2 4FA, UK

Phone 01634 300900 - Fax 01634 722398 - Email sales@dpie.com – Web www.dpie.com

All names, products, and/or services mentioned are trademarks or registered trademarks of their respective holders. All information contained herein is subject to change without notice.

TM900T0906R10

Aitech Defense Systems, Inc.

A member of the Ai-Rugged Group

9301 Oakdale Ave, Chatsworth, Ca 91311

Tel: (888) Aitech-8 (248-3248) Fax: (818) 718-9787 e-mail: sales@rugged.com web: www.rugged.com



Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

*InstraView*SM REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at www.instraview.com ↗

WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. www.artisanng.com/WeBuyEquipment ↗

LOOKING FOR MORE INFORMATION?

Visit us on the web at www.artisanng.com ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

Contact us: (888) 88-SOURCE | sales@artisanng.com | www.artisanng.com