ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Alcatel / Xylan CSM-155-8* at our website: *Click HERE*

OmniSwitch cell switching modules (CSM and FCSM)

Any Omni-3wx/5wx/9wx with a Cell Switching Module (CSM) requires MPM-1GW*, MPM-SW, MPM-CSM (MPM base software and CSM base software must be 3.0 or later.) and the FCSM155(W)-4C-CSM-3.2 module. When ordering narrow OmniSwitch modules, use the model name without the "W" suffix and when ordering wide OmniSwitch modules, use the module name with the "W" suffix. All wide modules must be installed in wide chassis.

* Note: Customers may use existing MPM-II-16MB instead of MPM-1GW. In order to use the MPM-II-16MB in the wide chassis, customers need to order the OMNI-SPCR. See Section 18. Refer to Minimum Software Requirements.

Type		Model	Description	Availability	More info (new window)
		CSM-155-8	Eight ports, 155 Mbps SONET/SDH OC-3c/STM-1, SC connectors. Supports multi-mode fiber-optic cable . Standard memory supports 4K VC/port and 8,192 cell buffers/port.	Standard	Specifications
		CSM-155-8S	Eight ports, 155 Mbps SONET/SDH OC-3c/STM-1, SC connectors. Supports single mode fiber-optic cable . Standard memory supports 4K VC/port and 8,192 cell buffers/port.	Standard	Specifications
		CSM-155-8SW	Eight ports, 155 Mbps SONET/SDH OC-3c/STM-1, SC connectors. Supports single mode fiber-optic cable . Standard memory supports 4K VC/port and 8,192 cell buffers/port.	Standard	Specifications
		CSM-155-8W	Eight ports, 155 Mbps SONET/SDH OC-3c/STM-1, SC connectors. Supports multi-mode fiber-optic cable . Standard memory supports 4K VC/port and 8,192 cell buffers/port.	Standard	Specifications
		CSM-155C-8W	Eight ports, 155Mbps SONET/SDH OC-3c/STM-1 with RJ45 connectors. Category 5 UTP cabling. Supports cabling distances of 90 meters. Standard memory supports 4K VC/port and 8,192 cell buffers/port.	Standard	Specifications
		CSM-622-2E	Two ports, 622 Mbps SONET/SDH OC-12c/STM-4c, SC connectors. Supports multi-mode fiber-optic cable . Extended memory supports 64K VC/port and 131,072 cell buffers/port.	Standard	Specifications
		CSM-622-2EW	Two ports, 622 Mbps SONET/SDH OC-12c/STM-4c, SC connectors. Supports multi-mode fiber-optic cable . Extended memory supports 64K VC/port and 131,072 cell buffers/port.	Standard	Specifications
		CSM-622-2SE	Two ports, 622 Mbps SONET/SDH OC-12c/STM-4c, SC connectors. Supports single mode fiber-optic cable . Extended memory supports 64K VC/port and 131,072 cell buffers/port.	Standard	Specifications
		CSM-622-2SEW	Two ports, 622 Mbps SONET/SDH OC-12c/STM-4c, SC connectors. Supports single mode fiber-optic cable . Extended memory supports 64K VC/port and 131,072 cell buffers/port.	Standard	Specifications
		CSM-A25-12	12-port ATM25, slot, RJ-45 connectors.	Contact	Specifications
		CSM-A25-12W	12-port ATM25, slot, RJ-45 connectors, wide form factor only.	Contact	Specifications
		CSM-A25-24W	24-port ATM25 module, wide form factor only.	Contact	Specifications
	New!	CSM-UW	Universal Cell Switching Module, 3 NNI adapter board slots available. (Please refer to the section below on adapter boards). All types of the CSM-UW daughtercard can be mixed. No restrictions apply.	Contact	
		FCSM-155-4C-CSM-3.2	Frame Cell Switching Module with 4K CAM. Provides an internal link between the frame bus and cell matrix. Required for hybrid frame and cell switching configurations.	Standard	Specifications
		FCSM-155W-4C-CSM-3.2	Frame Cell Switching Module with 4K CAM. Provides an internal link between the frame bus and cell matrix. Required for hybrid frame and cell switching configurations.	Standard	Specifications
CSM Adapters-Modules below are Daughter Cards used w/ the Universal Cell Switching Module	New!	CSM-AB-155C-2W	2-port 155Mbps OC-3/STM-1 adapter for CSM-UW, UTP. RJ-45 connector. Standard memory supports 4K VCs/port and 8,192 cell buffers/port.	Contact	
CSM Adapters-Modules below are Daughter Cards used w/ the Universal Cell Switching Module	New!	CSM-AB-155FM-2W	2-port 155Mbps OC-3/STM-1 NNI adapter for CSM-UW, MM fiber. SC connectors. Standard memory supports 4K VCs/port and 8,192 cell buffers/port.	Contact	Specifications
CSM Adapters-Modules below are Daughter Cards used w/ the Universal Cell Switching Module	New!	CSM-AB-155FS-2W	2-port 155Mbps OC-3/STM-1 adapter for CSM-UW, SM fiber, intermediate reach. SC connectors. Standard memory supports 4K VCs/port and 8,192 cell buffers/port.	Contact	Specifications
CSM Adapters-Modules below are Daughter Cards used w/ the Universal Cell Switching Module	New!	CSM-AB-155FSH-2W	2-port 155Mbps OC-3/STM-1 adapter for CSM-UW, SM fiber, long reach. SC connectors. Standard memory supports 4K VCs/port and 8,192 cell buffers/port.	Contact	Specifications

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

CSM Adapters-Modules below are Daughter Cards used w/ the Universal Cell Switching Module	New!	CSM-AB-DS1-4W	4-port DS-1 adapter for CSM-UW (RJ-45). SC connectors. Standard memory supports 2K VCs/port and 4,096 cell buffers/port.	Contact	Specifications
CSM Adapters-Modules below are Daughter Cards used w/ the Universal Cell Switching Module	New!	CSM-AB-DS3-2W	2-port 45Mbps DS-3 adapter for CSM-UW (BNC). Standard memory supports 4K VCs/port and 8,192 cell buffers/port.	Contact	Specifications
CSM Adapters-Modules below are Daughter Cards used w/ the Universal Cell Switching Module	New!	CSM-AB-E1-4W	4-port E1 adapter for CSM-UW (RJ-45). Standard memory supports 2K VCs/port and 4,096 cell buffers/port.	Contact	Specifications
CSM Adapters-Modules below are Daughter Cards used w/ the Universal Cell Switching Module	New!	CSM-AB-E3-2W	2-port 34Mbps E3 adapter for CSM-UW (BNC). Standard memory supports 4K VCs/port and 8,192 cell buffers/port.	Contact	Specifications
CSM-Circuit Emulation	New!	CSM-AB-CE-E1-4W	4-port AAL-1 E1 (RJ-45, 120 Ohm) Circuit Emulation Cell Switching Adapter Board for CSM-UW.	Contact	
CSM-Circuit Emulation	New!	CSM-AB-CE-T1-4W	4-port AAL-1 T1 (RJ-45, 120 Ohm) Circuit Emulation Cell Switching Adapter Board for CSM-UW.	Contact	

Technical information provided in this document is subject to change without notice. Xylan, OmniSwitch and PizzaSwitch are trademarks of Xylan Corporation registered in the U.S. Patent and Trademark Office. OmniStack is a trademark of Xylan Corporation. All other trademarks are property of their respective owners. © 1998 Xylan Corporation.

Xylan Corporation - 26707 W. Agoura Rd. - Calabasas, CA 91302 - 800-995-2612

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP