ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.


- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Ametek / VTI Instruments / VXI Technology VM8016* at our website: *Click HERE*

VM8016



16-channel Low Thermal Multiplexer (VMIP™)

Overview

The VM8016 is a high precision, low thermal relay multiplexer. The design ideally suits the needs of instrumentation and data acquisition/process control, and is recommended for use in high accuracy applications, where a general-purpose switch module will not suffice. It is also ideal in general-purpose applications when combined with other VMIP™ instruments, saving VXIbus card slot space. The relays are designed specifically for switching low level signals, and employ a thermally compensating ceramic chip to minimize the offset generated by the relay at the junctions.

The VM8016 belongs to the VMIP™ family of products. This gives the user the added flexibility of combining it with other instruments to create a multi-function C-size card, or with other VM8016s to provide up to 48 channels of low-level signal switching in a single C-size card slot.

Programming

The VM8016 is programmed using word-serial message-based commands that are SCPI compatible. SCPI commands are available to configure the VM8016 as either a 2- or 4-wire multiplexer, for programmable delays between relay closures to synchronize with external devices such as DMMs, or simply to open or close relays.

Specifications

Maximum Switching Voltage:	200 V dc or 200 V peak ac
Maximum Switching Current:	0.5 A
Minimum Carry Current:	1.0 A
Maximum Power per Channel:	10 w
Maximum Thermal EMF:	<1 µV
Closed Channel Path Resistance:	<0.5 Ω
Insulation Resistance: (between any two points)	10^{11} Ω

Features


- Low Thermal Offset Relays, <0.5 µV
- High Insulation Resistance - 10^{11} Ω
- Ideal for High-precision Signal Switching with DMMs
- Designed for 2- or 4-wire Switching
- Configured as 2 (1x8) 2-wire Multiplexers
- SCPI Compatible
- Message-based Control

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

16-channel Low Thermal Multiplexer (VMIP™)

Closed Channel Capacitance:	<50 pF
Minimum Bandwidth:	50 MHz
Minimum Relay Life:	100 x 10^6 (1 V, 10 mA)

Configuration



Ordering Information

VM8016	**16-channel Low Thermal Multiplexer**
	(Must be configured with a VM9000 host module)

VM8016

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP