

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*

Menu

NEED HELP?
Contact Customer Service
(800) 627 - 7100
CONTACT US

Amphenol® RF

HOME / CONNECTORS / N-TYPE

FILTER BY

- Gender
  - Jack (173)
  - Plug (155)
- + Orientation
- + Impedance (Ohms)
- + Mounting Feature
- + Termination Style
- + Cable Type
- + Cable Group
- + Body Finish
- + Body Material
- + Contact Finish
- + Contact Material
- + Contact Termination Style
- + Max Frequency (GHz)
- + Coupling Mechanism
- + Insulator Material
- + IP Rating
- + Polarity
- + Extended Dielectric
- + Low PIM
- + Military Qualified

N-TYPE CONNECTOR SERIES

N-Type connectors are designed to satisfy the need for a durable, weatherproof, medium-size RF connector with consistent performance through 11 GHz. Our N-Type connectors feature threaded coupling mechanisms and are fully interchangeable with N-Type connectors made to the MIL-C-39012 specification. These connectors are used in all systems where excellent RF and mechanical performance is critical.



Related Products

N-Type Adapters
N-Type Accessories
N-Type Cable Assemblies

FEATURES AND BENEFITS

- Broad line of military, industrial and commercial grade products available
- Excellent RF performance from DC to 11 GHz
- Threaded coupling mechanism ideal for vibration resistance

APPLICATIONS

- Antennas
- Base stations
- Instrumentation
- Satellite systems
- WLAN
- Radar systems
- Broadcast
- Surge protection

N-TYPE SPECIFICATIONS

Electrical

Impedance	50 Ohm
Frequency Range	0-11 GHz
VSWR	
M30912 Straight Connectors 0-11 GHz	1.30 Max
M30912 Right Angle Connectors 0-11 GHz	1.35 Max
Dielectric Withstanding Voltage	2500 VRMS
Voltage Rating	1500 volts peak
Insulation Resistance	5000 MΩ min

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Contact Resistance	
Outer Contact	0.2 mΩ
RF Leakage	-90 dB min @ 3 GHz
Insertion Loss	0.15 dB max @ 10 GHz

Environmental

Temperature Range:	
TFE Insulation	-65°C to +165°C
Copolymer of Styrene	-55°C to 85°C
Weatherproof	All series N with gaskets are weatherproof
Hermetic Seals	Pass helium leak test of 2 x 10^{-8} cc/sec
Pressurized Shock	Compressed seal Mil-STD-202, Method 213
Vibration	Mil-STD-202, Method 204 (test cond. D)
Moisture Resistance	MIL-STD-202 Method 106
Corrosion	Mil-STD-202, Method 101 (test cond. B)
Temperature Cycling	Mil-STD-202, Method 102 (test cond. D)
Altitude	MIL-STD-202 Method 105 (test cond. C)

Mechanical

Mating	5/8-24 threaded coupling
Cable Affixment (Braid or Jacket):	
All Crimps	Hex braid crimp
Clamps	Screw-thread nut and braid clamp
Cable Affixment (Center Conductor):	
Crimps	Crimp or solder
All Others	Solder only
Captivated Contact:	
All Crimps	Yes
Others	Where specified
Cable Retention	
Crimps	60-120 lbs
Clamps	30-70 lbs

CORRUGATED TYPE N SPECIFICATIONS

Electrical

Impedance	50 Ohm
Frequency Range	11.0 GHz
Return Loss (Freq. GHz)	
1-2GHz	33 dB
2-3GHz	28 dB
Operating Voltage	707 VRMS max
Dielectric Withstanding Voltage	2000 VDC
Peak Power	10kW max
Avg. Power	.60kW maz
Insulation Resistance	5000 MΩ
Shielding Effectiveness	125 dB min

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

3rd Order IM Product, typical	-125 dBm (-168 dBc)
Insertion Loss	.05 freq GHz

Environmental

Temperature Range	
Operating	-40°C to +150°C
Storage	-70°C to 100°C
Thermal Shock	Mil-STD-202, Method 107 (test cond. A)
Immersion	IEC 529, IP68
Vibration	Mil-STD-202, Method 204 (test cond. B)
Corrosion	Mil-STD-202, Method 101(test cond. B)
Mechanical Shock	MIL-STD-202 Method 213 (test cond. I)


Mechanical

Mating	MIL-STD-348
Inner Attachment Method	Solder or Captivated
Outer Attachment Method	Compression
Assembly Torque	18/22 lb-ft (25/30 N-m)
Coupling Torque	15.00 lb-in (1.70 N-m)
Coupling Nut Retention Force	100.00 lbs (444.80 N)
Connector Durability	500 cycles, 12 cycles/min


These characteristics are typical and may not apply to all connectors.

INTERFACE DIMENSIONS

Plug



Jack



Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

DISTRIBUTOR LISTING

Copyright © 2014 Amphenol RF. All Rights Reserved.
Copyright | Terms & Conditions | Privacy Policy | Logos | Amphenol.com

LMR® is a registered trademark of Times Microwave Systems

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP