

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.


- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*

EX200 Series



Features

- DIN rail or bench mounting
- Easy clamp terminals for our PCI200 series digital I/O boards
- Isolated input protection
- Isolated outputs/ relays
- 'Mix and match' panels to build the connection system for you

Description

The EX200 range of digital termination panels has been developed for connection of signals to the PCI236, PCI272 and PCI215. Three termination panels are available, and may be used in various combinations or individually, depending on whether isolation is required or not.

EX233 termination panel
The EX233 is a termination panel that provides 78 terminals for connection of external signals. A 78-way connector enables connection via an appropriate cable assembly, to either PCI272 or PCI215 digital I/O boards. It also has three 37-way connectors allowing distribution of input/ output signals, or connection to an isolation panel detailed below.

EX230 isolated input panel
The EX230 is a 24 line interface panel that provides isolation and protection from digital input signals. The EX230 may be connected directly to the PCI236 digital I/O board (via a cable), or to one of the three 37-way connectors on the EX233.

All inputs can be configured on a channel by channel basis. The following jumper selections can be made:

- An opto-isolated input with 2 ranges:
Low range: -5.0 to +1.5V = Low, and +4 to +20V = High.
High range: -15 to +2.0V = low, and +10 to +50V = high.

- Volt free contact closure input which uses the +5V supply onboard to detect a contact closure and like all the other input modes requires no external power.

EX213 relay/ isolated output panel
The EX213 is a 24 line interface panel that provides isolation or higher switching capability for digital outputs. The EX213 may be connected directly to the PCI236 digital I/O board (via a cable), or to one of the three 37-way connectors on the EX233.

There are independent terminal groups for relay and logic outputs and all outputs can be configured on a channel by channel basis. The following jumper selections can be made:

- Isolated relay output with changeover contact. This is rated for 8A at 30Vdc, or 49Vac.


- Isolated High level logic output with source drivers that can source up to 100mA for 90% duty cycle on all 24 lines.

- Non-isolated TTL outputs on port A (8-bits).

The outputs are in groups of 8, each of which may be independently powered by a 24Vdc supply. Alternatively they can share one 24V supply but either way external power is required. EX233 has terminals for introducing a common 24V power supply for the EX213 and EX221.

Schematic diagram


EX213 or EX230 can be connected to the EX233 or directly to a PCI236



Sales: +44 (0) 1273 570 220 Admin: +44 (0) 1273 608 331 Fax: +44 (0) 1273 570 215 Website: www.amplicon.co.uk Email: sales@amplicon.co.uk

EX200 Series

EX233 expansion panel



Specifications	
Board interface	78-pin male D-sub
Wiring termination	Spring loaded terminals
Expansion interface	Three 37-pin male D-sub
Dimensions	267 x 126 x 42mm (width x depth x height)
Mounting	DIN rail or bench top


Ordering information

90966333 EX233 termination and distribution panel

90966349 Cable 1m long screened 78 way for use with EX233 panel and 200 series DIO boards

91014890 ACL-10137-1 MF Screened cable, 37-way male D to female D

EX230 isolated input panel




Specifications	
Opto-isolated low range	Low or '0': -5.0 to +1.5V High or '1': +4 to +20V
Opto-isolated high range	Low or '0': -15 to 2.0V High or '1': +10 to +50V
Volt free contact	Low or '0': -1.0 to +1.5V High or '1': +2.0 to +5.0V
Wiring termination	Spring loaded terminals
Connector	37-way female D-sub
Dimensions	320 x 126 x 42mm (width x depth x height)

Ordering information

90966373 EX230 input panel, 24 isolated common & contact closure inputs

91014890 ACL-10137-1 MF Screened cable, 37-way male D to female D

EX213 Relay / isolated outputs



Specifications	
Number of relays	24 SPDT
Contact rating	30Vdc or 49Vac @ 8A
Opto-isolated output	Low or '0': +0.7V High or '1': +23V
Non-isolated outputs	TTL on Port A only, selectable
Max current source	100mA/ channel for 90% duty
Wiring termination	Spring loaded terminals
Connector	37-way female D-sub
Dimensions	320 x 126 x 42mm (width x depth x height)
Power requirements	24Vdc

Ordering information

90966363 EX213 output panel with 24 relays/isolated logic

91014890 ACL-10137-1 MF Screened cable, 37-way male D to female D

Sales: +44 (0) 1273 570 220 Admin: +44 (0) 1273 608 331 Fax: +44 (0) 1273 570 215 Website: www.amplicon.co.uk Email: sales@amplicon.co.uk

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP