ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Analog Devices 5B39-01* at our website: ***Click HERE***

5B Series Single / Double Channel Mounting Card

5B03/5B04

FEATURES

Mix and Match 5B Series I/O Module Capability
Factory Mutual (FM) Approved
Approved for Use in Class I, Division2, Groups A, B, C, and D Locations.
CE Certified: EMC Directive in Heavy Industrial Applications
1500 V rms Channel/Channel and Input/Output Isolation
Four Backplanes and Three Mounting card Options
1-, 2- channels
-25°C to +85°C Temperature Range
Single Threaded Insert for module Hold Down

APPLICATIONS

Industrial Signal Conditioning
Industrial Signal Isolation
Industrial Signal Filtering

PRODUCT OVERVIEW

To address diverse applications, the 5B Series includes a family of backplanes and mounting cards which provide a complete signal conditioning solution. The models 5B03 and 5B04, one and two channels cards, allow an economical means to handle a few signals.

FUNCTIONAL BLOCK DIAGRAM




Figure 1 5B03 & 5B04 Functional Block Diagram

The backplanes provide four screw terminals per channel for all field connections. These connections satisfy all transducer inputs, process current outputs and provide transducer excitation when necessary. A cold junction temperature sensor (model AC1361) sensor is also supplied on each channel to accommodate thermocouple input modules. All 5B Series backplanes and sockets require a regulated +5VDC external power source.

Rev. 0
Information furnished by Analog Devices is believed to be accurate and reliable. However, no responsibility is assumed by Analog Devices for its use, nor for any infringements of patents or other rights of third parties that may result from its use. Specifications subject to change without notice. No license is granted by implication or otherwise under any patent or patent rights of Analog Devices. Trademarks and registered trademarks are the property of their respective companies.

One Technology Way, P.O. Box 9106, Norwood, MA 02062-9106, U.S.A.
Tel: 781.329.4700 **www.analog.com**
Fax: 781.326.8703 **© 2005 Analog Devices, Inc. All rights reserved.**

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

GENERAL DESCRIPTION

MODELS 5B03 and 5B04 – For smaller applications, the models 5B03 and 5B04 mounting cards are available for one and two 5B Series modules respectively. These module cards may be clustered for groups of three or more signals. They are DIN rail compatible using Phoenix Universal Module UM elements.




Figure 2 5B03




Figure 3 5B04

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

5B03/04 Specifications

(typical @ +25°C and V_s =+5 V dc Power)

Description	Model 5B03	Model 5B04
Number of Channels	1	2
ISOLATION		
Input-to-Output Continuous	1500 V rms, Maximum	1500 V rms, Maximum
Channel-to-Channel Continuous	N/A	1500 V rms, Maximum
MECHANICAL DIMENSIONS	4.25” x 1.365”	4.25” x 1.365”
	(105 mm x 34.7 mm)	(105 mm x 34.7 mm)
DIN Rail Mountable	Yes	Yes
WEIGHT	0.85oz. (24.0)	1.06oz. (30.2g)
Provision for Mounting AC1352 Resistor	Yes	Yes
COLD JUNCTION TEMPERATURE SENSORS		
Number provided on backplane	1	2
Type	Model AC1361	Model AC1361
Initial Accuracy @ +25°C	±0.25°C (+0.75°C, maximum)	±0.25°C (+0.75°C, maximum)
Accuracy +5°C to +45°C	±0.5°C (+0.0125°C/°C)	±0.5°C (+0.0125°C/°C)
Field I/O CONNECTOR		
Number	1	2
Type	4-screw terminals	4-screw terminals
OUTPUT SWITCH ENABLE/READ INPUTS	NO	NO
POWER SUPPLY OPTIONS		
Voltage; Operating	+5 VDC ±5%	+5 VDC ±5%
Voltage; Max Safe Limit – with modules	+6.0 VDC Max.	+6.0 VDC Max.
Current – without modules	N/A	N/A
Fuse	N/A	N/A
Environmental Temperature Range		
Rated Performance	-25°C to +85°C	-25°C to +85°C
Operating	-40°C to +85°C	-40°C to +85°C
Storage	-40°C to +85°C	-40°C to +85°C
Relative Humidity	0 to 95% @ +60°C noncondensing	0 to 95% @ +60°C noncondensing

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

OUTLINE DIMENSIONS




Figure 4 Outline Dimensions 5B03




Figure 5 Outline Dimensions 5B04

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

NOTES

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

NOTES

© 2005 Analog Devices, Inc. All rights reserved. Trademarks and registered trademarks are the property of their respective companies.
D05412-0-2/05(0)

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP