ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.


- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Andor Design CIC301* at our website: ***Click HERE***

ANDOR DESIGN CORP



CIC301
MIL-STD-1553
Simulator/Analyzer/Tester

PCI BUS Interface Card

FEATURES

*** SUPPORTS VALIDATION/PRODUCTION TEST PLANS.**
*** SIMULTANEOUS BC, MULTIPLE RTS, MONITOR.**
*** FULL ERROR DETECTION AND GENERATION.**
*** ON BOARD MAJOR/MINOR FRAME TIMING.**
*** PROGRAMMABLE MESSAGE PARAMETERS.**
*** PROGRAMMABLE OUTPUT AMPLITUDE.**
*** SOFTWARE WITH SOURCE CODE INCLUDED.**
*** 32 WORDS BI DIRECTIONAL PCI FIFO.**
*** 128K x 16 DUAL PORT STATIC RAM.**

DEVICE TYPE

Size PCI 1/2 size
Type 32 Bits, 5 Volts, Target only.

DESCRIPTION

The CIC301 is a full-featured, high performance, Dual Redundant MIL-STD-1553A/B serial bus Simulator Analyzer Tester designed as a plug in card for PCI backplane. The CIC301 includes full error injection and can operate in independent or simultaneous mode as a Bus Controller, multiple simulated Remote Terminals and full/selective Monitor. Its data structure can be changed on the fly without interrupting the processor for real time operation. The active monitor stores, time tag and annotates bus traffic with the message type and any detected errors. Stored words are annotated with a break down of the word error.

APPLICATIONS

The CIC301 can be used for Validation Testing, Production Testing, full bus simulation and monitoring, as a general purpose 1553 interface or a stand alone bus Analyzer. For precise message scheduling and measurements, the Major and minor frame times are independent of message sequences or retransmissions on errors and the start of all command messages are independent of message length, response time or length of response. Message timing is calibrated and RT responses have low jitter.

GENERAL SPECIFICATIONS	
Parameter	Value
1553 SRAM	128K x 16
Major Frame Count	1 to 32768, Continuous
Major Frame Size	1 to 1024 Minor Frames
Minor Frame Time	0 to 419 msec
Minor Frame Size	0 to 32766 Commands
BC Messages	0 to 2048
Message intervals	2 to 6400 usec. in .1 usec. steps
Response timeout	2 to 33 usec. in .5 usec. steps
Response Time	2 to 33 usec. in .5 usec. steps
Response jitter	50ns Max
Retry on Error	Same or alternate bus
Internal time tag	16 bits, 6.4 or 64 usec. steps

WORD ERROR INJECTION/DETECTION
- Low bit count (1, 2)
- High bit count (1, 2, 3)
- Parity error
- Manchester low
- Manchester high
- Inverted Sync
- Zero crossing deviation (+/- 150 nsec, External)

MESSAGE ERROR INJECTION/DETECTION
- Format
- Response/Late response
- Sync
- Non contiguous data (2 microsec.)
- Word count error
- Data on two channels
- Status word
- Invalid Word

MAXIMUM	RATINGS
Parameter	Value
Temperature Range	
Operating	0 to +70 Deg. C
Storage	-65 to +150 Deg. C
*Power supplies	
+5 Volts +/- 5%	0.4 Amps Max
+12 Volts +/- 5%	0.160 Amps 50% duty cycle
-12 volts +/- 5%	0.005 Amps Max
Physical characteristics	
1/2 Size PCI card	4.2 x 7.6 x 0.47 inches

SOFTWARE
The CIC301 comes with software drivers for DOS and Windows 98/NT/2000/XP. A set of well-documented API's with Source code written in "C" is included.

STAND ALONE OPERATION
A menu driven user interface is included for stand alone operation. With this program the user can set up 1553 traffic, simulate RT'S responses, monitor all or selected traffic in real time and capture data using trigger and search arguments.

DATA FILTERING
The CIC301 data filter looks at the complete command rather than just addresses and sub addresses. Individual Messages are designated to be ignored, monitored, replied to or monitored and replied to.

CIC301 OPERATION
The CIC301 processes 1553 messages with a minimum attention from the CPU. The user need only write a set of command Blocks, a message list and number of messages to define a minor frame of 1553 messages. He writes a minor frame time, the number of minor frames per major frame and a minor frame list to define a major frame. The bus controller sends the major frame a number of times as programmed in the major frame count, without any further attention from the CPU.

In the Remote Terminal mode, the user writes a set of command Blocks and a look-up table for the CIC301 to respond autonomously to incoming messages. In both modes an active monitor analyzes, annotates and stores bus traffic in a monitor Buffer.

The CIC301 generates ten interrupt flags to show completion of a frame in the BC mode, receipt of a specified message, receipt of a specified Data word, receipt of a specified Status word, detected message errors or triggers.

1553 OUTPUT
- Direct coupling
- Transformer stub coupling

COMPUTER INTERFACE
The CIC301 operates as a 32 bits, target-only device with interrupt support. An auto indexing Dual ported, static RAM serves as the intermediate for data exchange between the on board PCI FIFO and the 1553 bus. An auto incrementing address register serves to hold the initial RAM Address and increments after each data transfer. Two additional registers control the mode of operation.

Both the registers and the RAM can be loaded with new data while a message is being transmitted over the 1553 channel for real time applications. Essentially, programming the CIC301 consists of transferring data to or from the RAM and the host.

For specialized features or unique interface requirements, please contact the factory.

Specifications subject to change without notice.
Copyright (c) 1995 - 2007 by Andor Design Corp.
All rights reserved.

ANDOR DESIGN CORP.
20 Pond View Drive
Syosset, New York, USA 11791-4409

www.AndorDesign.com
Telephone 516 364 1619
FAX 516 364 5428

Data Sheet. July 1, 1998

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP