ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Banner Engineering P4SLC50-G* at our website: ***Click HERE***

P.SLC..-.. Series Sealed Lens Enclosure

Waterproof lens enclosure for use with sealed PresencePLUS sensors



(Lens enclosure shown mounted to camera)

- Rugged, waterproof housing, rated IEC IP68
- Available with 316 stainless steel or nickel-plated aluminum housing and a choice of either acrylic or tempered optical glass windows
- Mounts directly to PresencePLUS® Sealed Pro and Sealed P4 models (when ring light is not used)

For use with	Length	Model	Housing	Window	Replace window model
PPROCAMS	50 mm	PPSLC50-G	Nickel-plated aluminum	Glass	PPSLC-RG
		PPSLC50-P		Acrylic	PPSLC-RP
PPROCAMS and P4.RS	75 mm	PPSLC75-G		Glass	PPSLC-RG
		PPSLC75-P		Acrylic	PPSLC-RP
PPROCAMSS	50 mm	PPSSLC50-G	316 Stainless steel	Glass	PPSLC-RG
		PPSSLC50-P		Acrylic	PPSLC-RP
P4.RS	50 mm	P4SLC50-G	Nickel-plated aluminum	Glass	PPSLC-RG
		P4SLC50-P		Acrylic	PPSLC-RP

Specifications

Construction

Housing: Nickel-plated aluminum or 100% 316 stainless steel depending on model

Window: Acrylic or tempered optical glass, depending on model

Outside Dimensions

PPSLC50-: 49.3 mm dia. by 48.9 mm long overall (1.94" dia. x 1.93" long)

PPSLC75-: 49.3 mm dia. by 75 mm long overall (1.94" dia x 2.95" long)

Environmental Rating

Nickel models: IEC IP68 when installed on Sealed PresencePLUS Sensors

Stainless steel models: NEMA 4X; IP68

Installing the Lens Enclosure

NOTE: Before installing this product, Banner Engineering Corp. recommends installing a light filter behind the lens. The filter improves image quality by reducing unwanted ambient light.

1. Install and focus the lens.
2. Thread the lens enclosure onto the lens until the enclosure is seated against the sensor.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP