



## Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

### SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

### *InstraView*<sup>SM</sup> REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at [www.instraview.com](http://www.instraview.com) ↗

### WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. [www.artisanng.com/WeBuyEquipment](http://www.artisanng.com/WeBuyEquipment) ↗

### LOOKING FOR MORE INFORMATION?

Visit us on the web at [www.artisanng.com](http://www.artisanng.com) ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

**Contact us:** (888) 88-SOURCE | [sales@artisanng.com](mailto:sales@artisanng.com) | [www.artisanng.com](http://www.artisanng.com)



## RF POWER METER 4730 SERIES

- Frequency Range: 10 kHz to 110 GHz
- Power Range: -70 dBm to +44 dBm
- 90 dB Dynamic Range
- Automatic download of sensor calibration data
- Backward compatible with all existing Boonton diode, thermocouple, and waveguide sensors
- Over 200 readings per second in single channel mode
- Single or Dual Channel Capability
- Single-slot, C-size Module
- VXI Bus Message Based Device



### Description

The 4730 series is a VXI microprocessor based RF power meter that can be configured to meet virtually any RF/Microwave power measurement requirement. It has the same state-of-the-art characteristics of the popular 4230A series along with accuracy, functionality, speed, and flexibility of VXI. The unit is a single-slot, C-size, VXIbus formatted instrument, which means that you will get extreme accuracy, in a mainframe chassis.

The 4730 series is designed for both military and commercial VXIbus ATE systems. Its high-stability and precision are ideal for radar, EW, avionics, automotive, and all facets of telecommunications. They include: ATE Systems, Satellite Communications, Paging, PCS, and Microwave Communications. As well as: manufacturers of

components of: attenuators, filters, amplifiers, (TWT and solid state), detectors, mixers, and antenna systems.

### Two Channel Operation

The 4730 series also can be configured with a second channel input that provides a duplicate set of input amplifiers and connectors for a second power sensor. This feature allows the unit to measure and calculate the difference and ratio of the two channels.

### Additional Features

- Duty Cycle Setting for Pulse Measurements
- Selectable Filtering
- Automatic or Preset Ranging
- Built in Calibration Source
- Automatic Calibration
- Automatic Zeroing



## 4730 Series VXI Power Meter Specifications

Frequency Range:	10 kHz to 100 GHz, sensor dependent
Power Range:	-70 dBm to +44 dBm, sensor dependent
Number of Channels:	One / Two
Measurement:	Speed: 1 channel: 200 readings/sec. 2 channel: 100 readings/sec.
Power Sensors:	Accepts sensor data adapter with full-calibration data, including high-frequency calibration factors, stored in non-volatile memory. Compatible with all Boonton CW Power Sensors. *See Sensor Data Sheet.
Dynamic Range:	Up to 90 dB with diode sensors, 50 dB with thermocouple sensors. * See power sensor specifications.
Inputs:	Front panel sensor connectors standard.
Outputs:	Front panel PWR REF connector, 0 dBm, 50 MHz. Front panel RECORDER BNC connector, 0 to 10 V into 1MΩ. Output impedance is 9.09 kΩ. May be operated into 1kΩ for 1V fs.
Measurement Units:	Absolute: watts, dBm. Relative: %, dBr.
Measurement Accuracy:	Total accuracy is the sum of the following uncertainties (errors are +/- worst case):
Instrumentation Accuracy:	0.002% at full scale.
Power Reference Uncertainty:	Output frequency: 50 MHz +/- 1.5%. Output level: 0 dBm level accuracy: +/- 0.7% (25°C) for 90 days. +/- 0.9% RSS, 1.2% worst case (0° to +55°C) for 1 year. Source impedance: 50 +/- 1 Ω. SWR: < 1.05. Harmonic output: < -50 dBc.
Other Uncertainties:	For sensor, noise, high-frequency calibration uncertainty, *See power sensor specifications.
Calibration Factors:	+3 dB to -3 dB in 0.01 dB steps. These calibration factors are stored in non-volatile memory. When a frequency other than that is stored is used, the meter linearity interpolates between the calibration factor above and below the frequency entered to obtain a calibration factor.
Ranging:	Automatic or manual.
Filtering:	Filter times in 0.05-second intervals to 20 seconds.
Zeroing:	Automatic function to calculate, store, and apply zero corrections to each range.
Measurement Offset:	-99.99 to 99.99 in 0.01 dB steps (dBr).
Power Consumption:	+24VDC      52 mA      1.3 Watts -24 VDC      57 ma      1.4 Watts +5 VDC      690 ma      4.7 Watts
Operating Temperature:	0 to +55°C.
Weight:	2.64 lbs. (1.20 kg).
Dimensions:	Single-slot, C-size module.
Accessories Required:	One or more of the available power sensors and a power sensor cable and one sensor data adapter are required.

## POWER SENSORS

### Ordering Information:

Single Channel	4731
Dual Channel	4732

Diode Sensors			Thermocouple Sensors		
Model Number	Frequency (MHz-GHz)	Power (dBm)	Model Number	Frequency (MHz-GHz)	Power (dBm)
51011(EMC)	0.01 to 8	-60 to +20	51100	10 to 18	-30 to +20
51011	0.1 to 12.4	-60 to +20			
51012*	0.1 to 2	-60 to +20	51101	0.1 to 4.2	-30 to +20
51013	0.1 to 18	-60 to +20			
51015	0.1 to 18	-50 to +30	51102	30 to 26.5	-30 to +20
51033	0.1 to 18	-40 to +33			
51071	10 to 26.5	-70 to +20	51200	10 to 18	-10 to +37
51072	30 to 40	-70 to +20			
51075	0.5 to 18	-70 to +20	51201	0.1 to 4.2	-10 to +37
51077	0.5 to 18	-60 to +30			
51078	0.1 to 18	-20 to +37	51300	10 to 18	0 to +44
			51301	0.1 to 4.2	0 to +44

\*75Ω

Consult factory for details on K, Ka, Q, U, V, & W waveguide sensors.

Specifications subject to change without notice.

**BOONTON ELECTRONICS** 25 Eastmans Road, P.O. Box 465, Parsippany, New Jersey. 07054-0465  
 •Tel: (973) 386-9696      •FAX: (973) 386-9191      •E-Mail: boonton@boonton.com



## Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

### SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

### *InstraView*<sup>SM</sup> REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at [www.instraview.com](http://www.instraview.com) ↗

### WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. [www.artisanng.com/WeBuyEquipment](http://www.artisanng.com/WeBuyEquipment) ↗

### LOOKING FOR MORE INFORMATION?

Visit us on the web at [www.artisanng.com](http://www.artisanng.com) ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

**Contact us:** (888) 88-SOURCE | [sales@artisanng.com](mailto:sales@artisanng.com) | [www.artisanng.com](http://www.artisanng.com)