ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *BP Microsystems ASM44PQ* at our website: *Click HERE*

*QFP variations e.g. BQFP...

Series IC51 (Clamshell)
QFP, PQFP, TQFP and MQUAD®

0.4mm to 1.27 Pitch

Specifications

Insulation Resistance:	1,000MΩ min. at 100V DC
Dielectric Withstanding Voltage:	for 1 minute (socket depended)
Contact Resistance:	30mΩ max. at 10mA/20mV max.
Operating Temperature Range:	–40°C to +150°C (for type PEI/PSF) –55°C to +170°C (for type PES) –55°C to +170°C (for type PEI)
Mating Cycles:	10,000 insertions min.

Materials and Finish

Housing: Polysulphone (PSF), glass-filled
Polyethersulphone (PES), glass-filled
Polyetherimide (PEI), glass-filled
Contacts: Beryllium Copper (BeCu)
Plating: Gold over Nickel



Part Number (Details)

IC51 - 064 4 - 807

- Series No.
- No. of Contact Pins
- Number of Sides with Contacts
- Design Number

As specifications for this product differ by pitch and material-mix, please contact our Sales Department for detailed information.

Series IC357 and IC402 (Open Top)
Quad Flat Package (QFP) with 2-Point Contact Type

0.4 to 0.8mm Pitch

Specifications

Insulation Resistance:	1,000MΩ min. at 500V DC, pitch 0.4 to 0.8
Dielectric Withstanding Voltage:	100V AC for 1 minute, pitch 0.5 to 0.8
Contact Resistance:	30mΩ max. at 10mA/20mV max.
Operating Temperature Range:	–40°C to +150°C
Mating Cycles:	10,000 insertions min.
Contact Force:	20g to 45g per pin

Materials and Finish

Housing: Polyetherimide (PEI), glass-filled
Polyethersulphone (PES) glass-filled
Contacts: Beryllium Copper (BeCu)
Plating: Gold over Nickel



Part Number (Details)

IC357 - 100 4 - 002 *

- Series No.
- No. of Contact Pins
- Number of Sides with Contacts
- Design Number
- Positioning Pin
  N = Without Positioning Pin
  P = With Positioning Pin

Series IC234 (Open Top)
Quad Flat Package (QFP) with Shoulder Contact Type

0.4 to 0.8mm Pitch

Specifications

Insulation Resistance:	1,000MΩ min. at 100V DC pitch 0.4, 0.5 1,000MΩ min. at 500V DC pitch 0.65, 0.8
Dielectric Withstanding Voltage:	100V AC for 1 minute pitch 0.4, 0.5 500V AC for 1 minute pitch 0.65 700V AC for 1 minute pitch 0.8
Contact Resistance:	30mΩ max. at 10mA/20mV max.
Operating Temperature Range:	–40°C to +150°C
Contact Force:	20g to 80g per pin
Mating Cycles:	10,000 insertions min.

Materials and Finish

Housing: Polyetherimide (PEI), glass-filled
Polyethersulphone (PES) glass-filled
Contacts: Beryllium Copper (BeCu)
Plating: Gold over Nickel



Part Number (Details)

IC234 - 120 4 - 017 *

- Series No.
- No. of Contact Pins
- Number of Sides with Contacts
- Design Number
- Positioning Pin
  N = Without Positioning Pin
  P = With Positioning Pin
  K = Protection Key **

** Protection Key: Prevents IC from releasing during transportation

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Series IC200 / IC201 / IC216 / IC217 / IC218 / IC248 (Open Top) Quad Flat Packages (QFP)

0.4 to 0.8mm Pitch

Specifications

Insulation Resistance:	1,000MΩ min. at 500V DC or 1,000MΩ min. at 100V DC
Dielectric Withstanding Voltage:	100/500/700V AC for 1 minute
Contact Resistance:	30mΩ max. at 10mA/20mV max.
Operating Temperature Range:	–40°C to +170°C and –40°C to +150°C
Contact Force:	20g to 80g per pin
Mating Cycles:	10,000 insertions min.

The information above is typical for this Series for individual specifications please contact Yamaichi

Materials and Finish

Housing: Polyetherimide (PEI), glass-filled
Polyphenylenesulfide (PPS), glass-filled
Contacts: Beryllium Copper (BeCu)
Plating: Gold over Nickel



Part Number (Details)

IC200 - 128 4 - 001 * - *

- Series No.
- No. of Contact Pins
- Number of Sides with Contacts
- Design Number
- Positioning Pin: N = Without Positioning Pin, P = With Positioning Pin
- Protection Key** K = With Protection Key, Unmarked = Without Protection Key

**Protection Key: Prevents IC from releasing during transportation

Series IC500 (Open Top) Quad Flat Package (QFP) with 2-Point Contact Type

0.5 to 0.8mm Pitch

Specifications

Insulation Resistance:	1,000MΩ min. at 100V DC pitch 0.5 1,000MΩ min. at 500V DC pitch 0.65, 0.8
Dielectric Withstanding Voltage:	100V AC for 1 minute pitch 0.5 500V AC for 1 minute pitch 0.65 700V AC for 1 minute pitch 0.8
Contact Resistance:	30mΩ max. at 10mA/20mV max.
Operating Temperature Range:	–40°C to +150°C
Contact Force:	20g to 80g per pin
Mating Cycles:	10,000 insertions min.

Materials and Finish

Housing: Polyetherimide (PEI), glass-filled
Polyethersulphone (PES) glass-filled
Contacts: Beryllium Copper (BeCu)
Plating: Gold over Nickel





Part Number (Details)


IC500 - 064 4 - 008 *


- Series No.
- No. of Contact Pins
- Number of Sides with Contacts
- Design Number
- Positioning Pin: N = Without Positioning Pin, P = With Positioning Pin, K = Protection Key


Contact Styles



Series IC51


Series IC357


Series IC234


Series IC (kelvin)



Series IC2**



Series IC500

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com


Applicable Dimensions

Outline IC Body Dimensions





Outline Open Top Socket Dimensions



Outline Clamshell Socket Dimensions

0.40mm Pitch

Part Number	Pitch	Pin Count	IC Dimensions				Socket Dimensions G X H	Package Type CL= Clamshell OT = Open Top
			Body A x B	Tip-to-Tip C x D	Parallel Clamp E	1/2 - IC height F		
IC51-0644-1972	0.4	64	7.0 x 7.0	9.0 x 9.0	8.25	-	35.0 x 32.0	CL
IC234-0804-055	0.4	80	10.0 x 10.0	12.0 x 12.0	-	0.7375	30.0 x 30.0	OT
IC234-1004-045	0.4	100	12.0 x 12.0	14.0 x 14.0	-	0.56	35.0 x 32.0	OT
IC51-1004-1919-*	0.4	100	12.0 x 12.0	14.0 x 14.0	13.30	-	36.0 x 42.5	CL
IC234-1204-022 *	0.4	120	14.0 x 14.0	16.0 x 16.0	-	0.762	34.0 x 34.0	OT
IC51-1204-1596	0.4	120	14.0 x 14.0	16.0 x 16.0	15.35	-	36.0 x 42.5	CL
IC51-1204-1812	0.4	120	14.0 x 14.0	16.0 x 16.0	-	-	36.0 x 42.5	CL
IC234-1284-043 *	0.4	128	14.0 x 14.0	16.0 x 16.0	-	0.56	34.0 x 34.0	OT
IC357-1284-056	0.4	128	14.0 x 14.0	16.0 x 16.0	-	0.65	34.0 x 34.0	OT
IC357-1284-076	0.4	128	14.0 x 14.0	16.0 x 16.0	-	0.45	34.0 x 34.0	OT
IC51-1284-1702	0.4	128	14.0 x 14.0	16.0 x 16.0	15.40	-	36.0 x 42.5	CL
IC51-1284-1702-2	0.4	128	14.0 x 14.0	16.0 x 16.0	15.40	-	36.0 x 42.5	CL
IC51-1284-1788	0.4	128	14.0 x 14.0	16.0 x 16.0	15.30	0.70	39.0 x 42.5	CL
IC234-1444-053 *	0.4	144	16,0 x 16,0	18.0 x 18.0	-	0.54	36.0 x 36.0	OT
QFP11T144-001	0.4	144	16.0 x 16.0	18.0 x 18.0	17.20	.	39.0 x 42.5	CL
IC234-1564-038P-2	0.4	156	14.0 x 14.0	16.0 x 16.0	.	0.76	38.0 x 44.0	OT
IC234-1764-059 *	0.4	176	20,0 x 20,0	22.0 x 22.0	.	0.67	40.0 x 40.0	OT
IC51-1764-1995	0.4	176	14.0 x 20.0	22.0 x 22.0	21.30	-	46.0 x 50.0	CL
IC51-1764-1995-6	0.4	176	20.0 x 20.0	22.0 x 22.0	21.20	-	46.0 x 50.0	CL
IC234-2164-050 *	0.4	216	20.0 x 20.0	26.0 x 26.0	-	0.67	44.0 x 44.0	OT
IC234-2164-066-*	0.4	216	20.0 x 20.0	26.0 x 26.0	-	0.67	44.0 x 44.0	OT
IC51-2164-1887	0.4	216	24.0 x 24.0	26.0 x 26.0	25.30	-	50.0 x 48.0	CL
IC51-2164-1887-10	0.4	216	24.0 x 24.0	26.0 x 26.0	25.30	-	50.0 x 48.0	CL
IC234-2564-020 *	0.4	256	24.0 x 24.0	30.0 x 30.0	-	0.67	48.0 x 48.0	OT
IC234-2564-078 *	0.4	256	24.0 x 24.0	30.0 x 30.0	-	0.67	48.0 x 48.0	OT
IC51-2564-1668	0.4	256	28.0 x 28.0	31.2 x 31.2	30.00	-	56.0 x 62.0	CL
IC51-2564-1668-10	0.4	256	28.0 x 28.0	30.0 x 30.0	29.40	-	56.0 x 62.0	CL
IC51-2564-1668-6	0.4	256	27.2 x 27.2	29.8 x 29.8	30.00	-	56.0 x 62.0	CL
IC51-2564-1668-8	0.4	256	28.0 x 28.0	30.6 x 30.6	30.00	-	56.0 x 62.0	CL

0.50mm Pitch

IC51-0324-805	0.5	32	5.0 x 5.0	7.0 x 7.0	6.20	-	28.0 x 31.0	CL
IC234-0484-034 *	0.5	48	7.0 x 7.0	9.0 x 9.0	-	0.47	26.6 x 26.6	OT
IC234-0484-039 *	0.5	48	7.0 x 7.0	9.0 x 9.0	-	0.74	26.6 x 26.6	OT
IC357-0484-078 *	0.5	48	7.0 x 7.0	9.0 x 9.0	-	0.45	22.0 x 22.0	OT
IC51-0484-806	0.5	48	7.0 x 7.0	9.0 x 9.0	8.20	-	29.0 x 32.0	CL
IC51-0484-806-2	0.5	48	7.0 x 7.0	9.0 x 9.0	8.30	-	29.0 x 32.0	CL
IC201-0644-003 *	0.5	64	10.0 x 10.0	12.0 x 12.0	-	0.70	30.0 x 36.0	OT
IC201-0644-040 *	0.5	64	10.0 x 10.0	12.0 x 12.0	-	0.67	28.7 x 28.7	OT
IC234-0644-027 *	0.5	64	10.0 x 10.0	12.0 x 12.0	-	0.66	29.6 x 29.6	OT
IC234-0644-122 *	0.5	64	10.0 x 10.0	12.0 x 12.0	-	0.66	29.6 x 29.6	OT

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

0.50mm Pitch (cont'd)


Part Numbers	Pitch	Pin Count	A x B	C x D	E	F	G x H	Type
IC357-0644-068	0.5	64	10.0 x 10.0	12.0 x 12.0	-	0.6375	26.2 x 26.2	OT
IC500-0644-008	0.5	64	10.0 x 10.0	12.0 x 12.0	-	0.67	29.6 x 29.6	OT
IC51-0644-807	0.5	64	10.0 x 10.0	12.0 x 12.0	11.30	-	32.0 x 35.0	CL
IC51-807 AC-15764	0.5	64	10.0 x 10.0	13.2 x 13.2	12.00	-	32.0 x 35.0	CL
IC201-0804-014 *-*	0.5	80	12.0 x 12.0	14.0 x 14.0	-	0.62	29.0 x 29.0	OT
IC234-0804-011 *	0.5	80	12.0 x 12.0	14.0 x 14.0	-	0.45	29.0 x 29.0	OT
IC234-0804-026 *	0.5	80	12.0 x 12.0	14.0 x 14.0	-	0.67	31.6 x 31.6	OT
IC357-0804-074	0.5	80	12.0 x 12.0	14.0 x 14.0	-	0.6375	29.0 x 29.0	OT
IC357-0804-096	0.5	80	12.0 x 12.0	14.0 x 14.0	-	0.6375	29.0 x 29.0	OT
IC51-0804-808	0.5	80	12.0 x 12.0	14.0 x 14.0	13.30	-	34.0 x 37.0	CL
IC51-0804-808-2	0.5	80	12.0 x 12.0	14.0 x 14.0	13.20	-	34.0 x 37.0	CL
IC51-0804-808-4	0.5	80	12.0 x 12.0	14.0 x 14.0	13.40	-	34.0 x 37.0	CL
IC201-1004-008 *-*	0.5	100	14.0 x 14.0	16.0 x 16.0	-	0.60	32.2 x 31.0	OT
IC201-1004-043 *	0.5	100	14.0 x 14.0	16.0 x 16.0	-	0.45	31.0 x 31.0	OT
IC234-1004-023 *	0.5	100	14.0 x 14.0	16.0 x 16.0	-	0.67	33.6 x 33.6	OT
IC357-1004-002	0.5	100	14.0 x 14.0	16.0 x 16.0	-	0.50	31.9 x 31.9	OT
IC357-1004-014	0.5	100	14.0 x 14.0	16.0 x 16.0	-	0.55	31.9 x 31.9	OT
IC357-1004-053	0.5	100	14.0 x 14.0	16.0 x 16.0	-	0.55	31.9 x 31.9	OT
IC402-1004-002*	0.5	100	14.0 x 20.0	16.0 x 22.0	-	0.70	29.8 x 23.8	OT
IC500-1004-004	0.5	100	14.0 x 14.0	16.0 x 16.0	-	0.68	33.6 x 33.6	OT
IC51-1004-809	0.5	100	14.0 x 14.0	16.0 x 16.0	15.30	-	39.0 x 39.0	CL
IC51-1004-809-14	0.5	100	14.0 x 14.0	16.0 x 16.0	15.30	-	39.0 x 39.0	CL
IC51-1004-809-2	0.5	100	14.0 x 14.0	16.0 x 16.0	15.30	-	39.0 x 39.0	CL
IC51-1004-809-6	0.5	100	14.0 x 14.0	16.0 x 16.0	15.30	-	39.0 x 39.0	CL
IC51-809 KS-13929	0.5	100	14.0 x 14.0	17.2 x 17.2	15.90	-	39.0 x 39.0	CL
IC234-1204-058 *	0.5	120	16.0 x 16.0	18.0 x 18.0	--	0.67	35.6 x 35.6	OT
IC51-1204-1652	0.5	120	15.93 x 15.93	17.35 x 17.35	17.60		40.0 x 43.0	CL
IC201-026 KS-13784	0.5	128	20.0 x 20.0	22.0 x 22.0	-	0.69	37.0 x 36.7	OT
IC248-1284-007 *-*	0.5	128	14.0 x 20.0	16.0 x 22.0	-	0.67	37.4 x 43.4	OT
IC357-1284-033*	0.5	128	14.0 x 20.0	22.0 x 22.0	-	1.10	31.0 x 37.0	OT
IC500-1284-007	0.5	128	14.0 x 20.0	16.0 x 22.0	-	0.625	33.6 x 39.6	OT
IC51-1284-1433	0.5	128	14.0 x 20.0	16.0 x 22.0	15.2x21.2	-	46.0 x 43.0	CL
IC51-1284-1433-10	0.5	128	14.0 x 20.0	17.2 x 23.2	16.4x22.4	-	46.0 x 43.0	CL
IC51-1284-1433-19	0.5	128	14.0 x 20.0	17.9 x 23.9	16.4x22.4	-	46.0 x 43.0	CL
IC201-1444-026 *-2	0.5	144	20.0 x 20.0	22.0 x 22.0	-	0.69	37.0 x 37.0	OT
IC201-1444-034 *	0.5	144	20.0 x 20.0	22.0 x 22.0	-	0.65	37.0 x 37.0	OT
IC234-1444-007 *	0.5	144	20.0 x 20.0	22.0 x 22.0	-	-		OT
IC234-1444-016 *	0.5	144	20.0 x 20.0	22.0 x 22.0	-	0.8370	37.0 x 37.0	OT
IC402-1444-003*	0.5	144	20.0 x 20.0	22.0 x 22.0	21.30	0.80	30.0 x 30.0	OT
IC500-1444-002P-2	0.5	144	20.0 x 20.0	22.0 x 22.0		0.68	37.0 x 37.0	OT
IC51-1444-1354	0.5	144	20.0 x 20.0	22.0 x 22.0	21.30	1.00	43.0 x 47.0	CL
IC51-1444-1354-7	0.5	144	20.0 x 20.0	22.0 x 22.0	21.30	0.50	43.0 x 47.0	CL
IC51-1604-1350	0.5	160	24.0 x 24.0	26.0 x 26.0	25.30	-	46.0 x 50.0	CL
IC201-1764-033	0.5	176	24.0 x 24.0	26.0 x 26.0	-	0.67	40.0 x 46.0	OT
IC234-1764-002 *	0.5	176	24.0 x 24.0	26.0 x 26.0	-	1.00	46.0 x 46.0	OT
IC234-1764-005 *	0.5	176	24.0 x 24.0	26.0 x 26.0	-	1.00	46.0 x 46.0	OT
IC234-1764-121 *	0.5	176	24.0 x 24.0	26.0 x 26.0	-	1.00	40.0 x 46.0	OT
IC357-1764-061	0.5	176	24.0 x 24.0	26.0 x 24.0	-	0.615	41.0 x 41.0	OT
IC357-1764-081	0.5	176	24.0 x 24.0	26.0 x 24.0	-	0.6375	36.0 x 36.0	OT
IC357-1764-087	0.5	176	24.0 x 24.0	26.0 x 24.0	-	0.735	41.0 x 41.0	OT
IC357-1764-094	0.5	176	24.0 x 24.0	26.0 x 24.0	-	0.735	41.0 x 41.0	OT
IC51-1764-1505	0.5	176	24.0 x 24.0	26.0 x 26.0	25.30	0.90	46.0 x 50.0	CL
IC51-1764-1505-10	0.5	176	24.0 x 24.0	26.0 x 26.0	25.30	0.50	46.0 x 50.0	CL
IC51-1764-1505-5	0.5	176	24.0 x 24.0	26.0 x 26.0	25.30	0.50	46.0 x 50.0	CL
IC200-2084-009 *-*	0.5	208	28.0 x 28.0	31.2 x 31.2	-	1.40	51.2 x 52.2	OT
IC200-2084-010 *-*	0.5	208	28.0 x 28.0	30.6 x 30.6	-	1.40	50.6 x 50.6	OT
IC201-2084-001 *-*	0.5	208	28.0 x 28.0	30.0 x 30.0	-	1.50	45.0 x 45.0	OT
IC201-2084-029 *	0.5	208	28.0 x 28.0	30.6 x 30.6	-	1.67	45.6 x 45.6	OT
IC201-2084-096	0.5	208	28.0 x 28.0	30.0 x 30.0	-	0.55	45.0 x 45.0	OT
IC357-2084-019P-2	0.5	208	28.0 x 28.0	30.6 x 30.6	-	-	45.6 x 45.6	OT


cont'd next page

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com


Applicable Dimensions

Outline IC Body Dimensions





Outline Open Top Socket Dimensions



Outline Clamshell Socket Dimensions

0.50mm Pitch (continued

Part Number	Pitch	Pin Count	IC Dimensions Body A x B	IC Dimensions Tip-to-Tip C x D	IC Dimensions Parallel Clamp E	IC Dimensions 1/2 - IC height F	Socket Dimensions G X H	Package Type CL= Clamshell OT = Open Top
IC51-2084-1052-*	0.5	208	28.0 x 28.0	-	-	-	52.0 x 58.0	CL
IC51-2084-1052-1	0.5	208	28.0 x 28.0	30.0 x 30.0	29.30	-	52.0 x 58.0	CL
IC51-2084-1052-13	0.5	208	28.0 x 28.0	30.6 x 30.6	29.70	-	52.0 x 58.0	CL
IC51-2084-1052-35	0.5	208	28.0 x 28.0	31.2 x 31.2	29.95	-	52.0 x 58.0	CL
IC51-2084-1052-36	0.5	208	28.0 x 28.0	30.0 x 30.0	29.30	-	52.0 x 58.0	CL
IC51-2084-1052-9	0.5	208	28.0 x 28.0	30.6 x 30.6	29.70	-	52.0 x 58.0	CL
IC51-2084-1052-55	0.5	208	28.0 x 28.0	30.6 x 30.6	29.95	-	52.0 x 58.0	CL
IC51-2084-1509	0.5	208	27.7 x 27.7	31.2 x 31.2	29.80	-	52.0 x 58.0	CL
IC51-2084-1566	0.5	208	28.0 x 28.0	31.2 x 31.2	30.30	-	52.0 x 58.0	CL
IC217-2404-007 *	0.5	240	32.0 x 32.0	34.6 x 34.6	-	1.75	56.1 x 56.1	OT
IC234-2404-030 *	0.5	240	32.0 x 32.0	34.6 x 34.6	-	2.06	51.6 x 51.6	OT
IC51-2404-1655-2	0.5	240	32.0 x 32.0	34.6 x 34.6	33.80	-	56.0 x 62.0	CL
IC201-2564-002 *-*-2	0.5	256	28.0 x 40.0	30.6 x 40.6	-	1.50	45.6 x 57.6	OT
IC51-2724-1727	0.5	272	35.9 x 35.9	37.4 x 37.4	37.60	-	58.0 x 72.0	CL
IC201-3044-004	0.5	304	40.0 x 40.0	42.6 x 42.6	-	1.50	57.6 x 57.6	OT
IC51-3044-1471-2	0.5	304	39.95 x 39.95	42.6 x 42.6	41.90	-	66.0 x 72.0	CL
IC51-3044-1471-5	0.5	304	39.64 x 39.64	42.6 x 42.6	41.90	-	66.0 x 72.0	CL

0.635mm Pitch

IC51-1004-827	0.635	100	22.86 x 22x86	22.35 x 22.35	-	-	47.5 x 34.0	OT
IC211-1324-002 *-*	0.635	132	24.10 x 24.10	28.0 x 28.0	-	-	47.4 x 47.4	OT
IC51-1324-828	0.635	132	27.94 x 27.94	27.43 x 27.43	-	-	53.5 x 40.0	OT
IC51-1964-1952	0.635	196	34.29 x 34.29	58.0 x 58.0	-	-	70.0 x 83.0	OT

0.65mm Pitch

IC51-0484-652	0.65	48	6.0 x 9.0	7.4 x 8.8	7.00	-	34.0 x 34.5	CL
QFP11T052-004 A102221*	0.65	52	10.0 x 10.0	13.2 x 13.2	13.30	-	34.0 x 37.0	CL
IC234-0564-084 *	0.65	56	10.0 x 10.0	12.8 x 12.8	-	1.50	29.3 x 29.3	OT
IC51-0564-680	0.65	56	10.0 x 10.0	13.2 x 13.2	11.80	-	34.0 x 35.5	CL
IC357-0644-077	0.65	64	12.0 x 12.0	14.0 x 14.0	-	0.6375	29.0 x 29.0	OT
IC51-0644-1586	0.65	64	12.0 x 12.0	15.3 x 15.3	13.90	-	36.0 x 39.0	CL
IC51-0644-1602	0.65	64	12.0 x 12.0	14.0 x 14.0	13.10	-	20.0 x 42.0	CL
IC51-0684-734	0.65	68	10.0 x 14.0	13.2 x 17.2	11.80 x 15.80	-	37.0 x 41.0	CL
IC201-0804-005 *-*	0.65	80	14.0 x 20.0	17.9 x 23.9	-	1.22	32.9 x 38.9	OT
IC201-0804-012 *-*	0.65	80	14.0 x 14.0	17.2 x 17.2	-	0.92	29.2 x 32.2	OT
IC234-0804-019 *	0.65	80	14.0 x 14.0	16.8 x 16.8	-	1.35	32.2 x 32.2	OT
IC357-0804-003	0.65	80	14.0 x 14.0	17.2 x 17.2	-	0.50	31.9 x 31.9	OT

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

0.65mm Pitch (cont'd)

Part Numbers	Pitch	Pin Count	A x B	C x D	E	F	G x H	Type
IC500-0804-005	0.65	80	14.0 x 14.0	16.0 x 16.0	-	1.07	32.0 x 32.2	OT
IC51-0804-711	0.65	80	14.0 x 14.0	17.2 x 17.2	15.80	-	37.0 x 41.0	CL
IC51-0804-795	0.65	80	14.0 x 14.0	16.0 x 16.0	15.30	-	37.0 x 41.0	CL
IC51-0804-956-2	0.65	80	14.0 x 14.0	17.2 x 17.2	16.40	-	34.0 x 42.5	CL
IC51-795 KS-13930	0.65	80	14.0 x 14.0	17.2 x 17.2	15.90	-	37.0 x 41.0	CL
QFP11T080-008	0.65	80	14.0 x 14.0	16.0 x 16.0	15.30	-	39.0 x 39,5	CL
IC201-1004-016 *-*	0.65	100	14.0 x 20.0	17.9 x 23.9	-	1.28	32.9 x 38.9	OT
IC201-1004-028 *	0.65	100	14.0 x 20.0	17.2 x 23.2	-	1.20	32.2 x 38.2	OT
IC201-1004-050 *	0.65	100	14.0 x 20.0	16.0 x 22.0	-	0.75	31.0 x 37.0	OT
IC234-0644-006 *	0.65	100	14.0 x 20.0	16.0 x 22.0	-	0.875	31.0 x 37.0	OT
IC234-1004-008 *	0.65	100	14.0 x 20.0	18.15 x 24.15	-	1.33	32.2 x 38.2	OT
IC234-1004-009 *	0.65	100	14.0 x 20.0	18.15 x 24.15	-	1.33	32.2 x 38.2	OT
IC234-1004-013 *	0.65	100	14.0 x 20.0	17.2 x 23.2	-	1.35	32.2 x 38.2	OT
IC234-1004-014 *	0.65	100	14.0 x 20.0	16.0 x 22.0	-	0.67	32.2 x 38.2	OT
IC234-1004-015 *	0.65	100	14.0 x 20.0	16.75 x 22.75	-	0.67	32.2 x 38.2	OT
IC234-1004-028 *	0.65	100	14.0 x 20.0	18.4 x 24.4	-	1.33	32.2 x 38.2	OT
IC234-1004-033 *	0.65	100	14.0 x 20.0	17.9 x 23.9	-	1.33	32.2 x 38.2	OT
IC51-1004-814-1	0.65	100	14.0 x 20.0	17.9 x 23.9	17.0 x 23.0	-	34.0 x 42.5	CL
IC51-1004-814-2	0.65	100	14.0 x 20.0	17.2 x 23.2	16.4 x 22.4	-	34.0 x 42.5	CL
IC51-1004-814-6	0.65	100	14.0 x 20.0	17.2 x 23.2	15.8 x 21.8	-	34.0 x 42.5	CL
IC51-1004-814-7	0.65	100	14.0 x 20.0	17.2 x 23.2	16.4 x 22.4	-	34.0 x 42.5	CL
IC51-814 KS-12033	0.65	100	14.0 x 20.0	17.2 x 23.2	16.4 x 22.4	-	34.0 x 42.5	CL
IC234-1124-093 *	0.65	112	24.0 x 24.0	23.2 x 23.2	-	1.30	38.2 x 38.2	OT
IC500-1124-001	0.65	112	20.0 x 20.0	22.0 x 22.0	-	0.68	38.2 x 38.2	OT
IC51-1124-1036-2	0.65	112	20.0 x 20.0	23.2 x 23.2	22.30	-	34.0 x 42.5	CL
IC51-1124-1036-YED	0.65	112	20.0 x 20.0	22.0 x 22.0	21.00	-	34.0 x 42.5	CL
IC201-006 AC-04462	0.65	144	28.0 x 28.0	31.2 x 31.2	-	1.65	46.2 x 46.2	OT
IC51-1444-1014	0.65	144	28.0 x 28.0	31.2 x 31.2	30.40	-	44.0 x 57.0	CL
IC51-1444-1014-3	0.65	144	28.0 x 28.0	31.2 x 31.2	30.40	-	44.0 x 57.0	CL
IC201-1604-006 *-*	0.65	160	28.0 x 28.0	31.2 x 31.2	-	1.65	46.2 x 46.2	OT
IC234-1604-018 *	0.65	160	27.9 x 27.9	32.0 x 32.0	-	1.48	47.6 x 47.6	OT
IC234-1604-032 *	0.65	160	28.0 x 28.0	30.6 x 30.6	-	1.66	47.6 x 47.6	OT
IC51-1604-845-1	0.65	160	28.0 x 28.0	31.6 x 31.6	30.60	-	44.0 x 57.0	CL
IC51-1604-845-2	0.65	160	28.0 x 28.0	31.6 x 31.6	30.60	-	44.0 x 57.0	CL
IC51-1604-845-4	0.65	160	28.0 x 28.0	31.2 x 31.2	30.20	-	44.0 x 57.0	CL
IC51-1604-845-8	0.65	160	28.0 x 28.0	31.2 x 31.2	30.20	-	44.0 x 57.0	CL
IC51-1604-926	0.65	160	29.0 x 29.0	30.2 x 31.4	30.40	-	44.0 x 57.0	CL


0.80mm Pitch

Part Number	Pitch	Pins	A x B	C x D	E	F	G x H	Type
IC234-0324-044 *	0.8	32	7.0 x 7.0	9.0 x 9.0	-	0.67	26.6 x 26.6	OT
IC51-0324-1498	0.8	32	7.0 x 7.0	9.0 x 9.0	8.4	-	30.0 x 35.5	CL
IC51-0324-354	0.8	32	7.4 x 7.4	9.8 x 9.8	8.4	-	30.0 x 37.5	CL
IC234-0444-037 *	0.8	44	10.0 x 10.0	12.0 x 12.0	-	0.45	29.6 x 29.6	OT
IC234-0444-054 *	0.8	44	9.95 x 9.95	12.8 x 12.8	-	1.35	29.6 x 29.5	OT
IC248-0444-001 *	0.8	44	10.0 x 10.0	13.2 x 13.2	-	0.80	27.0 x 27.0	OT
IC51-0444-1195-3	0.8	44	10.0 x 10.0	12.6 x 12.6	11.5	-	40.0 x 40.0	CL
IC51-0444-467	0.8	44	10.0 x 10.0	13.9 x 13.9	11.5	-	40.0 x 40.0	CL
QFP11T044-001	0.8	44	10.0 x 10.0	12.0 x 12.0	11.3	-	32.0 x 35.0	CL
IC51-0444-798	0.8	44	10.0 x 10.0	13.9 x 13.9	12.9	-	40.0 x 40.0	CL
IC51-0444-825	0.8	44	10.0 x 10.0	12.6 x 12.6	11.8	-	40.0 x 40.0	CL
IC51-467.AC-15687	0.8	44	10.0 x 10.0	12.0 x 12.0	11.6	-	37.5 x 37.5	CL
IC51-467.KS-11787	0.8	44	10.0 x 10.0	12.0 x 12.0	11.6	-	37.5 x 37.5	CL
IC51-467.KS-11247	0.8	44	10.0 x 10.0	13.2 x 13.2	12.1	-	40.0 x 40.0	CL
IC51-081-KS-14028	0.8	48	12.0 x 12.0	15.3 x 15.3	14.0	-	36.0 x 39.0	CL
IC51-0564-924	0.8	56	10.0 x 14.0	13.2 x 1 7.2	11.8 x 15.8	-	37.0 x 41.0	CL


cont'd next page

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com


Outline IC Body Dimensions



Applicable Dimensions



Outline Open Top
Socket Dimensions



Outline Clamshell
Socket Dimensions

0.80mm Pitch (cont'd)

Part Number	Pitch	Pin Count	IC Dimensions Body A x B	Tip-to-Tip C x D	Parallel Clamp E	1/2 - IC height F	Socket Dimensions G X H	Package Type CL= Clamshell OT = Open Top
IC51-0604-361	0.8	60	16.0 x 16.0	18.3 x 18.3	16.5	-	37.0 x 44.0	CL
IC51-0604-468	0.8	60	14.0 x 14.0	17.2 x 17.2	15.8	-	38.0 x 43.0	CL
IC234-0644-024 *	0.8	64	14.0 x 14.0	16.8 x 16.8	-	1.40	32.2 x 32.2	OT
IC51-0644-1240-2	0.8	64	14.0 x 14.0	16.5 x 16.5	15.0	-	42.5 x 34.0	CL
IC51-0644-692-*	0.8	64	14.0 x 14.0	-	-	-	22.0 x 26.0	CL
IC51-0644-824-1	0.8	64	14.0 x 14.0	17.2 x 17.2	15.8	-	30.0 x 42.5	CL
IC51-0644-824-2	0.8	64	14.0 x 14.0	17.9 x 17.9	16.7	-	30.0 x4 2.5	CL
IC51-0644-824-3	0.8	64	14.0 x 14.0	16.2 x 16.2	15.4	-	30.0 x4 2.5	CL
IC51-0644-824-5	0.8	64	14.0 x 14.0	16.0 x 16.0	15.2	-	30.0 x 42.5	CL
IC218-0724-001 *-*	0.8	72	13.2 x 18.0	18.8 x 23.6	-	0.90	31.8 x 36.6	OT
IC51-0724-698	0.8	72	16.0 x 20.0	18.2 x 23.1	16.6 x 21.5	-	36.0 x 44.5	CL
IC201-0804-032 *	0.8	80	14.0 x 20.0	17.2 x 23.2	-	-	38.2 x 38.2	OT
IC218-0804-002 *-*	0.8	80	14.0 x 20.0	19.2 x 25.2		0.95	31.0 x 38.2	OT
IC218-0804-007 *	0.8	80	14.0 x 14.0	16.0 x 16.0	-	-	32.2 x 29.2	OT
IC234-0804-001 *	0.8	80	14.0 x 20.0	19.1 x 25.1	-	1.60	32.2 x 32.2	OT
IC51-0804-819-1	0.8	80	14.0 x 20.0	17.9 x 23.9	16.9 x 22.9	-	34.0 x 42.5	CL
IC51-0804-819-2	0.8	80	14.0 x 20.0	17.6 x 23.6	16.3 x 22.3	-	34.0 x 42.5	CL
IC51-0804-819-6	0.8	80	14.0 x 20.0	16.8 x 22.8	15.6 x 21.6	-	34.0 x 42.5	CL
IC51-0804-819-8	0.8	80	14.0 x 20.0	17.2 x 23.8	16.9 x 22.9	-	24.0 x 42.5	CL
IC51-819.KS-12720	0.8	80	14.0 x 20.0	17.2 x 23.2	16.0 x 22.0		34.0 x 42.5	CL
IC234-1204-017 *	0.8	120	28.0 x 28.0	31.2 x 31.2	-	1.70	46.2 x 46.2	OT
IC234-1204-065 *	0.8	120	28.0 x 28.0	32.8 x 32.8	-	1.63	48.4 x 48.4	OT
IC51-1204-1497	0.8	120	28.0 x 28.0	29.7 x 29.7	30.5	-	60.0 x 58.0	CL
IC51-1204-1646	0.8	120	28.0 x 28.0	31.2 x 31.2	30.8	-	57.0 x 30.6	CL
IC200-1284-001 *-*	0.8	128	28.0 x 28.0	32.0 x 32.0	-	1.50	52.0 x 52.0	OT
IC51-1284-844-1	0.8	128	28.0 x 28.0	31.2 x 31.2	30.6	-	44.0 x 57.0	CL
IC234-017 AC-11315	0.8	128	28.0 x 28.0	31.2 x 31.2	-	1.70	34.0 x 34.0	OT
IC51-1284-617	0.8	128	29.0 x 29.0	31.2 x 31.2	30.60	-	44.0 x 57.0	CL
IC51-1284-976-*	0.8	128	28.0 x 28.0	31.2 x 31.2	30.6	-	44.0 x 57.0	CL

1.00mm Pitch

IC51-0444-615	1.0	44	14.0 x 14.0	17.2 x 17.2	15.80		34.0 x 42.5	CL
IC51-0444-621	1.0	44	14.0 x 14.0	17.9 x 17.9	17.00		34.0 x 42.5	CL
IC51-621 KS-8966	1.0	44	14.0 x 14.0	17.9 x 17.9	17.00		34.0 x 42.5	CL
IC51-0604-497-2	1.0	60	16.0 x 20.0	17.9 x 23.9	17.0 x 23.0		34.0 x 42.5	CL
IC201-0644-019 *-*	1.0	64	14.0 x 20.0	17.9 x 23.9		1.22	32.9 x 38.9	OT
IC51-0644-472	1.0	64	14.0 x 20.0	19.6 x 23.6	16.2 x 22.2		34.0 x 42.5	CL
IC51-0644-820-1	1.0	64	14.0 x 20.0	18.7 x 24.7	17.0 x 23.0		32.9 x 38.9	CL
IC51-0644-820-2	1.0	64	14.0 x 20.0	17.6 x 23.6	16.3 x 22.3		34.0 x 42.5	CL
IC51-0644-820-3	1.0	64	14.0 x 20.0	18.0 x 24.0	16.9 x 22.9		34.0 x 42.5	CL
IC51-0644-820-4	1.0	64	14.0 x 20.0	17.2 x 23.2	15.8 x 21.8		34.0 x 42.5	CL
IC51-820-2 KS-9376	1.0	64	14.0 x 20.0	17.2 x 23.2	17.0 x 23.0		34.0 x 42.5	CL

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Yamaichi Electronics:

IC201-0644-003 IC201-1004-008 IC201-1444-026N-2 IC234-0484-039N IC51-0484-806 IC51-0644-807 IC51-1004-809 IC234-1604-032P IC51-0644-824-5 IC200-2084-010 IC234-0644-024-N IC234-1004-023N IC51-0324-1498 IC51-0804-808 IC51-1284-1433 IC51-1284-1788 IC51-1444-1354-7 IC234-1764-059P IC201-0644-040 IC234-1604-018N

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP