ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction


All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Brandywine Communications / JXI2 PMC-SyncClock32-UNIV* at our website: *Click HERE*

brandywine communications

PMC-SyncClock32 Universal

- IRIG A & B, NASA 36 and 1 PPS inputs standard
- 3.3V or 5V signaling levels
- HaveQuick sync option
- Propagation delay compensation
- Zero latency time reads
- Match Time output
- IRIG B time code output
- External Event time tags
- *On-board* GPS receiver option *New!*
- Three user programmable rates
- Conduction Cooled Version *New!*



The PMC-SyncClock32 from Brandywine Communications is an advanced Mezzanine Card (PMC) module. Precision time is provided to the host computer with zero latency. The on-board microprocessor automatically synchronizes the clock to reference signal inputs. The reference signal inputs handled by the PMC in its standard configuration are IRIG's A and B, NASA 36 and 1 PPS. Alternatively, the clock in the PMC can be set using commands from host computer and free run using its on-board oscillator as the time base.

When synchronizing to time codes or 1 PPS the microprocessor constantly measures the time error between the on-board clock and the reference input code and adjusts the error measurement for propagation delay. When the disciplined TCXO option is selected the residual error is used in an adaptive gain loop to adjust the frequency of the 10 MHz oscillator for minimum error. Before being used as the time reference, the input code reference is checked (to code carrier resolution) for consistency with itself. If the incoming code is missing or corrupted by noise the on-board clock is updated by the 10 MHz oscillator. When the input code is again useable the correction loop is smoothly closed.

58 bits of BCD time are available to the host computer using two zero latency time reads. The time message contains units of microseconds through units of years. A status word is available using an additional read.

The time-of-occurrence of external events may be captured (time-tagged) by using the Event Time input. When the event input is sensed the current time is saved in a buffer for later interrogation by the host. The resolution of the time tag is 100 nanoseconds.

The Match Time feature may be used to automatically initiate or terminate an external process. The resolution of the Match Time comparison is one microsecond. The Match Time output is asserted when the time of the internal clock matches that of the user input start time. The Match Time output may be terminated by a user command or when the previously set stop time is encountered.

Three user programmable pulse rates are provided. Two pulse rates, Clock Low and Clock High, are available on the multi-pin connector. The third pulse rate provides heartbeat timing to the host computer and is also available on the multi-pin connector. The divider for each of the three pulse rate generators is programmable by the host computer over the range 2–65,535. The inputs to the rate generators are 3 MHz or 100 Hz for the heartbeat, 100 PPS for Clock Low and 3 MHz for Clock High.

The GPS synchronization option offers worldwide time transfer capability to the PMC-SyncClock32. Very precise synchronization, automatic leap year and leap second correction, plus accurate position information are additional benefits provided by the GPS option.

1153 Warner Ave. • Tustin, CA 92780 • 714-755-1050 phone • 714-755-0175 fax • Toll free 877-FOR-SYNC
www.brandywinecomm.com info@brandywinecomm.com

brandywine communications

PMC-SyncClock32 UNIV Specifications

General Input Specifications

Input Codes	IRIG A & B, NASA 36
Input Amplitude	.25 to 10 Vpp
Input Impedance	>10k Ohms
Ratio	2:1 to 4:1
Frequency Error	100 PPM maximum
Code Sync Accuracy	One microsecond
1 PPS input	RS-422 or TTL, positive edge
1 PPS Sync Accuracy	300 nanoseconds
External Event	
Resolution	100 nanoseconds–units year
Min. event spacing	None

General Output Specifications

IRIG B DC Shift	TTL
Match Pulse	TTL level at Start–Stop time
Resolution	Microseconds–eight millisecond
Clock Low	TTL, negative going
Clock Divisor	2–65,535
Clock Input	100 PPS
Default output	1 PPS
Clock High	TTL, negative going
Clock Divisor	2–65,535
Clock Input	3 MPPS
Default output	76.923 kPPS
Heartbeat Rate	Interrupt, flag, TTL, negative going
Clock Divisor	2–65,535
Clock Input	100 PPS or 3 MPPS
Default output	1 kPPS
BCD Time	Microseconds–unit year on demand, zero latency 58 bits in two 32 bit words
Status word	8 bits
Status LED	Flashes coded patterns
Interrupts	External Event, RAM FIFO, Heartbeat, Match Time
Flags	Dual Port RAM data ready, FIFO data ready, In sync, Heartbeat, Match Time, External Event
Connectors	SMB, high density IEEE–1284
MTBF	141,000 hours per Mil-217-F, Notice 2, 25° C, ground benign

Mechanical & Environmental

Size	74mm X 149mm single CMC
Type	Single-slot 32 bit 3.3V or 5V PCI
Power	
+ 5 Vdc	±5%,150 mA maximum
+12 Vdc	±5%, 60 mA maximum
-12 Vdc	±5%, 25 mA maximum
Operating Temperature	0°C to +55°C
Storage Temperature	-40°C to +85°C
Humidity	To 95% without condensation

Options

GPS Sync Input (external)	C/A code
Sync Accuracy	100 nanoseconds
Position Accuracy	25 meters SEP
Tracking	Eight parallel channels
Antenna*	L1, 25' cable
Antenna Options	
Hi-gain	L1, mast mount, 100' cable
Fiber Optic Kit	Fiber optic transmitter/receiver pair for long antenna cable runs
Differential GPS Inputs	Per RTCM 104
IRIG B Modulated Output	2.5 Vpp into 600 Ohms
Input Code Isolation	Transformer coupling
Input Codes	IRIG G, XR3, 2137, IRIG E, 109-60
Output Codes	IRIG A, NASA 36, IRIG G
Eight External Event Inputs	TTL, positive or negative edge
Have Quick Input	Per ICD–GPS–060
Have Quick Output	Per ICD–GPS–060
Binary Time Words	Replaces BCD
Oscillator Upgrades	Disciplined TCXO, 1 PPM
1 PPS 10 Vdc input	Sync input, +10 Vdc, 50 Ohms
New! Conduction Cooled	
On-board battery back up for oscillator	

*consult factory for cable length options

Other Brandywine Communications Products

Video Character Inserters
Time-Message Displays
VME, VXI, PC/104,PCI, CPCI, ISA Computer Clock Synchronization Boards
Network Time Servers and Network Time Displays
Frequency Generation and Distribution Instruments
Dual & Triple Redundant Systems

© brandywine communications 2006

1/4/2006

1153 Warner Ave. • Tustin, CA 92780 • 714-755-1050 phone • 714-755-0175 fax • Toll free 877-FOR-SYNC
http://www.brandywinecomm.com/ info@brandywinecomm.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP