ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Astronics / C&H Technologies VX405C* at our website: ***Click HERE***

C&H Technologies, Inc. • 445 Round Rock West Drive • Round Rock, TX 78681-5012
(512) 733-2621 • FAX (512) 733-2629 • www.chtech.com



M207 Precision Oscillator

The M207 is a precision oscillator source that provides a highly accurate and stable clock reference that can be used as a frequency or time reference. Using selectable switches, the output of the on-board ovenized oscillator can be output as is or be divided by any value from 2 to 16383. The resulting output can be directed to a front SMA connector and/or to either or both of the M-Module triggers. The output can be a 100ns pulse or a square wave.

Specifications:

Ovenized Oscillator:

Nominal Frequency:	10MHz
Stability (Freq. vs. Temp)	±0.01ppm
Aging (Freq. vs. Time)	
1st year	±0.1ppm
10 years	±1.0ppm
Cal. (Freq. vs. Control)	±1.0ppm
Warm Up (Freq. Ref. to 1 hr.)	
5 minutes	±0.1ppm
30 minutes	±0.01ppm

Front panel accessible calibration 25-turn potentiometer provided for 10 year adjustability.

Pulse Output: (front panel)

High, I_{OH} = -24mA	3.76V min.
Low, I_{OL} = 24mA	0.44V max.
Source/Sink	±50mA
Rise/Fall (0.8 to 2.0V)	1.5ns
Impedance (selectable)	3 or 50Ω

Pulse Width: 100ns*

* Pulse width is 50% of period when "Square Wave Output" or "No divide" output is selected.

Outputs:

- Front Panel
- M-Module Trig A
- M-Module Trig B

Switch Controls:

- Divide-by-N Value (3 to 16383)
- Clock Out Select
  - Square Wave Output (N ÷ 2)
  - Divide-By-2
  - No divide (10MHz output)
  - Divide-By-N
- M-Trigger A/B Output Enable
- Front Panel Output Enable
- Front Panel Output Impedance

Front Panel Connector: SMA

Temperature:

Operating:	0°C to 50°C
Storage:	-40°C to 70°C

Power:

+5V (during warm-up)	500mA
+5V (after warm-up)	250mA

M Module Compliance

Complies with ANSI/VITA Std. 12-1996 for single-wide M-Modules; however, the module does require or support data transfers.

Compatible with VXI, VME, PCI, cPCI and other M Module carriers.

Applications

- Frequency or Time Reference
- M-Module Triggering
- Synchronization of data acquisition hardware

Ordering Information

Part Number 11028610-0001

Additional Information

User Manuals for C&H carriers and this module can be found on our website at www.chtech.com.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP