ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.


- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Clippard ET-3M-12* at our website: *Click HERE*

3-Way Normally-Closed Valves, In-Line & Manifold



In-Line Mount Manifold Mount



Pressure Range: Vac. to 105 psig	Pressure Range: Vac. to 50 psig	Pressure Range: Vac. to 25 psig	Voltage: 12 VDC	Voltage: 24 VDC	Part No. In-Line Mount	Part No. Manifold Mount
					0.025″ Pin Connector	
•			•		*EC-3-12	*EC-3M-12
•				•	*EC-3-24	*EC-3M-24
	•		•		*EC-3-12-L	*EC-3M-12-L
	•			•	*EC-3-24-L	*EC-3M-24-L
		•	•		*EC-3-12-H	*EC-3M-12-H
		•		•	*EC-3-24-H	*EC-3M-24-H
					Spade Terminals	
•			•		*ET-3-12	*ET-3M-12
•				•	*ET-3-24	*ET-3M-24
	•		•		*ET-3-12-L	*ET-3M-12-L
	•			•	*ET-3-24-L	*ET-3M-24-L
		•	•		*ET-3-12-H	*ET-3M-12-H
		•		•	*ET-3-24-H	*ET-3M-24-H
					Wire Leads Side (Radial)	
•		•	•		*EV-3-12	*EV-3M-12
•				•	*EV-3-24	*EV-3M-24
	•		•		*EV-3-12-L	*EV-3M-12-L
	•			•	*EV-3-24-L	*EV-3M-24-L
		•	•		*EV-3-12-H	*EV-3M-12-H
		•		•	*EV-3-24-H	*EV-3M-24-H
					Wire Leads Top (Axial)	
•			•		*EW-3-12	*EW-3M-12
•				•	*EW-3-24	*EW-3M-24
	•		•		*EW-3-12-L	*EW-3M-12-L
	•			•	*EW-3-24-L	*EW-3M-24-L
		•	•		*EW-3-12-H	*EW-3M-12-H
		•		•	*EW-3-24-H	*EW-3M-24-H

Medium: Clean, dry air (40 micron filter)

Power Consumption: 0.67 watt (CR Series: 1.2 watt)


Temperature Range: 32 to 180°F, CR Series: 32 to 150°F

Response: 5 to 10 milliseconds (nominal)

Operating Range: 90 to 150% of rated voltage (CR Series: ±10%)

Ports: #10-32

RoHS



In-Line Mount Manifold Mount

Valve Series (*)	Standard	Non-Standard
Standard	(blank)	
Oxygen Clean	O-	*See Pages 179 & 180 for further information*
Analytical Series**	A-	
Corrosion-Resistant *(not std. on "EW")*	CR-	
Options *(add to end of Part No.)*		
FKM Seals	-V	
EPR Seals		-E
Silicone Seals		-S
Diode		-D

Pressure Range	Suffix	Air Flow
28″ Hg Vac. to 105 psig	(blank)	0.6 scfm @ 100 psig
28″ Hg Vac. to 50 psig	-L	0.5 scfm @ 50 psig
28″ Hg Vac. to 25 psig	-H	0.45 scfm @ 25 psig

Example Part No's: ET-3-12-S O-EW-3-24

See Page 181 for mounting options

** Available on manifold mount valves only

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP