

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Commtech SuperFastcom-RS-422 / 485* at our website: *Click HERE*

COMMTECH
COMMUNICATION • TECHNOLOGIES

2006

Phone: (316) 636-1131
Fax: (316) 636-1163

"FASTCOM™ is the solution to all of your industrial/commercial serial communication needs"

SuperFastcom

Four Port High Speed Synchronous Serial Adapter RS422/485 Interface

$749.00

ADD TO CART

The SuperFASTCOM PCI adapter is a very high speed, four channel, synchronous serial communications adapter designed for use in Windows and Linux based industrial/commercial systems. Its outstanding features include data rates up to 40 Mbits/s[1] and the ability to buffer up to 4 Gigabytes of data (Windows 2000) in system memory.

The SuperFASTCOM supports all standard synchronous protocols (HDLC, SDLC) and their variations as well as all standard asynchronous data formats at data rates up to 40 Mbits/s[1]. The external on-board clock generator provides a high-speed clock source for your system and eliminates the need for an external clock. The board also features high-speed RS422 / RS485 drivers/receivers with on board line termination.

SuperFastcom Cable

DB78 plug to four DB25 plugs (Included)

Programming is simplified with the inclusion of drivers, example programs, and comprehensive documentation supplied on the Fastcom CD. Software drivers are included for Windows 2000/NT/XP, and Linux Kernel 2.4.x and 2.6.x. The SuperFASTCOM provides high speed and high reliability while greatly reducing development time and system complexity.

The following diagram illustrates the basic structure of the SuperFASTCOM:

Basic Structure Diagram for the SuperFastcom

The SuperFASTCOM family of adapters also includes RS232 PCI, PC/104+, cPCI, and cPCI Rear I/O Bus Styles.

SPECIFICATIONS:

- **COMM. CONTROLLER:**
  - INFINEON PEB20534 (Data Sheet)
- **DRIVERS/RECEIVERS:** High-speed RS422 / RS485
- **SIGNALS:**
  - SD, RD, RTS, CTS, DCD, TT, RT, ST
- **BUS INTERFACE:** PCI 32 bit (standard PCI)
- **MAXIMUM DATA RATE:** 40 Mbits/s[1] per channel

POWER REQUIREMENTS:

- +5V @ 450mA (typical)

ENVIRONMENT:

- Operating Temperature Range: 0 to 70 C
- Humidity: 0 to 90% (non-condensing)

FEATURES:

- High speed, up to 40Mbits/s[1]
- Drivers: RS422 / RS485 multi-drop
- **Serial Communication Controllers (SCCs)**
  - Four independent channels
  - Full duplex data rates on each channel of up to 10Mbits/s sync - 2Mbit/s with DPLL, 2 Mbits/s async
  - 17 DWORDs deep receive FIFO per SCC (+ 128 DWORDs central receive FIFO)
  - 8 DWORDs deep transmit FIFO per SCC (+128 DWORDs central transmit FIFO)
- **Serial Interface**
  - On-chip clock generation or external clock sources
  - On-chip DPLLs for clock recovery[2]
  - Baud rate generator
  - Clock gating signals
  - Clock gapping capability
  - Programmable time-slot capability for connection to TDM interfaces
  - Encoding Schemes: NRZ (Non-Return-To-Zero), NRZI (Non-Return-To-Zero-Inverted), FM0 (Bi-Phase Space), FM1 (Bi-Phase Mark), Manchester (Bi-Phase)
  - Optional data flow control using modem control lines (/RTS, /CTS, CD)
  - **HDLC/SDLC Protocol Modes**
    - Automatic flag detection and transmission
    - Shared opening and closing flag
    - Generation of interframe-time fill '1's or flags
    - Detection of receive line status
    - Zero bit insertion and deletion
    - CRC generation and checking (CRC-CCITT or CRC-32)
    - Transparent CRC option per channel and/or per frame
    - Programmable Preamble (8bit) with selectable repetition rate
    - Error detection (abort, long frame, CRC error, short frame)
  - **Bit Synchronous PPP Mode**
    - Bit oriented transmission of HDLC frame (flag, data, CRC, flag)
    - Zero bit insertion/deletion
    - 15 consecutive '1' bits abort sequence
  - **Asynchronous (ASYNC) Protocol Mode**
    - Selectable character length (5 to 8 bits)
    - Even, odd, forced or no parity generation/checking
    - 1 or 2 stop bits
    - Break detection/generation
    - In-banc flow control by XON/XOFF
    - Immediate character insertion
    - Termination character detection for end of block identification
    - Time out detection
    - Error detection (parity error, framing error)
  - **BISYNC Protocol Mode**
    - Programmable 6/8 bit SYN pattern (MONOSYNC)
    - Programmable 12/16 bit SYN pattern (BISYNC)
    - Selectable character length (5 to 8 bits)
    - Even, Odd, forced or no parity generation/checking
    - Generation of interframe-time fill '1's or SYN characters
    - CRC generation (CRC-16 or CRC-CCITT)
    - Transparent CRC option per channel and/or per frame
    - Programmable Preamble (8bit) with selectable repetition rate
    - Termination character detection for end of block identification
    - Error detection (parity error, framing error)
  - **Extended Transparent Mode**
    - Fully bit transparent (no framing, no bit manipulation)
    - Octet-aligned transmission and reception
  - **Protocol and Mode Independent**
    - Data bit inversion
    - Data overflow and underrun detection
    - Timer
- **Protocol Support**
  - **Address Recognition Modes**
    - No address recognition (Address Mode 0)
    - 8-bit (high byte) address recognition (Address Mode 1)
    - 8-bit (low byte) or 16-bit (high and low byte address recognition (Non Auto Mode)
- On-chip Rx and Tx data buffer; 128 32-bit words each
- Programmable buffer size in transmit direction per channel; buffer allocation in receive direction on request
- Internal test loop capability
- Programmable watermark for receive channels to control transfer of receive data to host memory
- Two programmable watermarks for each transmit channel. One controlling data loading from host memory and one controlling transfer of transmit data to the corresponding Serial Communication Controller (SCC)
- Status LEDs for system development/debugging
- Two programmable on-board clock generators (one internal, one external).
- Cable, documentation, and software drivers included
- **Certification:**
  - FCC compliant
  - CE marked
- **Designed and manufactured by COMMTECH, INC. Wichita, Kansas, USA**
- For a more complete and detailed list of features available on this card, please see the documentation for the PEB20534 serial communication controller

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP