

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Concurrent Technologies FP 110/008* at our website: ***Click HERE***

FP 110/008

N, E - Series


10/100/1000 Ethernet Switched Fabric Board

Key Features

FP 110/008 is an entry-level Ethernet Switched Fabric Board for use in CompactPCI® PICMG® 2.16 and VITA 31.1 Packet Switched Backplane environments.

- Supports up to 8 Packet Switched Backplane boards at 10/100/1000Mbps Ethernet speeds
- Includes rear port for fabric board to fabric board link and front panel Ethernet port via RJ45 connector
- Non-blocking Layer 2 switching for wire-speed throughput
- Virtual LAN (VLAN) and Quality of Service (QoS) support
- Extended temperature version available





Concurrent Technologies Plc 4 Gilberd Court, Colchester, Essex, CO4 9WN, UK
Tel: +44 (0)1206 752626 Fax: +44 (0)1206 751116

Concurrent Technologies Inc. 400 West Cummings Park, Suite 1300, Woburn, MA 01801, USA
Tel: (781) 933 5900 Fax: (781) 933 5911
email:info@gocct.com http://www.gocct.com

All companies and product names are trademarks of their respective organizations.
Specification subject to change; E and OE.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Specification

Ethernet Switched Fabric

- 10-port 10/100/1000Mbps Ethernet Switched Fabric board:
  - for use with PICMG® 2.16 and VITA 31.1 Packet Switched Backplanes (PSB)
- high performance Ethernet Switched Fabric:
  - implemented by Marvell® 88E6185 single-chip switch
  - Layer 2 non-blocking fabric
  - 8K MAC address cache with automatic learning and aging
  - full Virtual LAN (VLAN) support
- auto-negotiation on all ports:
  - 10/100/1000Mbps
  - full/half duplex
- EEPROM storage for user configuration data

Backplane Interfaces

- compatible with CompactPCI® Packet Switched Backplane (PSB):
  - conforms to the relevant sections of PICMG 2.16 R1.0
- compatible with ANSI/VITA 31.1-2003 Gigabit Ethernet on VME64x backplanes
- 8 PSB Ethernet ports for PSB node boards
- Ethernet port for linking with second fabric board:
  - enables redundant fabric board or
  - increases the number of Ethernet ports in the system
- J1, J2 and J3 connectors fitted as standard

Front Panel Interfaces

- RJ45 connector for 10/100/1000Mbps Ethernet User port
- speed and Link/Activity LEDs for all Ethernet ports
- 1 user LED
- reset switch (recessed)

System Management

- board health and status management:
  - conforms to PICMG® 2.9 R1.0 (System Management Specification)
  - implements the IPMB0 interface on J1
  - microcontroller-based Peripheral Management Controller
  - EEPROM for Field Replaceable Unit (FRU) and Sensor Data Record (SDR) storage
- network management:
  - extensive statistics counters per port
  - SNMP support for Remote Monitoring (RMON)
  - IGMP snooping (IPv4)
  - MLD snooping (IPv6)
  - accessible via the IPMB0 interface
- hot swap insertion and removal

Virtual LAN (VLAN)

- hardware based VLAN operation supporting:
  - port-based membership
  - IEEE 802.1Q VLAN (up to 4096 VLANs)
- offering security through:
  - controlling group membership
  - providing Layer 2 firewall protection

Quality of Service (QoS)

- prioritized packet streams for management of voice, video and data
- 4 hardware priority queues per port
- fixed priority or weighted fair queuing
- QoS traffic classification, determined by:
  - MAC address (SA or DA)
  - port ID
  - IEEE 802.1Q VLAN ID
  - IEEE 802.1p multimedia traffic tags
  - IPv4 Type of Service (TOS) or DiffServ
  - IPv6 Traffic Class

Electrical Specification

- +5V (+5%/-3%) @ 3.0A (maximum)
- +12V (+5%/-5%) @ 0.01A (maximum)
- +3.3V and -12V supplies are not required

Safety

- PCB (PWB) manufactured with flammability rating of UL 94V-0

Environmental Specification

- operating temperature:
  - 0°C to +55°C (N-Series)
  - -25°C to +70°C (E-Series)
- -40°C to +70°C (non-operating)
- 10% to 90% Relative Humidity, non-condensing

Mechanical Specification

- 6U form factor: 9.2 inches x 6.3 inches (233mm x 160mm)
- single slot: 0.8 inches (20.3mm)
- connectors: IEC-1076-4-101 for J1 and J3
- shock:
  20g, 11ms, ½ sine (operating);
  30g, 11ms, ½ sine (non-operating)
- vibration:
  5Hz-2000Hz at 2g, 0.38mm peak displacement (operating);
  5Hz-2000Hz at 5g, 0.76mm peak displacement (non-operating)

Please contact your local Concurrent Technologies sales office for further details on board build options and accessories.

Datasheet Code 1477/0217
© Concurrent Technologies 2017

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP