

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction


All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*

CompactPCI

PP 310/01x

Intel® Pentium® M Processor Intelligent Dual PMC Carrier



APPLICATIONS

The PP 310/01x is a PC-compatible high performance, high functionality, dual PMC CompactPCI® board supporting the 1.6 GHz or 1.1 GHz Intel® Pentium® M processor. The PP310/01x will operate in a system slot, a peripheral slot or independently from the CompactPCI bus. High-performance networking is provided by two Gigabit Ethernet links, and the board is compliant to the PICMG® 2.16 specification. Full system monitoring is provided by the PICMG 2.9 compliant IPMI interface. To simplify the board's integration many popular industry standard operating systems are supported. The PP 310/01x is suitable for a range of high-performance applications within the industrial control, telecomms, telemetry, scientific and aerospace markets. The board is plug compatible with the PP 110/01x family.

HIGHLIGHTS

- 1.6 GHz or 1.1 GHz Intel Pentium M processor:
  - 64 Kbytes L1 cache
  - 1 Mbyte L2 cache
  - no CPU fan needed; low power processor
- 1.8 GHz processor version available; see PP 312/01x datasheet
- Single slot (for all option combinations)
- Up to 2 Gbytes of DDR DRAM (with ECC)
- 2 x PMC module interfaces (32/64-bit at 33/66 MHz)
- High performance EIDE interfaces with optional on-board disk drive or optional CompactFlash™/Microdrive™ interface
- 2 x 10/100/1000Mbps Ethernet interfaces
- Dual Gigabit Packet Switching Backplane (PICMG 2.16)
- Graphics interface
- 32 Mbytes of Application Flash EPROM
- 512 Kbytes of BIOS Flash EPROM
- 512 Kbytes of battery backed SRAM
- CompactPCI controller:
  - operates in system slot or peripheral slot
  - 32/64-bit at 33/66 MHz CompactPCI interface
- Option to bypass CompactPCI bus (Satellite Mode)
- IPMI (Intelligent Platform Management Interface):
  - PICMG 2.9 (System Management Specification)
- Keyboard and Mouse interfaces
- Up to 3 x RS232 serial channel interfaces:
  - 1 or 2 on-board
  - 2 on optional Transition Module
- Watchdog timer and Long Duration Timer
- Extended temperature version available:
  - see PP 310/011-E datasheet
- Support for VxWorks®, Windows NT® , Windows® 2000, Windows® XP, Windows® XP Embedded, QNX®, Solaris™ and Linux®
- Optional Transition Module for rear panel I/O:
  - 2 x RS232 channels, Parallel Printer Port and Floppy Disk interfaces included

CONCURRENT TECHNOLOGIES

Concurrent Technologies Plc 4 Gilberd Court, Colchester, Essex, CO4 9WN, UK
Tel: +44 (0)1206 752626 Fax: +44 (0)1206 751116

Concurrent Technologies Inc 3840 Packard Road, Ann Arbor, MI 48108, USA
Tel: (734) 971 6309 Fax: (734) 971 6350

email: info@gocct.com http://www.gocct.com

Specification

Central Processor
- 1.6 GHz or 1.1 GHz Intel® Pentium® M processor:-
  - → 1.6 GHz uses µFC-PGA 478 (micro Flip-Chip Pin Grid Array) package
  - → 1.1 GHz uses µFC-BGA 479 (micro Flip-Chip Ball Grid Array) package
  - → 64 Kbytes of primary (L1) on-die cache
  - → 1 Mbyte of secondary (L2) on-die cache
  - → 400 MHz Front Side Bus (FSB)
  - → no CPU fan
- 1.8 GHz processor version available; see PP 312/01x datasheet
- utilizes 64-bit ServerWorks' GC-LE chipset
- provision for ITP debug port

DRAM
- supporting up to 2 Gbytes DDR ECC SDRAM:-
  - → up to 2 Gbytes provided via two SODIMM sockets
  - → error correction up to 4-bits
- accessible from Intel Pentium M processor or CompactPCI bus


Hard Disk Interfaces
- EIDE interface:-
  - → supports up to Ultra-DMA 100 for high performance drives
  - → two channels (primary and secondary)
  - → secondary channel can be used for on-board 2.5 inch hard disk drive (within a single slot); or, support for 1 or 2 CompactFlash modules or IBM®/Hitachi Microdrive Type II drives
  - → primary channel is accessible via Transition Module

Ethernet Interfaces
- implemented by Intel 82546EB LAN Controller via 64-bit PCI bus
- two channels supporting 10 Base-T, 100 Base-TX, 1000 Base-T:-
  - → support for PICMG 2.16 R1.0 - Packet Switching Backplane (PSB)
  - → optional support for rear panel RJ45's via Transition Module
- one channel switchable to front panel RJ45, supports 10 Base-T, 100Base-Tx and 1000Base-T

Graphics Interface
- implemented by a Silicon Motion SM722 providing:-
  - → 8 Mbytes video memory
  - → resolutions up to 1280 x 1024; supporting up to 16M colors
- accessed via a 26-way high-density connector on front panel

PMC Interface
- 2 x PMC sites; for both sites:-
  - → I/O via front panel
  - → I/O via J3 and J5
  - → 32/64-bit, 33/66 MHz PCI operation
  - → 3.3V or 5V signaling levels
- Transition Module provides rear I/O for both PMC sites

Firmware Support
- Phoenix® ServerBIOS™
- comprehensive Power-On Self-Test (POST)
- LAN boot firmware included



Battery Backed SRAM
- 512 Kbytes battery backed SRAM

Serial Interface
- up to 3 x RS232 serial channels:-
  - → 1 channel via a 26-way high-density connector on front panel
  - → either 1 channel via J5 or 2 channels via optional Transition Module
- 16550 compatible UART
- channels support RI, CTS, RTS, DSR, DTR and DCD

Other Peripheral Interfaces
- keyboard and mouse interfaces accessed via a 26-way high-density connector on front panel
- PC-compatible Real Time Clock (Year 2000 compliant)
- watchdog timer
- system fan monitor; CPU temperature monitor; voltages monitor:-
  - → all accessible via IPMI
- speaker interface
- 1 x USB (Universal Serial Bus) interface via J5 Transition Module
- 1 x 32-bit Long Duration Timer with processor interrupt capability
- LPC (Low Pin Count) bus via J5 to enable AD PP5/001 Transition Module to support:-
  - → floppy disk interface
  - → parallel printer port interface (ECP, EPP and IEEE1284)
  - → 2 x RS232 serial channels

Flash EPROMs
- 32 Mbytes of 8-bit Application Flash EPROM
- 512 Kbytes of 8-bit BIOS Flash EPROM

Software Support
- support for VxWorks, Windows NT, Windows 2000, Windows XP, Windows XP Embedded, QNX, Solaris and Linux

CompactPCI Interface
- compliant with PICMG 2.0 R3.0; 3.3V or 5V signaling levels:-
  - → universal signaling support
- J4 connector not fitted
- 33/66 MHz; 32/64-bit interface accessed via J1/J2 connectors
- utilizing a PCI-PCI bridge for off-board accesses
- PICMG 2.1 R2.0 Hot Swap Specification compatible
- operates as a System Slot controller or in a Peripheral slot
- option to disable CompactPCI interface (Satellite Mode):-
  - → receives power from CompactPCI bus
  - → board can be hot swapped in this mode

IPMI
- PICMG 2.9 R1.0 (System Management Specification)
- implements the IPMB0 interface
- on-board Baseboard Management Controller
- supports 8 Kbytes of non-volatile memory

Electrical Specification
- +5V@3.7A (typical at 1.6 GHz with 512 Mbytes DRAM); +5% / -3%
- +3.3V@6.5A; +5% / -3%
- +12V@0.01A; -12V@0.01A
- +12V and -12V routed to PMC slots

Safety
- PCB (PWB) manufactured with flammability rating of 94V-0

Environmental Specification
- 0°C to +55°C (operating); for extended temperature version see PP 310/011-E
- 10% to 90% Relative Humidity, non-condensing (operating)
- -40°C to +70°C (storage)
- 10% to 90% Relative Humidity, non-condensing (storage)

Mechanical Specification
- 6U form-factor: 9.2inches x 6.3inches (233mm x 160mm)
- single-slot: 0.8inches (20.3mm)
- connectors: IEC-1076-4-101 for J1-J5
- shock: 20g, 11ms, ½ sine (operating); 30g, 11ms, ½ sine (non-operating)
- vibration: 5Hz-2000Hz at 2g, 0.38mm peak displacement (operating); 5Hz-2000Hz at 5g, 0.76mm peak displacement (non-operating)

ORDERING INFORMATION

Order Number	Product Description (Hardware)
PP 310/011-xy	1.1 GHz Pentium M Processor
PP 310/012-xy	1.6 GHz Pentium M Processor
AD PP5/001-xx	Transition Module
AD 200/001-00	CompactFlash/Microdrive carrier assembly
AD CP1/DR1-xx	2.5 inch Hard Disk Drive assembly
AD HSC/001-02	Board Hot Swap cover (rear mounting)
CB 26D/124-00	26-way HD to VGA, Keyboard, Mouse, RS232 connector cable

Replace the order number suffix (xy) with selections from the following:

where x =	where y =
1 - Ethernet via rear panel	1 - 512 Mbytes
2 - Ethernet via PICMG 2.16	2 - 1 Gbyte
3 - Reserved	3 - 1.5 Gbytes
4 - Ethernet via PICMG 2.16, RS232 via J5	4 - 2 Gbytes

NOTE: compatible with AD PP5/001 Transition Module when x = 1 or 2

All companies and product names are trademarks of their respective organizations.
Specification subject to change; E and OE.

Datasheet Code 1419/0604
© Concurrent Technologies 2004

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP