

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions


Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Concurrent Technologies PP 330/022* at our website: *Click HERE*

PP 330/02x
N - Series

Intel® Pentium® M Processor Intelligent Dual PMC Carrier



APPLICATIONS

The PP 330/02x is an entry-level PC-compatible, low power, high functionality, dual PMC CompactPCI® board. Supporting the 1.6 GHz Intel® Pentium® M processor, the PP 330/02x will operate in a system slot or independently from the CompactPCI bus. High-performance networking is provided by four Gigabit Ethernet links, and the board is compliant to the PICMG® 2.16 specification. Full system monitoring is provided by the PICMG 2.9 compliant IPMI interface. To simplify the board's integration many popular industry standard operating systems are supported. The PP 330/02x is suitable for a range of applications within the industrial control, telecomms, telemetry, scientific and aerospace markets. The board is rear plug compatible with the PP 332/02x family.

HIGHLIGHTS

- 1.6 GHz Intel Pentium M processor:
  - 64 Kbytes L1 cache
  - 1 Mbyte L2 cache
  - no CPU fan needed; low power processor
- 1.8 GHz or 1.4 GHz processor version (2 Mbytes L2 cache) available; see PP 332/02x datasheet
- For extended temperature version see PP 332/02x datasheet
- Single slot (for all option combinations)
- Up to 2 Gbytes of 333 MHz DDR DRAM (with ECC)
- 2 x PMC module interfaces (32/64-bit at 33/66 MHz)
- High performance EIDE interfaces with optional on-board disk drive or optional CompactFlash™/Microdrive™ interface (in a single-slot)
- 4 x 10/100/1000Mbps Ethernet interfaces:
  - 2 via front panel
  - 2 via rear panel
- Dual Gigabit Packet Switched Backplane (PICMG 2.16)
- CompactPCI controller:
  - operates in system slot
  - 64-bit at 33/66 MHz CompactPCI interface
- Option to bypass CompactPCI bus (Satellite Mode)
- IPMI (Intelligent Platform Management Interface):
  - PICMG 2.9 (System Management Specification)
- 3 x USB 2.0 interfaces:
  - 2 via front panel
  - 1 via rear panel
- Up to 3 x RS232 serial channel interfaces:
  - 1 on-board
  - 2 on optional Transition Module
- Watchdog timer
- Support for VxWorks®, Windows® 2000, Windows® XP, Windows® XP Embedded, QNX® and Linux®
- Optional Transition Module for rear panel I/O:
  - 2 x RS232 channels, parallel printer port and floppy disk interfaces included

CONCURRENT TECHNOLOGIES

Concurrent Technologies Plc 4 Gilberd Court, Colchester, Essex, CO4 9WN, UK
Tel: +44 (0)1206 752626 Fax: +44 (0)1206 751116

Concurrent Technologies Inc 3840 Packard Road, Ann Arbor, MI 48108, USA
Tel: (734) 971 6309 Fax: (734) 971 6350

email: info@gocct.com http://www.gocct.com

Specification

Central Processor

- 1.6 GHz Intel® Pentium® M processor:-
  - → uses µFC-PGA 478 (micro Flip-Chip Pin Grid Array) package
  - → 64 Kbytes of primary (L1) on-die cache
  - → 1 Mbyte of secondary (L2) on-die cache
  - → 400 MHz Front Side Bus (FSB)
  - → no CPU fan
- 1.8 GHz or 1.4 GHz processor version (2 Mbytes L2 cache) available; see PP 332/02x datasheet
- utilizes 64-bit Intel® 855GME chipset:-
  - → supports 400 MHz bus frequency
  - → uses Intel® 6300ESB I/O Controller Hub
- provision for ITP debug port

DRAM

- supporting up to 2 Gbytes 333 MHz DDR ECC SDRAM:-
  - → up to 2 Gbytes provided via two SODIMM sockets
  - → single bit error correction
- accessible from Intel Pentium M processor or CompactPCI bus

Hard Disk Interfaces

- EIDE interface:-
  - → supports up to Ultra-DMA 100 for high performance drives
  - → two channels (primary and secondary)
  - → secondary channel supports on-board CompactFlash site
  - → secondary channel can be used for on-board 2.5 inch disk drive (within a single slot); or, support for 1 or 2 CompactFlash or Microdrive™ Type II drives (in a single slot)
  - → primary channel is accessible via Transition Module
  - → on-board options use a PMC site

Ethernet Interfaces

- 4 x channels supporting 10 Base-T, 100 Base-TX, 1000 Base-T:-
  - → front panel implemented by 2 x Intel® 82540EM via 32-bit 33MHz PCI bus
  - → rear panel implemented by Intel® 82546GB via 64-bit 33/66 MHz PCI bus
- 2 x channels accessed via J3 and 2 x channels via front panel RJ45 connectors:-
  - → support for rear panel RJ45 connectors via Transition Module
- support for PICMG 2.16 R1.0 - Packet Switched Backplane (PSB)

PMC Interface


- 2 x PMC sites; for both sites:-
  - → I/O via front panel
  - → I/O via J3 and J5
  - → 32/64-bit, 33/66 MHz PCI operation
  - → 3.3V signaling levels
- Transition Module provides rear I/O for both PMC sites

Flash EPROM

- 1 Mbyte of BIOS Flash EPROM

Firmware Support

- Phoenix™ BIOS
- comprehensive Power-On Self-Test (POST)
- LAN boot firmware included



Software Support

- support for Windows 2000, Windows XP, Windows XP Embedded, VxWorks, QNX and Linux

Serial Interface

- up to 3 x RS232 serial channels:-
  - → 1 channel via an onboard header (serial cable supplied)
  - → 2 channels via optional Transition Module
- 16550 compatible UARTs
- channels support RI, CTS, RTS, DSR, DTR and DCD

Other Peripheral Interfaces

- PC-compatible Real Time Clock (Year 2000 compliant)
- watchdog timer
- system fan monitor; CPU temperature monitor; voltages monitor:-
  - → all accessible via IPMI
- legacy speaker interface
- 3 x USB (Universal Serial Bus 2.0) interfaces:-
  - → 2 via front panel
  - → 1 via J5 Transition Module
- LPC (Low Pin Count) bus via J5 to enable AD PP5/001 Transition Module to support:-
  - → floppy disk interface
  - → parallel printer port interface (ECP, EPP and IEEE1284)
  - → 2 x RS232 serial channels

CompactPCI Interface

- compliant with PICMG 2.0 R3.0; 3.3V or 5V signaling levels:-
  - → universal signaling support
- J4 connector not fitted
- 33/66 MHz; 32/64-bit interface accessed via J1/J2 connectors
- utilizing a PCI-PCI bridge for off-board accesses
- PICMG 2.1 R2.0 Hot Swap Specification
- operates as a System Slot controller
- option to disable CompactPCI interface (Satellite Mode):-
  - → receives power from CompactPCI bus
  - → board can be hot swapped in this mode

IPMI

- PICMG 2.9 R1.0 (System Management Specification):-
  - → implements the IPMB0 interface
  - → implements an IPMB1 interface
- on-board Baseboard Management Controller
- supports 8 Kbytes of non-volatile memory

Electrical Specification

- +5V@3.6A (typical with 512 Mbytes DRAM); +5% / -3%
- +3.3V@2.1A; +5% / -3%
- +12V@0.05A; -12V@0.05A
- +12V and -12V routed to PMC slots

Safety

- PCB (PWB) manufactured with flammability rating of 94V-0

Environmental Specification

- operating temperature:-
  - → 0°C to +55°C (N-Series)
- 10% to 90% Relative Humidity, non-condensing (operating):-
  - → option for board humidity sealant
- -40°C to +85°C (storage)
- 10% to 90% Relative Humidity, non-condensing (storage)
- for extended temperature operation see PP 332/02x datasheet

Mechanical Specification

- 6U form-factor: 9.2 inches x 6.3 inches (233mm x 160mm)
- single-slot: 0.8 inches (20.3mm)
- connectors: IEC-1076-4-101 for J1-J5
- shock:
  20g, 11ms, ½ sine (operating);
  30g, 11ms, ½ sine (non-operating)
- vibration:
  5Hz-2000Hz at 2g, 0.38mm peak displacement (operating);
  5Hz-2000Hz at 5g, 0.76mm peak displacement (non-operating)

ORDERING INFORMATION

Order Number	Product Description (Hardware)
PP 330/022-xy	1.6 GHz Pentium M Processor
AD PP5/001-zz	Transition Module
AD 200/001-01	CompactFlash/Microdrive carrier assembly
AD CP1/DR1-z2	2.5 inch Hard Disk Drive assembly
AD HSC/001-04	Board Hot Swap cover (rear mounting)

For z options please contact your local sales office

Replace the order number suffix (xy) with selections from the following:

where x =
1 - Ethernet via rear panel
2 - Ethernet via PICMG 2.16

where y =
0 - reserved
1 - 512 Mbytes
2 - 1 Gbyte
3 - 1.5 Gbytes
4 - 2 Gbytes

All companies and product names are trademarks of their respective organizations
Specification subject to change; E and OE.

Datasheet Code 1470/1105
© Concurrent Technologies 2005

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP