

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*

VME

VP A45/01x

N, E, K - Series

Intel® Atom™ Processor Dual PMC Controller



RoHS 2002/95/EC

APPLICATIONS

The VP A45/01x is a PC-compatible low power, high functionality, 6U VME board supporting the 1.6 GHz Intel® Atom™ processor N270. It utilizes the Mobile Intel® 945GSE Express chipset to support 2 Gbytes of DDR2-533 SDRAM. This single slot board features 1 PMC/XMC site and 1 PMC site, an on-board CompactFlash™ site and a range of I/O including four Ethernet interfaces. The VP A45/01x is a commercial air-cooled board, suitable for a range of environments within industrial control, transportation, security, telemetry, scientific and medical applications. Options to operate in temperatures ranging from -40°C to +85°C are available. A ruggedized conduction-cooled version is planned and a ruggedized air-cooled version is available. To simplify the board's integration many industry standard operating systems are supported.

HIGHLIGHTS

- 1.6 GHz Intel® Atom™ processor N270:
  - 512 Kbytes L2 cache
  - Intel® Hyper-Threading Technology supports 2 execution threads
- 2 Gbytes of DDR2-533 SDRAM
- Dual SATA150 drive interfaces
- Option for an on-board SATA 2.5-inch mass storage device
- EIDE interface for an on-board CompactFlash® socket
- 1 x PMC/XMC and 1 x PMC module interfaces:
  - 1 x 32-bit, 33 MHz PCI PMC site
  - 1 x 32/64-bit, 33/66 MHz PCI/PCI-X™ PMC site
  - 1 x XMC module interface (x1 PCI Express™)
  - Expansion carrier for 2 more PMC/XMC sites
- Keyboard, mouse and DVI-D graphics interfaces via P2
- 2 x serial channels and 3 x USB 2.0 interfaces
- Watchdog and long duration timer
- 4 Mbytes of BIOS Flash EPROM
- 4 x Ethernet interfaces:
  - 1 x 10/100Mbps and 1 x 10/100/1000Mbps Ethernet channels via front panel RJ45 connectors
  - 2 x 10/100/1000Mbps Ethernet channels via P0
- VME64 interface supporting A32/A24/A16/D64/D32/D16/D8(E0), MBLT64
- Extended temperature versions available:
  - -25°C to +70°C (E-Series)
  - -40°C to +85°C (K-Series, includes humidity sealant)
- Ruggedized air-cooled version (RA-Series) available:
  - -40°C to +75°C, conformally coated
  - see separate VP A45/01x-RA datasheet
- Ruggedized conduction-cooled version (RC-Series) planned:
  - conduction-cooled to ANSI/VITA 30.1-2002
  - -40°C to +85°C, conformally coated
  - see separate VP A45/01x-RC datasheet
- Support for Linux®, Windows® XP, Windows® XP Embedded, QNX® and VxWorks®

CONCURRENT TECHNOLOGIES

Concurrent Technologies Plc 4 Gilberd Court, Colchester, Essex, CO4 9WN, UK
Tel: +44 (0)1206 752626 Fax: +44 (0)1206 751116

Concurrent Technologies Inc 6 Tower Office Park, Woburn, MA 01801, USA
Tel: (781) 933 5900 Fax: (781) 933 5911

email: info@gocct.com **http://www.gocct.com**

Specification

Central Processor
- 1.6 GHz Intel® Atom™ processor N270:-
  - → 512 Kbytes of secondary (L2) on-die cache
  - → 533 MHz Front Side Bus
  - → Intel Hyper-Threading Technology supporting 2 execution threads
- utilizes Mobile Intel® 945GSE Express chipset:-
  - → uses Intel® ICH7M I/O Hub


SDRAM
- 2 Gbytes soldered DDR2-533 SDRAM
- accessible from processor or VME bus

Mass Storage Interfaces
- 1 x EIDE interface supports on-board CompactFlash™ socket
- 2 x Serial ATA150 interfaces:-
  - → transfer rate up to 150 Mbytes/s
  - → accessed via P2 connector
  - → one channel switchable to on-board SATA 2.5-inch mass storage device
- option for USB Flash drive module

Ethernet Interfaces
- 1 x 10/100Mbps interface via front panel:-
  - → provided by Intel ICH7M
- 1 x 10/100/1000Mbps interface via front panel:-
  - → implemented by Intel® 82574 LAN Controller via x1 PCI Express® link
- 2 x 10/100/1000 Mbps interfaces via P0:-
  - → implemented by 2 x Intel® 82574 LAN Controllers via x1 PCI Express® links

PMC/XMC Interfaces
- 1 x PMC/XMC site and 1 x PMC site
- PMC site 1 supports:-
  - → 32/64-bit, 33/66 MHz PCI/PCI-X
  - → 3.3V or 5V signaling
  - → XMC interface via x1 PCI Express port
  - → I/O via front panel and via P2 (VITA 35 P4V2-64ac pinout)
- PMC site 2 supports:-
  - → 32-bit, 33MHz PCI only
  - → 3.3V or 5V signaling
  - → I/O via front panel and via optional P0
- expansion to optional dual PMC/XMC carrier board:-
  - → via x1 PCI Express XMC site

Serial Interfaces
- 1 x RS232 serial channel accessed via RJ45 connector on front panel:-
  - → supporting CTS, RTS, DSR, DTR and DCD
- 1 x RS232/422/485 serial channel accessed via P2:-
  - → supporting RI, CTS, RTS, DSR, DTR, DCD and RI
  - → 16550 compatible UART



Graphics Interface
- implemented by Intel 945GSE:-
  - → resolutions up to 1600 x 1200 @ 16M colors
- DVI-D graphics accessed via P2 connector

Flash EPROM
- 4 Mbytes of BIOS Flash EPROM

Software Support
- supports Linux®, Windows® XP, Windows® XP Embedded, QNX®, and VxWorks®

Firmware Support
- Phoenix™ TrustedCore BIOS
- comprehensive Power-On Self-Test (POST)
- LAN boot firmware included

Other Peripheral Interfaces
- PC-compatible Real Time Clock (Year 2000 compliant)
- 3 x USB 2.0 interfaces:-
  - → 1 via a USB connector on front panel
  - → 2 via P2 connector
- keyboard and mouse interfaces accessed via P2 connector
- watchdog timer
- 1 x 32-bit Long Duration Timer with processor interrupt capability
- 4 x GPIO signals via P2

VME Interface
- P1 and P2 connectors compatible with VME64x
- implemented using Tundra® Tsi148 device
- VME Master/Slave
- A32/A24/A16/D64/D32/D16/D8(EO)/MBLT64
- fast hardware byte swapping
- auto system controller detect
- full interrupter/interrupt handler support

Safety
- PCB (PWB) manufactured with flammability rating of 94V-0

Electrical Specification
- +5V@4.4 A (typical, 2Gbytes SDRAM)
- +12V@0.0A; -12V@0.0A; 3.3V not required
- +12V and -12V routed to both PMC sites

Environmental Specification
- operating temperatures:-
  - → 0°C to +55°C (N-Series)
  - → -25°C to +70°C (E-Series)
  - → -40°C to +85°C (K-Series)
- storage temperature - VITA 47 Class C1
- operating altitude - 0 to 15,000 feet (0 to 4,572 meters)
- 5% to 95% Relative Humidity, non condensing (operating or storage):-
  - → K-Series includes humidity sealant
- ruggedized versions planned, see separate datasheets:-
  - → conduction-cooled: VP A45/01x-RC
  - → air-cooled: VP A45/01x-RA

Mechanical Specification
- 6U form-factor
- single slot, front panel width 0.8 inch (20.3mm)
- utilizes 160-way connectors for P1 and P2
- optional P0
- IEEE 1101.10 handles
- operating shock - VITA 47 Class OS1
- operating vibration - VITA 47 Class V1

ORDERING INFORMATION

Order Number	Product Description (Hardware)	Replace the order number suffix (-xy) with selections from the following: Where x = P2/P0 Breakout combinations	Where y = SDRAM size
VP A45/013-x2	1.6 GHz Atom processor N270	5 - No P0, PMC (VITA35 P4V2-64ac) 6 - P0 fitted, PMC (VITA35 P4V2-64ac)	1 - reserved 2 - 2 Gbytes

AD 110/001-zz	SATA 2.5-inch Mass Storage Drive kit
AD CR3/PMC-zz	PMC Carrier board for 2 PMC modules
AD VP2/020-10	Rear Transition Module with I/O peripheral connectors, no P0: use when x = 5, i.e. VP A45/013-5y
AD VP2/020-30	Rear Transition Module with I/O peripheral connectors, P0 fitted: use when x = 6, i.e. VP A45/013-6y
AD 235/001-0z	USB Flash Drive Module (optional, fits on VP A45/01x baseboard)

For z options please contact your local sales office
For extended temperature, 1.6 GHz E and K-Series, please contact your local sales office
For ruggedized versions, see separate datasheets: VP A45/01x-RC (conduction-cooled) or VP A45/01x-RA (air-cooled))

All companies and product names are trademarks of their respective organizations.
Specification subject to change; E and OE. RoHS 2002/95/EC compliant.

Datasheet Code 1591/1109
© Concurrent Technologies 2009

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP