ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Creative Electronic Systems PVIC 8425D* at our website: *Click HERE*

Multi-Drop Data Transporters: PVIC



PVIC Elements

Highlights

- Fully transparent byte, word, long-word transactions
- Onboard autonomous block mover offering multiple chained DMAs, executed concurrently
- Supports hot disconnection
- Full PCI speed traffic at 132 MBytes/s bandwidth
- Advanced mechanism for real-time interprocessor communication
- Up to fifteen stops per interconnection spanning up to 200 meters, no driver required
- VME, PMC and PCI form factors
- Versatile interrupt dispatching logic for remote and local interrupt handling
- Rich set of broadcast modes

Applications

Typical applications include any real-time distributed high-speed data transportation such as robotics, aircraft test equipment, distributed CPU clusters, flight simulators, physics experiments, etc.

General Description

Combining VME interconnection know-how, which contributed to an ISO standard (VIC Bus - ISO/IEC 26.11458), with in-depth PCI expertise, the PVIC (PCI Vertical InterConnection) concept gives the PCI the right dimension in advanced data acquisition systems: the data backbone between PCI-based VME or CompactPCI processors and workstations.


As in every major CES product, it combines state-of-the-art technology with a system-level approach. This translates into unique features such as atomic cycle support, global semaphores, intelligent broadcasts, etc. in order to build a smooth running scalable multiprocessor architecture.

Together with CES deterministic PowerPC computing cores and network interfaces, PVIC provides a totally safe and easy-to-use global solution, which meets demanding data-processing requirements in command and control, distributed telecommunications and signal processing.


PCI bus is widely used as a local bus for both VME and CompactPCI processor boards and desktop workstations. The PVIC concept described here has been developed by CES to allow PCI-based processors to be connected in clusters of up to 15 nodes spanning up to 200 meters. While preserving the full PCI throughput (132 MBytes/s at 32-bit, 33 MHz) for block accesses, the transparent mapping of remote PCI addresses minimizes latencies and drastically reduces the software overhead.

Belonging to the data transporter class, the PVIC architecture features self-hosted data transportation through an onboard block mover engine, multiple DMA channels, as well as efficient signaling services. The PVIC connection also offers linked lists, multi-cast cycles, local and remote interrupt, mailboxes and global semaphores. Broadcast and multicast cycles, interrupt dispatching, mailboxes, a mirrored memory and global semaphores provide the hardware support for efficient inter-processor communication.

For maximum flexibility, each of the PVIC interfaces can be adapted to the users environment and distance requirements due to small piggy-backs called PIBs (Physical Interface Board), which are available for small distances (down to 1 meter), medium distances (up to 30 meters) and long distances (up to 200 meters).



Three Sequences of a Data Transporter Class Connection




Transportation Sequences

1 - Local CPU request phase
2 - Local PCI data transport phase
3 - PVIC data transport phase
4 - Remote PCI data transport phase
5 - End of transaction / acknowledgement phase

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Multi-Drop Data Transporters: PVIC



Broadcast Transfer with Multiple Addresses

PVIC Architecture

The PVIC (PCI Vertical InterConnection) is the PCI equivalent of the VIC (VME InterConnection) with added functionalities, such as an onboard chained DMA engine and intelligent broadcast logic. The PVIC is a 16-bit bus time-multiplexed clocked at 66 MHz, delivering a 132 MBytes/s bandwidth memory mapped.

PVIC Transactions

The PVIC provides a transparent PCI bus-to-PCI bus coupler, which supports all byte, word, long word and burst cycles with no latency.

PVIC supports the following transaction types:

- Write single shot
- Broadcast
- Write burst and burst broadcast
- Write mirrored memory
- Read single shot
- Read burst
- Semaphore test and set

The arbitration on the bus is multilevel (standard and high-priority) with a rotating arbiter and support for “fair” mode, so that multiple concurrent transactions can occur.

Transparent Mode

The PVIC is mapped in the PCI bus through two independent spaces:

- Standard PCI configuration space, which contains all of the required CSRs to set up the connection
- PCI memory space window, which allocates the memory windows for each PVIC-interconnected local PCI bus

The memory allocation uses one in-coming and one out-going scatter / gather with page sizes of 64 KBytes and 4 KBytes respectively.

Once the initialization library has set up the desired working modes and page selection, a fully transparent connection is established between all of the PVIC interconnected systems.

DMA Block Mover

PVIC nodes may incorporate a DMA sequencer as an option. The DMA sequencer supports elementary DMAs or linked lists of DMA. The DMAs can be controlled either from the local PCI or from a remote PCI through PVIC.

Complete messages can be sent to specific nodes or may be broadcast. DMA sequences operate at full PCI speed with a payload of up to 16 KBytes per elementary DMA.

Multiple DMA chains can be defined per node. Sixteen DMA channels can run concurrently per node.

Intelligent Broadcast

Data distribution requires high-speed, safe and efficient mechanisms when transporting data to its destination.

The PVIC provides a unique broadcast mechanism, which incorporates an acknowledge check from all slave nodes, to guarantee reception. It also has an address relocation mechanism, where each slave node remaps the data to its own chosen address, so that software data copy is no longer required. The broadcast logic also supports burst transactions.

Interrupt Structure

The PVIC incorporates an advanced interrupt dispatching logic, which supports local and remote interrupt handling.

Interrupt sources are the four PCI interrupt lines, the PCI error interrupts, PVIC transaction error interrupts and the DMA controller interrupts (normal ending condition or error condition). All of these sources can be transparently exported to the local PCI bus or to a remote PCI bus.

The interrupt logic incorporates a complete set of CSRs, a programmable priority encoder as well as an enabling / disabling logic.

Message Passing


For multiprocessor applications an efficient message passing mechanism is required. Therefore the PVIC uses a global semaphore logic and provides a mailbox system for efficient interprocessor communication.

Message signaling occurs with a user-level programmable FIFO-based interprocessor message passing mechanism.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

PVIC 8425

PCI-to-PCI Vertical Interconnection PMC Interface



PVIC 8425


Highlights

The PMC member of the PVIC family, the PVIC 8425, can be used with CES VME or CompactPCI-based processor boards for in-chassis processor interconnection (from 1 meter to 30 meters) or long distance inter-chassis connection. It takes advantage of the RIO4, RIO3, RIOC and RIOS technology, which allows simultaneous VME or CompactPCI acquisition, CPU operation and PCI input / output. It supports dedicated GTL or differential onboard physical interfaces.

It features an embedded physical interface, which can be either GTL 8425BA or differential 8425DA, therefore it does not require any PIBs.

PVIC 7225

PCI-to-PCI Vertical Interconnection PCI / PCI-X Compatible Host Computer Interface



PVIC 7225

Highlights

The PVIC 7225 is a PCI ISA form factor board for use in PCI or PCI-X equipped workstations (Alpha, Macintosh, PC, Silicon Graphics, Sun, etc.). It supports differential, GTL and optical physical interfaces. Drivers are available under the principal operating systems of these workstations.

The combination is available to deliver continuous data transfers at over 50 MBytes/s to 100 MBytes/s into the host without any impact on the host computing capacity.

Two versions are available, one for PC's equipped with PCI and one for the PCs equipped with PCI-X in PCI emulation.

PVIC 8025

PCI-to-PCI Vertical Interconnection VME Interface



PVIC 8025

Highlights


The PVIC 8025 is the VME interface of the PVIC family. It features the following:

- VME slot-1 and arbiter functions
- VME master / slave D64 interface
- Autonomous VME link list DMA block mover
- Remote or local trigger logic
- Completely transparent VME-to-remote PCI data transporter
- Supports both single shot and DMA transfers between PVIC and VME

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

PIB 6801 / PIB 6802


Differential and Optical Physical Interfaces



PIB 6801



Cable and TER 6225



PIB 6802



Fiber Optic

PIB 6801

For distances up to 15 meters (132 MBytes/s at 66 MHz) or 30 meters (66 MBytes/s at 33 MHz). Interconnected with a shielded round cable with auto daisy-chaining (VDC 6500), which is equipped with a SCSI II 68-pin connector. A terminator (TER 6225) must be used at both ends of the differential bus.

PIB 6802

For distances up to 200 meters (1.5 GBits/s). Interconnected with a 850 nm multi-mode fiber, which is equipped with standard SC connectors.

PVIC 8426

PVIC Bridge




PVIC 8426

Highlights

The PVIC 8426 is attached to a CES RIO3 through its PCI extension connector, thus leaving free the two PMC slots of the motherboard. It can be equipped with two different PVIC physical interfaces, each of which may be either GTL, differential or optical (maximum one optical PIB), and therefore used as a PVIC bridge. PVIC 8425 mezzanines can be interfaced with a long-distance PVIC link through the PVIC 8426 bridge.

PVIC 8026

Transparent VME-to-VME VIC-Based Connection



PVIC 8026

Highlights

The PVIC 8026 is a VME board that allows transparent VME-to-VME connections, which are function-compatible with the VICbus family. Although, the PVIC 8026 uses the modern PVIC link technology. It features the following:

- VME-to-VME transparent link
- VME master / slave interface VME Rev D
- MBLT support in slave mode
- Connects up to fifteen chassis in a multi-drop / multi-master
- Transmission medium on a 68-pin twisted pair cable with LVDS technology
- Simple memory-mapped connections through scatter / gather
- SCSI II cables and connectors

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP