

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*

60 Watts PA Amplifier




Features
- 117/220 VAC or 12 VDC Mobile Use
- Heavy Duty Adjustable Chrome Plated Mounting Bracket
- AC and DC Fuse Protected
- Inputs to Accommodate Microphones, Tape Decks, Phonos, Tuners
- Attractive Silver Front Panel, Black Accents, Dark Grey Cabinet
- Output Impedances for All Installations
- Dimensions: 4½ × 10 × 8½

Specifications. Output Power: 60 watts music power, 20 watts RMS @ 5% THD. **Frequency Response:** 100-18,000 Hz. **Output Impedance:** 4, 8, 16 ohms, 25 and 70 volt line. **Power Source:** 117 VAC, 50/60 Hz, 220/240 VAC, 12 VDC mobile. **Weight:** 10 lbs. **Inputs:** Mic.-1 (LO-Z) — 2 mV/600 ohms; Mic.-2 (HI-Z) — 2 mV/50 K ohms; Aux.-1 — 200 mV/100 K ohms, Aux.-2 — 200 mV/100 K ohms. **Controls:** Mic. 1, Mic. 2, Aux. 1, Aux. 2, on/off power/tone.

958-8060. Model PAT-60 ..... **EACH 195.08**

60 Watts RMS P.A. Amplifier with Digital FM/AM Tuner



Features
- FM/AM Digital Tuner with 30 Presets
- 4 and 8 Ohm, 25 and 70 Volt Output
- Voice Activated Priority Page
- Dual 110/220 VAC 50/100 Hz
- 4 Microphone Cannon Inputs
- 1 Aux. Input
- 600 Ohm Telephone Paging Input Built-In
- Auto Reverse Cassette Deck

Specifications. Power: 60 watts RMS @ less than 1.0% distortion. **Frequency Response:** 30 Hz to 20 kHz. **Noise:** Mic. — 1-4 60 dB; Aux. — 70 dB. **Sensitivity:** Mic. — 0.3 mV; Aux. — 0.3 V.

958Q0060. Model P-60FAC ..... **EACH 592.45**

120 Watts RMS P.A. Amplifier



Features
- Heavy Duty Heat Sinks
- 4 Microphone Inputs with Lock-In Cannon Connectors; Can Be Used with Balanced or Unbalanced, High or Low Impedance Microphones
- 2 Aux. Inputs
- 1 Magnetic Phone Input
- 1 Equalizer Input
- Separate Volume Control for Each Microphone and Aux. Input
- Master Volume Control
- Separate Bass and Treble Control
- 4, 8, 16 Ohm Outputs, Screw Terminals
- 25 and 70 Volt Outputs, Screw Terminals
- 2 RCA Speaker Outputs
- 1 Booster/Tape Output
- Built-In Priority Paging
- Separate On/Off Switch

Specifications. Power: 120 watts RMS @ less than 50% distortion. **Frequency Response:** 20 Hz to 15 KHz. **Noise:** Mic. — 60 dB, Aux. — 75 dB. **Sensitivity:** Mic. — 0.3 mV, Aux. — 0.3 V. **Tone Controls:** Bass — ±15 dB @ 100 Hz, Treble — ±15 dB @ 10 KHz. **Power Req.:** 120 VAC, 50-60 Hz, 230 W. **Dimensions:** 4¼" (H) × 17¼" (W) × 11½" (D). **Weight:** 33 lbs.

958Q8120. Model P-120A ..... **EACH 547.66**

Amplified Extension Speaker



An economical extension speaker with 10 watts of amplified power. Ideal for mobile or base 2-way. ABS plastic enclosure with soft-padded grille and all-angle swivel bracket. Includes 10' cord and 3.5 mm mini plug. **Specifications. Voltage:** 12 VDC. **Input Impedance:** 4 to 80. **Wattage:** 10 W amplified.

958-8036. Model AES-4 ..... **EACH 41.19**

Communications Extension Speaker



4", 5 watt 8 ohms, enclosed extension voice communication speaker. Multi-angle 180° mounting bracket; 10' cord and 3.5 mm mini plug. ABS plastic enclosure.

958-7090. Model CBS-240 ..... **EACH 14.51**


10-Watt 70-Volt Line Transformer with Color-Coded Leads



10-watt primary. Taps at 10, 5, 2.5, 1.25, and 0.62 watts. **Secondary Impedance:** 4 or 8 ohms. For driving speakers at various power levels from the same 70-volt line, simply charge the transformer taps to achieve the power level you desire. **Size:** 1.65" × 1.65" × 2". **Shipping Weight:** 1½ lbs.

958-0013. Model T-7010 ..... **EACH 4.37**


Background Sound Amplifiers



- Two Mic Inputs
- Aux Input
- Front Panel Level Controls
- Auto Mute Function
- Bass and Treble Tone Controls
- Outputs 25/70 V and 4/8/16 Ω
- Music On Hold Output with Separate Level Control (600 Ω Line and One Watt 8 Ω)
- 600 Ohm Telephone Line Input with Level Control
- Manual Muting Contacts
- Accessory AC Outlet
- Rack Mount and Wall Mounting Kits Available

958-0020. PBM-15. 15 Watt RMS ..... **EACH 202.00**
958-0025. PBM-30. 30 Watt RMS ..... **EACH 255.00**

ABS Plastic and Aluminum Series Speakers



All the SPC-series aluminum and ABS plastic speakers are fully weatherproof and of rugged design to assure durability. All are furnished with hookup wires and mounting bracket. The SPC-10 is also available in 4 ohms (SPC-10/4) at the same price shown below. Frequency response and sensitivity may vary slightly with each individual speaker.

Model SPC-8. 5" Aluminum Weatherproof PA Speaker. **Specifications. Frequency Response:** 30-15,000 Hz. **Power Rating:** 12 W nom. 15 W max. **Sensitivity:** 105 dB/1 W/1 M. **Impedance:** 8 ohms. **Size:** 5 × 5".
958-8005. Model SPC-8 ..... **EACH 13.05**

Model SPC-10. 6" Aluminum Weatherproof PA Speaker. **Specifications. Frequency Response:** 250-15,000 Hz. **Power Rating:** 10 W nom. 15 W max. **Sensitivity:** 105 dB/1 W/1 M. **Impedance:** 8 ohms. **Size:** 6 × 6".
958-7098. Model SPC-10 ..... **EACH 24.50**


Model SPC-15. 8" Aluminum Weatherproof PA Speaker. **Specifications. Frequency Response:** 200-15,000 Hz. **Power Rating:** 15 W nom. 25 W max. **Sensitivity:** 110 dB/1 W/1 M. **Impedance:** 8 ohms. **Size:** 8 × 8".
958-8006. Model SPC-15 ..... **EACH 30.26**

Model SPC-40RP. 6½" × 11" White ABS Speaker. Includes universal all position mounting bracket and stainless steel hardware. Completely weatherproof. **Specifications. Frequency Response:** 200-15,000 Hz. **Power Rating:** 40 W max. **Sensitivity:** 1020 dB/1 W/1 M. **Impedance:** 8 ohms. **Size:** 6½ × 11" (Dia.) × 9" (L).
958-8025. Model SPC-40RP ..... **EACH 34.18**

Model SPC-5P. 5" White ABS Indoor/Outdoor PA Speaker. Includes 10' cord and mini plug and stainless steel hardware. **Specifications. Frequency Response:** 300-15,000 Hz. **Power Rating:** 8 W nom. 12 W max. **Sensitivity:** 105 dB/1 W/1 M. **Impedance:** 8 ohms. **Size:** 5 × 5".
958-7097. Model SPC-5P ..... **EACH 9.54**

Model SPC-30. 15" Aluminum Weatherproof PA Speaker. **Specifications. Frequency Response:** 130-15,000 Hz. **Power Rating:** 40 W nom. 75 W max. **Sensitivity:** 120 dB/1 W/1 M. **Impedance:** 8 ohms. **Size:** 15 × 13".
958-8007. Model SPC-30 ..... **EACH 72.10**


SS-1 Solid State Sine/Square Wave Generator



Provides sine and square wave outputs simultaneously while covering 20 Hz to 2 MHz in 5 bands. **Specifications. Square Wave:** 20 Hz-200 KHz. **Sine Wave:** 20 Hz to 2 MHz. **Output Voltage:** sine wave 0-7.5 volts rms into high impedance output, 0-6.5 volts into 600 ohms. **Square Wave:** 0-10 volts p-p into high impedance, positive direction with ground zero. **Calibration Accuracy:** 3% except for 5%, 20 Hz to 100 Hz and 1 MHz to 2 MHz. **Maximum Distortion Across Audio Range:** 0.25% rise time at 20 KHz, less than 0.1 microseconds. **Power Requirements:** 105-132 volts. 50/60 Hz, 10 VA.

776-0379. Model SS-1 ..... **EACH 200.86**

PSV-5 General Purpose Variable DC Power Supply



- Input: 117V/220V AC, 60 Hz
- Output: 0-30V DC, 0-5 Amp Regulated
- Dual Panel Meters, Volts and Amps
- Coarse and Fine Voltage Adjustment
- Hi-Lo Current Switch with Min.-Max. Control
- Dual Scale Amp Meter
- Low Ripple 0.5mV rms
- Single Output Heavy Duty Binding Posts for (+) (–) and Ground
- Overload and Short Circuit Protection
- Current Limiting 0-5 Amps
- Heavy Duty 3 Prong Power Cord
- 6¼"H × 8½"W × 10"D; 10 Lbs.

776-0050. PSV-5 ..... **EACH 258.66**

F-72 Multitester




- Better Overload Protection
- Battery Tester
- With Carrying Case and Buzzer
- Includes Test Leads and Batteries
- Adjustable Handle
- Mirror-Back Scale
- 23 Ranges

Specifications. 20 k ohms/vdc. **DC V:** 0, 2.5, 10, 50, 250, 1000 V. **AC V:** 0, 10, 50, 250, 1000 V. **DC Current:** 0, 5, 50, 500 mA, 10 A on separate jack. **Resistance:** R × 1, R × 10, R × 1K (Center 50 ohm). **Decibel:** –8 dB to +62 dB on all AC V range. **Battery Test:** 1.5 V size AA; internal loading resistance and current 75 ohm/20 mA; 9 V Std.; internal loading resistance and current 450 ohm/20 mA. **Audio Power Level:** –8 dB to +22 dB on a 600 3" arc of scale length. **Batteries:** 1.5 V AA × 2 pcs. **Protection:** 1 A/250 V fuse and silicon double diode. MT-20-BC made of high impact plastic and phenolic PCB. 5¼"H × 3½"W × 1½"D. **Weight:** 1.2 lbs.

776-0020. Model F-72 ..... **EACH 28.82**

PSR-7 7 Amp and PSR-10 10 Amp Regulated DC Power Supplies



- Input: 117 V AC, 60 Hz
- Output: PSR-7 — 13.8 V DC 7 Amp Constant, 9 Amp Surge; PSR-10 — 13.8 VDC 10 Amp Constant, 12 Amp Surge
- Dim.: PSR-7 — 3¾"H × 6¼"W × 7⅝"D; PSR-10 — 4½"H × 6½"W × 7¾"D
- Regulated and Filtered
- Universal Binding Posts
- Fuse and Auto Reset Circuit Breaker Overload Protected
- Heavy Duty Grounded 3 Prong AC Power Cord
- Weight: PSR-7 — 6½ Lbs.; PSR-10 — 9¼ Lbs.
- Display Boxed

776-0015. PSR-7 ..... **EACH 57.75**
776-0030. PSR-10 ..... **EACH 77.96**

8" Speaker with Line Transformer with Grille



Model G86FT70GW. 8" speaker with line transformer and grille — assembled and wired. 6 oz. dual cone, 70 V, 10 watt transformer, white metal grille. (10 oz. dual cone, air susp. and coaxial in 70 V and 25 V also available upon request.)
958-8018. Model G86FT70GW ..... **EACH 19.43**

Alarm Sirens




Model SA-15RP. 5" × 8", 30 Watt DC Siren. Made of weatherproof ABS plastic. Tamperproof, concealed cable. Dual tone — warbling and steady; 120 dB. Operates on 6 to 12 VDC.
958-8010. Model SA-15RP ..... **EACH 25.94**

Model SA-4P. 4", 20 watts, 120 dB, warbling tone. Weatherproof ABS plastic. Operates on 6-12 VDC. Easy mounting base.
958-8111. Model SA-4P ..... **EACH 13.72**

Model SA-5P. 5", 20 Watt DC Siren. Provides sharp, loud warbling tone, 115 dB. Black weatherproof ABS plastic with horn design. Operates on 6 to 12 VDC.
958-8012. Model SA-5P ..... **EACH 10.57**

Stereo and Monaural Audio Level Control



Long threaded bushing for mounting in cabinets. Complete with knob and mounting plate.

Monaural — Heavy Duty Single "L" Pad
958-8575. Model AT-10. 10 Watts ..... **EACH 5.04**
958-8580. Model AT-50. 50 Watts ..... **EACH 9.41**
958-8585. Model AT-100. 100 Watts ..... **EACH 13.27**

Stereo — Dual Stereo "L" Pad with Simple Control
958-8590. Model AT-10D. 10 Watts ..... **EACH 8.11**

Accessories



Wall mount custom design and high power attenuators. Monaural. Stainless steel plate/black knob, white plastic plate/white knob. **Line/Volt:** 70/25.

Stock No.	Mfr.'s Type	Watt	Plate Type	Ohm	EACH
958-8515	WAT-10W	10	White Plastic	—	17.25
958-8520	WAT-10-8	10	Stainless Steel	8	16.80
958-8530	WAT-25	25	Stainless Steel	—	20.16
958-8540	WAT-35*	35	Stainless Steel	—	21.54

*Dual Gang.

15

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP