ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.


Find the *Curtiss-Wright / Systran DIO316I* at our website: ***Click HERE***

blueline.jpg (320 bytes)

[Home][Products]

DIO316I


Tristateable, 48-Channel, Digital I/O IP Module



The DIO316I provides 48 lines of digital inputs and outputs including 16 bits of digital input, 16 bits of output and 16 bi-directional bits. With four individually configurable interrupts, it is ideal for responding to changes in input signals without continually polling the inputs. Its modular design provides up to 80 bits of digital input, 80 bits of output and 80 bi-directional bits, for a total of 240 I/O points in a single VME slot using the VMESC5 carrier. Up to 288 I/O points are possible through a single PC slot using the ISASC6 carrier. The DIO316I can also be mixed with other IP modules for a more customized, modular I/O system solution.

Application Features:

- Hard drive capability without adding an external buffer in most applications.
- Direct Pin Out provides peripheral compatibility to industry standard interface modules.
- Bi-directional inputs/outputs afford you the flexibility to customize the I/O to fit your needs. The outputs are easily changed via software.
- Four independent interrupt engines act as event triggers which allow you to control I/O activity; thus providing for versatile system-level support.
- Output ports are tristateable for custom busing applications.



Specifications:

- Physical Dimensions: 1.800 " x 3.900 " x 0.303 " (45.72 mm x 99.06 mm x 7.70 mm)
- Weight: 0.944 oz. (26.76 grams)
- Hardware Compatibility: IndustryPack Logic Interface Specification, Rev. 0.7.1
- Mechanical/Electrical Interface: Singlewide IP module
- IP Transfer Types: (memory not supported) – I/O: 16-bit writes, 16-bit reads; No wait states, hold states supported – ID: 8-bit read only; No wait states, hold states supported – INT: 8-bit vector read only; No wait states, hold states supported
- Electrical Requirements: +5 Vdc @ 130 mA (typ., no load)
- Operating Temperature: 0 to +70 C (32 to +158 F)
- Storage Temperature: -40 to +85 C (-40 to +185 F)
- Humidity (non-condensing): 5% to 95%
- Operating Vibration: 10 G's RMS, 20-2000 Hz random
- Operating Shock: 50 G's max.
- Operating Altitude: 10,000 ft.
- MTBF: 3,805,175 hrs. per MIL-HDBK-217F
- Port Drivers: TTL Compatible
  – Source Rating: -15 mA
  – Sink Rating: 64 mA
  – High-impedance Leakage Currents: ±1µA
  – Input Current: ±1µA (@ 10 pf max.)
- Interrupt Support:
  – Maskable Interrupts on: Rising Edges, Falling Edges, High-Level, Low-Level, and On-Change
  – Single Interrupt Request: (Level 0) with 8-bit Vector Support
  – RORA-Type ISR Support
  – Low nibble of Port 4

Ordering Information:

BHAS-DIO316I: 48 Channel Tristateable Digital IP Board

DIO316I PIN ASSIGNMENTS

50	GND	40	Port 4 Bit 0	30	Port 3 Bit 2	20	Port 2 Bit 4	10	Port 1 Bit 6
49	Not Used	39	Port 4 Bit 1	29	Port 3 Bit 3	19	Port 2 Bit 5	9	Port 1 Bit 7
48	Port 5 Bit 0	38	Port 4 Bit 2	28	Port 3 Bit 4	18	Port 2 Bit 6	8	Port 0 Bit 0
47	Port 5 Bit 1	37	Port 4 Bit 3	27	Port 3 Bit 5	17	Port 2 Bit 7	7	Port 0 Bit 1
46	Port 5 Bit 2	36	Port 4 Bit 4	26	Port 3 Bit 6	16	Port 1 Bit 0	6	Port 0 Bit 2
45	Port 5 Bit 3	35	Port 4 Bit 5	25	Port 3 Bit 7	15	Port 1 Bit 1	5	Port 0 Bit 3
44	Port 5 Bit 4	34	Port 4 Bit 6	24	Port 2 Bit 0	14	Port 1 Bit 2	4	Port 0 Bit 4

43	Port 5 Bit 5	33	Port 4 Bit 7	23	Port 2 Bit 1	13	Port 1 Bit 3	3	Port 0 Bit 5
42	Port 5 Bit 6	32	Port 3 Bit 0	22	Port 2 Bit 2	12	Port 1 Bit 4	2	Port 0 Bit 6
41	Port 5 Bit 7	31	Port 3 Bit 1	21	Port 2 Bit 3	11	Port 1 Bit 5	1	Port 0 Bit 7

[Home][Products]

blueline.jpg (320 bytes)

Aerotech World Trade Ltd.
Tel: (818) 991-2972

31316 Via Colinas Unit 118
Fax: (818) 991-2974

Westlake Village, CA 91362
e-mail: sales@aerotecusa.com
web: www.aerotechusa.com

blueline.jpg (320 bytes)

Web design by B. Sam Cook and B.S. Software

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP