ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *CyberOptics / Imagenation PX-610A-00* at our website: *Click HERE*

PX Frame Grabber Family

Specifications & Features Overview
Common to all PX Family Members

Specifications



- **Bus** PCI bus master design for real-time image capture. PCI short card, PC/104-*Plus* core module and *Compact*PCI 3U size card
- **Input composite video format** Monochrome, RS-170 (NTSC) or CCIR (PAL) autodetect
- **Input video** 1 V peak to peak, 75W
- **Resolution** RS-170: 640 x 480 pixels (maximum: 768 x 486 pixels); CCIR: 768 x 576 pixels; 256 gray levels, 8 bits
- **Power** - + 5 VDC, PCI, 850 mA; PC/ 104-*Plus* and *Compact*PCI, 650 mA
- **Camera Power** - + 12 VDC output
- **Supported Operating systems** - DOS, Win 3.1, Win 95 / 98 / ME, Win NT / 2000
- **Supported Languages** C / C++, Visual Basic

Features

- **Sampling jitter** Maximum of ± 3 ns relative to horizontal synchronization
- **Software programmable look up tables (LUTs)** 256 byte input LUT
- **External trigger** Input pulled by 10k ohm to 5 V, trigger requires a TTL pulse of 100 ns (minimum); software programmable edge or level sensitivity; software programmable polarity
- **Strobe output** Two TTL outputs with independently programmable pulse widths and polarities to control resettable cameras, exposure time, strobe lights, etc.
- **Video noise** - < 0.8 LSB (least significant bit)
- **Video Multiplexer** Four video inputs which can be a mix of RS-170 and CCIR
- **Camera gen-locking** Horizontal and vertical drive outputs to gen-lock camera with a frame grabber
- **Resettable camera support** With high precision digital synchronization
- **Vertical and horizontal cropping and scaling** Minimize memory and bus bandwidth requirements
- **Programmable offset and gain**
- **Standard Product** FCC verification and CE marked
- **Software and manual included**

Specific to individual PX family products

	PX610A-00	**PX610A-00E**
Input composite video format	NTSC	CCIR

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP