

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction


All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*

SWITCHING SYSTEMS

LOW COST SOLUTIONS FROM THE SWITCHING SPECIALISTS.
• MATRICES • MULTIPLEXERS • POWER RELAYS
• COAXIAL MATRICES • CUSTOM MODULES.

Full Assortment of C Size VXI Switch Modules



B Size Modules and VME Modules also available

Member of the VXI plug&play Alliance

FOR TECHNICAL ASSISTANCE or a FULL PRODUCT CATALOG, CONTACT
1-800-346-3117 or
www.cytec-ate.com or
sales@cytec-ate.com

CYTEC CORP.

2555 Baird Road, Penfield, New York 14526

CYTEC CORP.

BULLETIN
CY/9

2555 Baird Road, Penfield, New York 14526 (716) 381-4740 FAX (716) 381-0475

CY SERIES

VXI C-SIZE SWITCH MODULES

The CY Series are low cost C-Size VXI Bus Switch Modules that utilize both Message and Register based operation. Available modules include Multiplexers, Matrices, Microwave Switches, Individual Form A and Form C Relays, Driver Modules, 50 Ohm Coaxial, Solid State and ECL Matrices.

FEATURES INCLUDE:

- **FULL FIVE YEAR WARRANTY**
- **STATUS of individual relays monitored at the relay drives.**
- **HIGH RELIABILITY Type S Standard and Type M Mercury Wetted Reed Relays with a guaranteed life of 100 million operations.**
- **LOW THERMAL Relays with offsets less than 1 μvolt.**
- **MICROWAVE Switches with a Bandpass of DC to 18 GHz; 26 GHz optionally available.**
- **HIGH FREQUENCY 50 ohm impedance 8x8 Coaxial Matrix with 200 MHz bandpass.**
- **HIGH POWER Switch Modules with 32 Form C Armature Relays with 150 W or 2000 VA rating.**
- **MULTIPLEXERS with up to 128 switch points.**
- **BIDIRECTIONAL HIGH DENSITY MATRICES up to 16x8 or 62x2 configurations.**
- **"K" MODULES with 64 individual Form A or Form C relays.**
- **SOLID STATE 48x48 Matrices.**
- **ECL 16x16 Differential Pair Matrix.**
- **BUFFER Amplifier Modules with unity gain for impedance matching.**
- **DIFFERENTIAL INSTRUMENTATION Amplifiers with preset gains.**
- **DRIVER MODULES with individual current sourcing or sinking drives.**

SOFTWARE

Drivers and/or sample programs are available in the most common programming languages. Please consult our expert Sales Engineers.



GENERAL SPECIFICATIONS

VXI Revision	1.4
Logical Address	Per DIP Switch Setting
Radiated Emissions	Per VXI Specification
Conducted Emissions	Per VXI Specification

ENVIRONMENTAL

Operating Temperature	0^{o} to 55^{o}C
Storage Temperature	-25^{o} to 80^{o}C
Humidity	Less than 95% RH no condensation to 30^{o}C
Cooling	$<10^{o}$C rise w/air flow 1.5 L/sec & dP = 0.04 mm H_2O

WARRANTY

CYTEC Corp. warrants that all products are free from defects in workmanship and materials for a period of 5 years. Reed relays are guaranteed for 100 million operations when used within their published specifications.

Member of the VXI Plug and Play Alliance..

FOR TECHNICAL ASSISTANCE CALL 1-800-346-3117

CY SERIES RELAY SPECIFICATIONS

- **Type S** - Standard Dry Reed Relays.
- **Type M** - Mercury Wetted Reed Relays.
- **Type LT** - Low Thermal Reed Relays.
- **Type P** - Armature Power Relays.
- **Type A** - Instrumentation Level Signal Armature Relays.

Relays have the following guaranteed lifetimes when operated within the specified operating parameters.

Relay Type	S	M	LT	P	A
Min. Life - Mechanical	10^8	10^8	10^8	10^7	10^8
Min. Life - Full Load*	10^8	10^8	10^8	$2x10^5$	$2x10^5$
Contact Rating VA	10	50	10	2000	30
Switch Voltage	200V	500V	100V	380V	110V
Max. Switch Current	0.5A	2.0A	0.2A	8A	1.0A
Max. Carry Current	1.0A	2.0A	1.0A	10A	1.0A
Breakdown Voltage	400V	1000V	200V	1000V	750V
Operate Time	<1ms	<2ms	<1ms	<15ms	<3ms
DC Isolation - Ohms	10^{11}	10^{11}	10^{12}	10^9	10^9

*Load is purely resistive

CY SERIES MODEL OVERVIEW

CYTEC currently offers the following Models/Configurations:

Relay Modules (Note: All Relay Modules are bidirectional.)

- **CY/128** - These are built with 64 two-pole reed relays. Internal Pin Jumpers permit a variety of user-defined configurations, ranging from eight individual 8x1 two-pole multiplexers to one 128x1 single pole mux.
- **CY/8x8 -** This 8 Input/8 Output Matrix Switch Module is available with either single or two pole reed relays.
- **CY/16x8 -** This is a 16 Input/8 Output Matrix that is built with Type A armature relays and is used for switching instrumentation level signals.
- **CY/64x2 -** This holds 128 single pole reed relays arranged as eight individual 8x2 matrices. Many other configurations are possible, including the "standard" 64x2.
- **CY/64K -** This provides 64 individual Form A (NO) Reed Relays.
- **CY/64KC -** This supplies 64 separate Form C (NO/COM/NC) Type A Instrumentation Armature Relays.
- **CY/32KCP -** This is built with 32 Individual Form C Type P Power Relays for high power/current applications.
- **CY/CX -** This is a 50 ohm impedance 8x8 matrix which is designed to switch RF signals. Bandpass (-3dB) is 200 MHz.
- **CY/G and CY/M -** These switch microwave signals (DC-18 GHz). These one, two or three slots modules are built to the user's specifications and hold the CXR/1G and CXM Series Switch Modules.

Solid State Modules

- **CY/48x48 -** This 48x48 single pole matrix designed to switch ±5 volt signals. Bandpass is DC to 1 MHz, and path on resistance is 60 ohms.
- **CY/16x16ECL -** This provides a 16x16 nonblocking matrix for switching Differential ECL up to 1.2GBPS.
- **CY/IO-48 -** This holds 48 unity gain impedance matching buffer amplifiers.
- **CY/INST-48 -** This holds 48 precision differential input op amps. These have high input and low output impedances and make an ideal buffer into the CY/48x48 Solid State VXI Matrix.

PRICING:

MULTIPLEXERS		
CY/128-S	Type S Multiplexer	$1,100.00
CY/128-M	Type M Multiplexer	1,500.00
CY/128LT	Type LT Multiplexer	1,400.00
CY/64x2-S	Type S Multiplexer	1,300.00
CY/64x2-M	Type M Multiplexer	1,900.00
INDIVIDUAL SWITCHES		
CY/64K-S	Type S Switch Module	$1,100.00
CY/64K-M	Type M Switch Module	1,250.00
CY/64KC	Type A Switch Module	1,200.00
CY/64DRV-SNK, -SRC	Module	800.00
CY/32KCP	Power Relays	1,000.00
MATRICES		
CY/8x8-2S	Two Pole Type S	$1,100.00
CY/8x8-1S	One Pole Type S	1,000.00
CY/8x8-2M	Two Pole Type M	1,500.00
CY/8x8-1M	One Pole Type M	1,250.00
CY/8x8-LT	Two Pole Type LT	1,750.00
CY/16x16ECL	Module	2,100.00
CY/CX-2(8x4)	Coaxial Matrix	1,900.00
CY/CX-8x8	Coaxial Matrix	1,800.00
CY/CX-16x4	Coaxial Matrix	2,000.00
CY/16x8	Two Pole Matrix	1,800.00
CY/48x48	Solid State Matrix	1,500.00
CY/INST-48	Instrumentation Amplifier	1,500.00
CY/IO-48	Buffer Amplifier Module	750.00
CONNECTORS		
J20R	Ribbon Cable Connector	$ 5.00
J20C	Crimp Type Connectors	8.00
J25R	Ribbon Cable Connectors	6.00
J25C	Crimp Type Connectors	10.00
J34R	Ribbon Cable Connectors	8.00
J34C	Crimp Type Connectors	12.00
J50R	Ribbon Cable Connectors	8.00
J50C	Crimp Type Connectors	16.00
J64R	Ribbon Cable Connectors	12.00
J64C	Crimp Type Connectors	18.00

MICROWAVE RELAYS

These **CY/G** and **CY/M** Modules are available as individual relays or as multiplexers. They can also be supplied wired in a variety of different configurations including matrices.

For your particular requirement and pricing, please contact our Sales Department.

AVAILABILITY

Standard modules are typically available 15 days ARO in small quantities. Larger orders are subject to a negotiated delivery schedule.

CALL 1-800-346-3117 FOR TECHNICAL SALES ASSISTANCE

CYTEC CORP.

BULLETIN
CY/128

2555 Baird Road, Penfield, New York 14526 (716) 381-4740 FAX (716) 381-0475

CY/128 MULTIPLEXER

VXI C-SIZE SWITCH MODULE

The CY/128 is a bidirectional reed relay multiplexer and is used in general purpose switching applications. The module is designed with flexibility in mind, and a variety of different configurations are available. This allows the users to choose the configuration which most closely matches their requirements. All CYTEC VXI Modules use both Message and Register based operation.

DETAILED DESCRIPTION

The CY/128 Multiplexer holds eight individual 8x1 two-pole multiplexers and two Form C submultiplexer relays. Pin jumpers can be installed to interconnect the individual multiplexers, allowing the following configurations to be created:

- **Eight - 8x1** Two-Pole Multiplexers
- **Four - 16x1** Two-Pole Multiplexers
- **Two - 32x1** Two-Pole Multiplexers
- **One - 64x1** Two-Pole Multiplexer
- **One - 128x1** Single Wire Multiplexer using one Form C Submultiplexer Relay
- **Two - 64x1** Single Wire Muxes using two Form C Submux Relays
- **One - 32x1** Four Wire Multiplexer
- **One - 16x1** Eight Wire Multiplexer
- **One - 8x1** Sixteen Wire Multiplexer

Any number of relays can be energized concurrently, and the status of all relays may be read at any time.


AVAILABLE MODELS

- **CY/128-S** with Type S Standard Dry Reed Relays
- **CY/128-M** with Type M Mercury Wetted Reed Relays
- **CY/128-LT** with Low Thermal Offset Reeds

CONNECTORS

- Two 64 Pin Headers (128 Individual "Inputs")
- One 20 Pin Header (Eight Multiplexer and Two Form C Submux "Outputs")

Member of the VXI Plug and Play Alliance..



GENERAL SPECIFICATIONS

Power	**+5 Volts**	less than 1.0 Amp
	+12 Volts	20 mA per energized relay
Bandpass		DC to 80 MHz (-3dB)
Insertion Loss		less than 0.2dB at 10 MHz
Isolation/Crosstalk		100 kHz - 80dB
		1 MHz - 60dB
		10 MHz - 40dB
DC Isolation		Greater than 10^{10} ohms

REED RELAY SPECIFICATIONS

- **Type S** - Standard Dry Reed Relays.
- **Type M** - Mercury Wetted Reed Relays.
- **Type LT** - Low Thermal Reed Relays.

	Type S	Type M	Type LT
Contact Rating	10VA	50VA	10VA
Max. Switch Voltage	200V	500V	100V
Max. Switch Current	0.5A	2.0A	0.2A
Breakdown Voltage	400V	1000V	200V
Operate Time, less than	1ms	2ms	1ms
DC Isolation - Ohms	10^{11}	10^{11}	10^{12}

WARRANTY

CYTEC Corp. warrants that all products are free from defects in workmanship and materials for a period of 5 years. Reed relays are guaranteed for 100 million operations when used within their published specifications.

FOR TECHNICAL ASSISTANCE CALL 1-800-346-3117

CYTEC CORP.

BULLETIN
CY/64x2

2555 Baird Road, Penfield, New York 14526 (716) 381-4740 FAX (716) 381-0475


CY/64x2 SINGLE POLE MATRIX

VXI C-SIZE SWITCH MODULE


The CY/64x2 is a bidirectional reed relay matrix and is designed for general purpose switching applications. The module can be configured in a variety of different ways. The users can specify the configuration which most closely matches their requirements. All CYTEC VXI Modules use both Message and Register based operation.

DETAILED DESCRIPTION

The CY/64x2 Matrix contains 128 single pole reed relays arranged as eight banks of 8x2 matrices. These banks may be used individually or combined via internal pin jumpers to form larger Nx2 matrices. External wiring added by the user provides many other configurations, such as two 16x4 matrices or a single 32x4. Any number of relays may be closed simultaneously, and the status of all relays may be read at any time.



CY/64x2-S



AVAILABLE MODELS

- **CY/64x2-S** with Type S Standard Dry Reed Relays.
- **CY/64x2-M** with Type M Mercury Weed Reed Relays.

CONNECTORS

- Two 34 Pin Headers (128 Individual "Inputs")
- One 20 Pin Header (16 total "Outputs" - one from each of eight 8x2 matrices.)

RELAY SPECIFICATIONS

	Type S	Type M
Contact Rating	10VA	50VA
Max. Switch Voltage	200V	500V
Max. Switch Current	0.5A	2.0A
Max. Carry Current	1.0A	2.0A
Breakdown Voltage	400V	1000V
Operate Time, less than	1ms	2ms
DC Isolation - Ohms	10^{12}	10^{12}

SPECIFICATIONS

POWER	+5 Volts, less than 1.2 Amp +12 Volts, 25 mA per relay
BANDPASS	DC to 50 MHz (-3dB) - One 8x2 Bank
ISOLATION/CROSSTALK	<-50 dB at 10 MHz

PRICING:

CY/64x2-S	**$1,300.00**
CY/64x2-M	**$1,900.00**

Member of the VXI Plug and Play Alliance..

WARRANTY

CYTEC Corp. warrants that all products are free from defects in workmanship and materials for a period of 5 years. Reed relays are guaranteed for 100 million operations when used within their published specifications.

FOR TECHNICAL ASSISTANCE CALL 1-800-346-3117

CYTEC CORP.

BULLETIN
CY/64K

2555 Baird Road, Penfield, New York 14526 (716) 381-4740 FAX (716) 381-0475


CY/64K & CY/64KC

VXI C-SIZE INDIVIDUAL RELAY SWITCH MODULES


Each of these VXI Switch Modules provides 64 individual switch points. The CY/64K supplies 64 Form A reed relays, while the CY/64KC furnishes 64 Form C general purpose armature relays. Any number or relays may be closed simultaneously and relay status may be read at any time. All CYTEC products utilize both Register and Message based operation.

DETAILED DESCRIPTION


- **CY/64K** holds 64 separate single pole Form C Type S Standard or Type M Mercury reed relays. Each contact set is individually wired to 34 pin front panel connectors.
- **CY/64KC** is built with 64 individual high sensitivity, low thermal offset single pole Form C Type A armature relays for switching instrumentation level signals. The Normally Open, Normally Closed and Common contacts of all relays are wired out to 50 pin header connectors. Thermal Offsets are less than five microvolts.




Form A Relays - CY/64K



Form C Relays - CY/64KC



CY/64K



CY/64KC

AVAILABLE MODELS

- **CY/64K-S -** Form A Type S Standard Reed Relays
- **CY/64K-M -** Form A Type M Mercury Reed Relays
- **CY/64KC -** Form C Type A Armature Relays

CONNECTORS

- **CY/64K-** Four 34 Pin Header Connectors
- **CY/64KC -** Four 50 Pin Header Connectors

PRICING:

CY/64K-S	**$1,100.00**
CY/64K-M	**$1,250.00**
CY/64KC	**$1,200.00**

Member of the VXI Plug and Play Alliance..

WARRANTY

CYTEC Corp. warrants that all products are free from defects in workmanship and materials for a period of 5 years. Reed relays are guaranteed for 100 million operations when used within their published specifications.

SPECIFICATIONS

POWER	+5 Volts, less than 1.2 Amp
CY64/K	+12V, 15 mA per energ. relay
CY64/KC	+12V, 20 mA per energ. relay
BANDPASS	DC to 10 MHz (-3dB)
INSERTION LOSS	less than 0.1 dB at 1 MHz
ISOLATION/CROSSTALK	less than -40 dB at 1 MHz

RELAY SPECIFICATIONS

	Type S	Type M	Type A
Contact Rating	10VA	50VA	30VA
Max. Switch Voltage	200V	500V	110V
Max. Switch Current	0.5A	2.0A	1.0A
Max. Carry Current	1.0A	2.0A	1.0A
Breakdown Voltage	0.5A	2.0A	1.0A
Operate Time, less than	1ms	2ms	3ms
Lifetime, Mechanical	10^8	10^8	10^8
Lifetime, Full Load	10^8	10^8	$2x10^5$

FOR TECHNICAL ASSISTANCE CALL 1-800-346-3117

CYTEC CORP.

BULLETIN
CY/DRV

2555 Baird Road, Penfield, New York 14526 (716) 381-4740 FAX (716) 381-0475

CY/64DRV RELAY/SOLENOID DRIVER MODULE
CY/32KCP FORM C POWER SWITCH MODULE

CYTEC's CY/64DRV VXI C-Size Driver Module is built with 64 individually addressable current sourcing or sinking drives and is designed to power external loads such as relays or solenoids. The CY/32KCP has 32 Form C Power Relays that can switch up to 8 A of current and 150 watts DC or 2000 watts AC.

CY/64 DRV C-SIZE DRIVER MODULE

This module has 64 individually controlled drives and is built with either current sourcing or sinking ICs. These modules are typically used to drive solenoids or relays located external to the VXI Module. Each drive channel is an open collector and has integral diode suppression. The drives can be wired to the VXI Chassis' internal power supply busses or to an external source.

The **CY/64DRV** is configured via an internal DIP Switch to furnish one of eight different operational modes, supplying either 64 randomly controllable drives, one of four different multiplexing modes or one of three different group switch types. The use of any mode is determined by the switching application. Drive status (on/off) can be verified by the controlling computer at any time.

AVAILABLE MODELS

- **CY/64DRV-SNK** 64 Channel Current Sinking Driver
- **CY/64DRV-SRC** 64 Channel Current Sourcing Driver

CONNECTORS

- Internal 14 Pin Headers - wired out to external loads

CY/64DRV SPECIFICATIONS

Control Power	+5 Volts, 2.1 A Max. +12 Volts, 0.2A Max. (not including relay driver)

Drive Power	**Source**	**Sink**
Max. Voltage	80 VDC	50 VDC
Max. Current per Driver	350 mA	400 mA
Max. Current per IC Package	1 Amp	1 Amp


PRICING:

CY/64DRV-SNK	**$ 800.00**
CY/64DRV-SRC	**$ 800.00**

Member of the VXI Plug and Play Alliance..

CY/32KCP POWER SWITCH MODULE

This module is built with 32 individually controllable Form C Armature type Power Relays. The Normally Open, Normally Closed and Common contacts of each relay are individually wired out to three separate pins on a "D" style connector as shown below. Any number of relays may be closed simultaneously, and the status of all relays may be read at any time by the controlling computer.



25 Pin "D" Connector

AVAILABLE MODELS

- **CY/32KCP-** 32 Form C Power Relays Switch Module

CONNECTORS

- Four 25 Pin Ds

CY/32KCP SPECIFICATIONS

Power	+5 V, 1.2 Amp. Max. +12 V, 25 mA per ener. relay
TYPE P RELAY RATINGS	
Switching Power	2000VA, 150W
Switching Voltage	380VAC
Switching Current	8 Amp.
Breakdown Voltage	1200 VRMS
Operate Time	10 mSec. Max.
Mechanical Life	10^7 Operations

PRICING:

CY/32KCP	**$ 1,000.00**

WARRANTY

CYTEC Corp. warrants that all products are free from defects in workmanship and materials for a period of 5 years.

FOR TECHNICAL ASSISTANCE CALL 1-800-346-3117

CYTEC CORP.

BULLETIN
CY/CX

2555 Baird Road, Penfield, New York 14526 (716) 381-4740 FAX (716) 381-0475

CY/CX COAXIAL MATRIX

VXI C-SIZE SWITCH MODULE

The CY/CX Module is a high frequency coaxial matrix with 50 ohm characteristic impedance through any signal path and bandpass up to 200 MHz.
The matrix is bidirectional and non-blocking, switching any one input to one output with coaxial dry reed relays and rated at 10VA.
Standard input and output connectors are SMA.


MATRIX CONFIGURATIONS

The basic module has two separate 8x4 matrices which can be supplied as one 8x8 or one 16x4 matrix.

CY/CX-2(8x4) - This has two individual **8x4** matrices as shown in **Fig. 1** and each matrix has a bandpass from **DC to 200 MHz (-3dB)** with crosstalk of **-40dB at 100 MHz**.

CY/CX-8x8 - The two **8x4** matrices are interconnected by isolation relays shown in **Fig. 1** to form an **8x8** matrix. The relays also serve to reduce stub length and maintain bandpass from **DC to 170 MHz** with crosstalk of **-40dB at 100 MHz**.

CY/CX-16x4 - The two **8x4** matrices are interconnected by additional isolation relays to form a **16x4** matrix. The relays also serve to reduce stub length and maintain bandpass from **DC to 170 MHz** with crosstalk of **-40dB at 100 MHz**.



REED RELAY SPECIFICATIONS

	Type S
Contact Rating	10VA
Maximum Switching Voltage	200V
Maximum Switching Current	0.5A
Breakdown Voltage	400V
Operate Time, less than	1ms
DC Isolation - ohm	10^{12}
Capacitance across reeds	0.1pF

Member of the VXI Plug and Play Alliance..

GENERAL SPECIFICATIONS

Power	**+5 Volts**	less than 1.2 Amp
	+12 Volts	20 mA per energized relay

PRICE LIST

CY/CX-2(8x4)	**$1,900.00**
CY/CX-8x8	**$1,800.00**
CY/CX-16x4	**$2,000.00**

WARRANTY

CYTEC Corp. warrants that all products are free from defects in workmanship and materials for a period of 5 years. Reed relays are guaranteed for 100 million operations when used within their published specifications.

CONTACT 1-800-346-3117 OR WWW.CYTEC-ATE.COM
FOR TECHNICAL ASSISTANCE

CYTEC CORP.

BULLETIN
CY/8x8

2555 Baird Road, Penfield, New York 14526 (716) 381-4740 FAX (716) 381-0475

CY/8x8 REED RELAY MATRIX

VXI C-SIZE GENERAL PURPOSE SWITCH MODULE

The CY/8x8 is a general purpose, bidirectional reed relay matrix. It is a true non-blocking matrix, and each input can be connected to one, many or all outputs concurrently. All CYTEC VXI Modules utilize both Message and Register based operation.

DETAILED DESCRIPTION

The CY/8x8 holds two individual 8x4 matrices. These can be interconnect externally by the user to provide one 8x8 or one 16x4 matrix. This VXI Switch Module is built with 64 Reed Relays and is available in either single or two pole versions, and with Type S Standard or Type M Mercury reeds. It is also available as a two pole matrix with Type LT Low Thermal reeds. Any number of relays can be energized concurrently, and the status of all relays may be read at any time.

AVAILABLE MODELS

- **CY/8x8-1S** - Single Pole Type S Standard Reed Relays
- **CY/8x8-1M** - Single Pole Type M Mercury Wetted Reeds
- **CY/8x8-2S -** Two Pole Type S Standard Reeds
- **CY/8x8-2M -** Two Pole Type M Mercury Wetted Reeds
- **CY/8x8-LT -** Two Pole Low Thermal Reed Relays

CONNECTORS


- Three 34 Pin Headers

REED RELAY SPECIFICATIONS

- **Type S** - Standard Dry Reed Relays.
- **Type M** - Mercury Wetted Reed Relays.*
- **Type LT** - Low Thermal Reed Relays.

	Type S	Type M	Type LT
Contact Rating	10VA	50VA	10VA
Max. Switch Voltage	200V	500V	100V
Max. Switch Current	0.5A	2.0A	0.2A
Breakdown Voltage	400V	1000V	200V
Operate Time, less than	1ms	2ms	1ms
DC Isolation - Ohms	10^{11}	10^{11}	10^{12}

* Must be operated in vertical position



GENERAL SPECIFICATIONS

Power	**+5 Volts**	less than 1.0 Amp
	+12 Volts	20 mA per energized relay
Bandpass		DC to 100 MHz (-3dB)
Insertion Loss		less than 0.2 dB at 10 MHz
Isolation/Crosstalk		100 kHz - 80 dB
		1 MHz - 60 dB
		10 MHz - 40 dB
DC Isolation		Greater than 10^{10} ohms

WARRANTY

CYTEC Corp. warrants that all products are free from defects in workmanship and materials for a period of 5 years. Reed relays are guaranteed for 100 million operations when used within their published specifications.

Member of the VXI Plug and Play Alliance..

FOR TECHNICAL ASSISTANCE CALL 1-800-346-3117

CYTEC CORP.

BULLETIN
CY/16x8

2555 Baird Road, Penfield, New York 14526 (716) 381-4740 FAX (716) 381-0475

CY/16x8 ARMATURE RELAY MATRIX

VXI C-SIZE GENERAL PURPOSE SWITCH MODULE

The CY/16x8 is a two pole, bidirectional armature relay matrix that is used to switch instrumentation level signals. It is a true non-blocking unit, and each input can simultaneously be connected to one, many or all outputs. All CYTEC VXI Switch Modules utilize both Message and Register based operation.

DETAILED DESCRIPTION


The CY/16x8 is built with 128 two pole Type A Armature Relays and is designed to be used for switching instrumentation level signals. The relays are organized as sixteen rows in the Y direction and eight columns in the X direction. All switching paths are two wires with integral grounds located between all path pairs. Status checking of any input reports all connected outputs, and any number of relays can be energized at one time.

CONNECTORS

- Three 20 Pin Headers

TYPE A ARMATURE RELAY SPECIFICATIONS

	Type A
Contact Rating	30W, 62.5VA
Maximum Switched Voltage	110VDC, 125VAC
Maximum Switched Current	1.0A
Breakdown Voltage	750Vrms
Operate Time	2msec
Release Time	1msec
Lifetime, Resistive Load	
Mechanical	10^8 Operations
1A, 30VDC	$2x10^5$ Operations
0.5A, 125VAC	10^5 Operations
Contact Resistance	50 milli ohm max.
DC Isolation - Ohms	10^9



SPECIFICATIONS

Power	**+5 Volts**	less than 1.2 Amp
	+12 Volts	25 mA per energ. relay
Bandpass		DC to 50 MHz (-3dB)
Insertion Loss		less than 0.2dB at 10 MHz
Isolation/Crosstalk		less than -50dB at 10 MHz

WARRANTY

CYTEC Corp. warrants that all products are free from defects in workmanship and materials for a period of 5 years.

Member of the VXI Plug and Play Alliance..

FOR TECHNICAL ASSISTANCE CALL 1-800-346-3117

CYTEC CORP.

BULLETIN
CY/MW

2555 Baird Road, Penfield, New York 14526 (716) 381-4740 FAX (716) 381-0475

CY/G AND CY/M C-SIZE VXI MICROWAVE SWITCH MODULES

The CY/G and CY/M Series of Microwave Switch Modules have user defined configurations and are used to switch RF Signals. Bandpasses of approximately 1.0, 18 and 26 GHz can be provided, and characteristic impedances of either 50 or 75 ohms are available.

MICROWAVE SWITCH MODULES

These Modules are one or two slot wide C-Size VXI Switch Modules which are built in accordance with the end users needs. Two basic series are available: The **CY/G Switch Modules** that furnish a bandpass of about 1 GHz, and the **CY/M Switch Modules** that typically have a bandpass of 18 GHz, with 26 GHz optionally available.

CY/G 1 GHZ VXI SWITCH MODULES

The **CY/G** VXI Switch Modules are assembled using the CXR/2x1-1G, CXR/4x1-1G, CXR/8x1-1G, and CXR/4x2-1G Gigahertz Switch Cards. These cards provide a bandpass of approximately DC to 1 Gigahertz. Multiple cards can be placed in one VXI module, with the number of cards typically limited only by the available VXI panel area.

CY/M 18 OR 26 GHZ VXI SWITCH MODULES

The **CY/M** VXI Switch Modules are used for switching microwave signals. These are one or two slots wide and are built with either the CXM/2x1 A/B Switches or the CXM/Nx1 Rotary Microwave Switches. A bandpass of DC to 18 GHz is standard, with DC to 26 GHz optionally available. As an example, six CXM/6x1 Switches can be fitted into a single two-slot VXI Switch Module.

AVAILABLE MODELS


- **CY/G** One Gigahertz VXI Switch Modules
- **CY/M** Microwave VXI Switch Modules

CONNECTORS

- **SMA recommended because of limited panel space.**
- **Consult factory for other options.**

PRICING:

These Modules are designed so that they can be assembled using a selection of Microwave relays to meet the customer's specification.
Call our Technical Sales for pricing of your specific requirement.




CXR/8x1-1G - Typical of a GHz Switch used in CY/G VXI Switch Modules.

SPECIFICATIONS

Power
+5 Volts, 2.1 A Max.
+12 Volts, 0.2A Max.

Relay Drive Power
Dependent on type of Microwave relays required.




Six CXM/6x1 Relay Module

WARRANTY

CYTEC Corp. warrants that all products are free from defects in workmanship and materials for a period of 5 years. Microwave relays are warrantied for only two years.

Member of the VXI Plug and Play Alliance.

FOR TECHNICAL ASSISTANCE CALL 1-800-346-3117



For additional details contact Cytec technical sales at 1-800-346-3117 or www.cytec-ate.com or sales@cytec-ate.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP