

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions


Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*

Overview





Features

- Sizes 17, 23, 34 and 42
- Optimized for use with IDC's microstepping controls
- Bipolar current ratings for use with IDC's microstepping controls
- High torque-to-inertia, yielding high acceleration
- 120°C rated Class B winding
- 12-ft motor cables standard
- Encoder optional (sizes 23, 34, 42); see page G-61
- Quick disconnect motor cabling option (sizes 34 and 42)

Model	Holding Torque oz-in [N-m]	Recommended Current/Phase Series [Parallel]	See page
S12	30 [0.25]	1.0 [2.0]	G-47
S21	65 [0.46]	1.2 [2.4]	G-48
S22	100 [0.71]	1.5 [3.0]	G-49
S23	125 [0.88]	1.75 [3.5]	G-50
S32	300 [2.1]	2.8 [5.6]	G-53
S33	400 [2.8]	3.5 [7.0]	G-54
P21	100 [0.7]	0.7 [13]	G-51
P22	200 [1.4]	1.0 [2.0]	G-52
P31	450 [3.2]	1.5 [3.0]	G-55
P32	920 [6.5]	1.6 [3.3]	G-56
P33	1260 [8.9]	2.0 [4.0]	G-57
P41	1250 [8.8]	2.8 [5.7]	G-58
P42	2300 [16.2]	3.3 [6.6]	G-59
K42	3000 [21.2]	3.2 [6.4]	G-60

How To Order

Motor Models	Options
S12	None
S21, S22, S23 P21, P22	EMK EM
S32X, S33X	EMK EM C25
P31X, P32X, P33X P41X, P42X K42X	EMK EM EQK EQ EQK25 EQ25 C25

Description

EMK – 1000 line encoder option with 12-ft, jacketed cable
EM – 500 line encoder option with 12-ft, jacketed cable
EQK – 1000 line encoder with 12-ft quick disconnect cable
EQ – 500 line encoder with 12-ft quick disconnect cable
EQK25 – 1000 line encoder with 25-ft quick disconnect cable
EQ25 – 500 line encoder with 25-ft quick disconnect cable
C25 – 25-ft quick disconnect motor lead cable

A 30% torque safety margin is recommended when applying step motors.


Replace the Xs in the above part numbers with N, T or V:
N = 8 leads, 12 inches long
T = Series wired motor and 12-foot quick-disconnect cable included
V = Parallel wired motor and 12-foot quick-disconnect cable included

To confirm your selection, review the checklist on page G-6.


Performance

S23 Hybrid Step Motor in [mm]

CE certified



Motor Performance



120 Series (100% duty cycle)

120 Parallel*/240 Series*
* 50% duty cycle max above 5 rps (300 rpm)

A 30% torque safety margin is recommended when applying step motors.



Warning: Do not run S21, S22 or S23 motors wired in parallel with a NextStep 240 drive or SmartStep 240. Motors will exceed their rated temperatures and be damaged. All motors should be wired in series when run with the NextStep 240 or SmartStep 240.

Applying Gearmotors

- See page I-1 for IDC gearmotor information and for how to determine gearmotor performance



Motor and Encoder Data	S23 Series	S23 Parallel
Continuous Stall Torque oz-in [N-m]	125 [0.88]	
Recommended Current/Phase Amps	1.7	3.5
Inductance mH	18	4.5
Max. Motor Winding Temp. °F [°C]	248 [120]	
Rotor Inertia oz-in-s^2 [kg-m^2]	4.97x10^{-3} [3.51x10^{-5}]	
Axial Shaft Load lbs [N]	10 [44]	
Radial Shaft Load @ 0.75" [19 mm]	15 [66]	
Motor Weight lbs [kg]	3.2 [1.5]	
Step Angle (full step) degrees	1.8	
How to order	G-46	

Performance Planetary Gearmotors

In-line  Right-angle 

Gear Ratio in [mm]	L	A x B
3 to10	6.8 [172.2]	3.61 x 10.51 [91.7 x 266.9]
16 to 100	7.6 [193.3]	3.61 x 11.34 [91.7 x 288.0]
160 to 700	8.4 [213.4]	Above 100:1, not available

Value Planetary Gearmotors

In-line  Right-angle 

Gear Ratio in [mm]	L	A x B
3 to 10	7.1 [180.0]	3.61 x 10.80 [91.7 x 274.3]
16 to 100	8.0 [203.0]	3.61 x 11.70 [91.7 x 297.2]

Industrial Devices Corporation
707-789-1000 • 800-747-0064 • E-mail: info@idcmotion.com

Specifications

The -EMK option provides an incremental 1000 line rotary encoder coupled to the rear shaft of our S, P and K Series step motors.

The -EM option provides an incremental 500 line rotary encoder coupled to the rear shaft of our S, P and K Series step motors.

An encoder is typically used with the SmartStep, S6961 and S6962 programmable step motor controls to provide stall detection and position maintenance. Encoders are also commonly used with displays to provide position information, or to provide position feedback to your own controller when using our NextStep® or S6002 drive.

-EM and -EMK are compatible with:
S, P and K Series step motors and gearmotors, sizes 23, 34 and 42

Electrical

Output Format	Incremental, dual square wave quadrature, with index.
-EMK Pulses Per Revolution	1000 line (4000 post-quadrature), one index line
-EM Pulses Per Revolution	500 line (2000 post-quadrature), one index line
Supply Voltage	5VDC ± 5 %
Current Requirements	140 mA
Frequency	100 kHz pre-quadrature, max.

Mechanical

Outline Dimensions	Adds 1.0 inch to the length of 23 frame motors. No dimension change on 34 and 42 frame motors.
Speed	6000 rpm max
Weight	6 oz
Cable	12-foot cable standard

Environmental

Operating Temperature	-10° to 70°C (S Series, P2X Series), -10° to 100°C (P3X, P4X & K Series)
Storage Temperature	-20° to 70°C (S Series, P2X Series), -30° to 110°C (P3X, P4X & K Series)
Housing	Drip-proof
Vibration	10 to 200 Hz @ 5Gs (S & P2X Series), 5-2000 Hz @ 10 Gs (P3X, P4X & K Series)
Shock	100G for 6 ms (S & P2X Series, 50 G for 11 ms (P3X, P4X & K Series)

Notes:

- S32, S33, P31, P32, P33, P41, P42, and K42 motors: the encoder is housed inside the rear plate of the motor.
- The encoder adds 1.0 inch to the length of the S21, S22, S23, P21 and P22 motors.
- The encoder cable can be extended by the customer to a maximum of 100 feet if a high quality shielded, twisted pair cable is used.

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP