

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.


Visit our website - *Click HERE*

M06

Standard 60mm Frame Size (NEMA Size 23)

Performance Envelope

(see page xx for detailed torque-speed curves)






- Up to 150% rated torque reserve capacity
- ± 3% typical step accuracy
- UL and Canadian recognized
- Standard terminal box, encoders, and precision gearheads available
- Available with four, six or eight leads
- Customized configurations available

Motor Frame	Minimum Holding Torque		Rotor Inertia	Weight		Maximum Shaft Load		Minimum Residual Torque
	Unipolar 2Ø on	Bipolar 2Ø on		Net*	Ship*	Overhang	Thrust	
	oz-in (Ncm)	oz-in (Ncm)	oz-in-s² (kg-cm²)	lb (kg)	lb (kg)	lb (kg)	lb (kg)	oz-in (Ncm)
M061	60 (42)	75 (53)	0.0017 (0.12)	1.3 (0.57)	2.5 (0.68)	15 (6.8)	25 (11)	1.0 (0.71)
M062	100 (71)	125 (88)	0.0034 (0.24)	2.0 (0.91)	2.5 (1.1)	15 (6.8)	25 (11)	1.4 (0.99)

** Weight for motor with leads*

Distributed by ELECTRO SALES CO., INC. Phone: (617) 666-0500 ~ Fax: (617) 628-2800
Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

SLO-SYN® DC STEP MOTORS



See next page for detailed model number information

◊ 4-CONNECTION STEP MOTORS					
Model Number		Winding Specifications			
New	Old (Leads)	Voltage VDC	Current Amperes	Resistance ohms	Inductance mH
M061-□F01	M061-LF-408	8.0	0.50	16	61
M061-□F03	M061-FF-206	6.3	1.0	6.3	25
M062-□F03	M062-LF-402	6.6	1.0	6.6	33
M062-□F04	M062-FF-206	4.2	1.5	2.8	13
M063-□F04	M063-FF-206	5.4	1.5	3.6	18


6-CONNECTION STEP MOTORS								
Model Number	Winding Specifications							
	Unipolar				Bipolar Series			
See next page for options	Voltage VDC	Current Amperes	Resistance ohms	Inductance mH	Voltage VDC	Current Amperes	Resistance ohms	Inductance mH
M061□S-301	11	0.44	23	38	16	0.30	45	150
M061□S02	5.0	1.0	5.0	9.6	7.0	0.70	10	38
M061□S08	1.3	3.8	0.33	0.64	1.8	2.7	0.66	2.5
M062□S03	5.3	1.6	3.3	8.3	7.5	1.1	6.6	33
M062□S04	4.2	1.9	2.2	5.9	5.9	1.3	4.4	24
M062□S06	2.6	3.1	0.88	2.0	3.9	2.2	1.8	8.0
M062□S09	1.7	4.7	0.35	0.80	2.3	3.3	0.7	3.2

8-CONNECTION STEP MOTORS								
Model Number	Winding Specifications							
	Unipolar				Bipolar Parallel ♦			
See next page for options	Voltage VDC	Current Amperes	Resistance ohms	Inductance mH	Voltage VDC	Current Amperes	Resistance ohms	Inductance mH
M061□E02	5.0	1.0	5.0	9.6	3.5	1.4	2.5	9.6
M061□E08	1.3	3.8	0.33	0.64	0.89	5.4	0.16	0.64
M061□E04	4.2	1.9	2.2	5.9	3.0	2.7	1.1	5.9
M062□E06	2.6	3.1	0.88	2	1.9	4.4	0.44	2.0
M062□E09	1.7	4.7	0.35	0.80	1.2	6.7	0.18	0.80

◊ *nameplate may reference old model number*
♦ *see 6-leead table for 8-lead bipolar series ratings*


Distributed by ELECTRO SALES CO., INC. Phone: (617) 666-0500 ~ Fax: (617) 628-2800
Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Motor Dimensions



Add "E" to model number for double ended shaft. Example: M062-LS03E

Encoder



Add to Model Number:		
C	500	6

Pulses per Revolution

200, 400, 500, or 1250

Number of Outputs


2 A, B *(not available with 1250)*
3 A, B, Index *(not available with 1250)*
6 A, B, Index, A, B, Index
Differential Line Drivers supplied with 6 outputs

M061-LE08C2003 single stack, eight leads, 8 amps, 200 pulse encoder with A , B outputs

M062-LS09C12506 double stack, six leads, 9 amps, 1250 pulse encoder with 6 ouputs.

(consult factory for encoder with terminal box)

Terminal Box



Change Model Number:	
Example: M062-TE09	(double stack, terminal box, eight leads, 9 amp winding)

(consult factory for encoder with terminal box)

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com


24 V Bipolar - Full Step


36 V Bipolar - Full Step


72 V Bipolar - Full Step

- 24 and 36 volt data measured with SD200 Modular Drive Module or the SS2000MD4 Modular Drive.
- 72 volt data measured with MD808 Modular Drive


M061









M062







- The curves do not show system resonances which will vary with system mechanical parameters.
- Duty cycle is dependent on torque, speed, Drive parameters, and heat sink conditions. **Maximum case temperature is 100°C.**

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP