

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*

CY3600i

FLASH370i™ ISR™ Programming Kit

Features

- **Supports FLASH370i™ and Ultra37000™ devices (for Ultra37000V 3.3V support, please see the Ultra37000 ISR™ Programming Kit data sheet, CY3700i)**
- **Jam programming language support for Ultra37000 devices**
- **Standard JTAG programming interface**
- **Multi-device programming**
- **Supports cascading of devices**
- **Easy to use Windows 95™, Windows 98™, and Windows NT™ 4.0 compatible interface**
- **Eliminates programming insertion to improve manufacturing efficiency**
- **For programming in the lab, on the manufacturing floor, or at remote sites**
- **ATE support via Jam on industry leading ATE platforms**

Kit Contents

- **ISR (In-System Reprogrammable™) Programming Cable for use with FLASH370i and Ultra37000 devices**
- **ISR Programming Software Release 2.2**
- **ISR Application Notes**

Functional Description

The ISR programming kit enables users to program FLASH370i and Ultra37000 CPLDs on board with our ISR Programming Kit, ISR programming cable, and a personal computer. The ISR programming cable connects to the parallel port of a PC into a standard 10-pin male connector mounted on the user's board.

ISR Programming Software

The ISR software provides an easy to use Graphical User Interface that accepts JEDEC files as input. The JEDEC files are used in ISR programming for FLASH370i CPLDs.

JEDEC files are also used to compose platform and device independent Jam files. Jam files are used in ISR programming for Ultra37000 CPLDs.

The ISR software reads in a simple user-defined configuration file that dictates how many devices are in the daisy chain and what operation is to be done on each Cypress device. The same chain can be used with other JTAG compliant devices.

The ISR User's Guide (in the CD-ROM documentation) describes the operation of the ISR software. The application notes included with the kit describe the Ultra37000 and FLASH370i architectures and system design considerations for programming with the FLASH370i ISR Programming Kit.


10-pin ISR Connector

The diagram below shows the pinout of the 10-pin male connector to be mounted onto the board.

The view looking down onto the board is shown below.

SDO	VCC	ISR[1]	ISRVPP	GND[2]
GND	NC	SDI	SCLK	SMODE

ISR PC Cable Programming



Notes:
1. Refer to the CD-ROM ISR User's Guide documentation for detailed information on ISR programming and electrical specification requirements.
2. Pin1 Connection.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Table 1. FLASH370i Pin Description.

Pin	Type	Description
ISRVPP	OUTPUT	In System Reprogramming high-voltage programming pin.
ISR*	OUTPUT	In System Reprogramming enable indicator (active LOW).
VCC	INPUT	+5V supply voltage provided from the target system to the cable.
SDO	INPUT	Serial Data Output Receiver. The SDO output pin of the last device in the ISR chain of the system is connected to this input pin.
SMODE	OUTPUT	Serial Mode Control. This is the mode select control input for the TAP controller state machine contained in the ISR interface.
SCLK	OUTPUT	Serial Clock. ISR interface clock input.
SDI	OUTPUT	Serial Data Input Driver. This output pin is connected to the SDI input of the first device in the ISR chain.
NC	NC	No Connect.
GND	—	Zero volt common ground for PC and target system.

Table 1 describes the function of each of these pins on the ISR programming cable. An OUTPUT is provided by the PC and an INPUT is provided by the target system. The dimensions of the male connector required in the system are given below:

Male Connector:

- 2 x 5 = 2 rows, 5 pins per row
- Measuring from center of the pins, each pin is 0.1” from the others.
- Pin Length is 0.23”
- Pin cross-section is 0.025” x 0.025”

Part Number:

- Digi-Key® S2012-05-ND (straight-pin connector)
- Digi-Key S2112-05-ND (right-angle connector)

PC System Requirements

- One free parallel port
- 486 / 66MHz PC or better
- Windows 95/98/NT
- 16 MB of RAM
- 1MB or more disk space

Ordering Information

Product Code	Description
CY3600i	ISR Programming Kit

ISR, Ultra37000, and FLASH370i are trademarks of Cypress Semiconductor Corporation.
Windows 95, Windows 98, and Windows NT are trademarks of Microsoft Corporation.
Digi-Key is a registered trademark of Digi-Key Corporation.

© Cypress Semiconductor Corporation, 2001. The information contained herein is subject to change without notice. Cypress Semiconductor Corporation assumes no responsibility for the use of any circuitry other than circuitry embodied in a Cypress Semiconductor product. Nor does it convey or imply any license under patent or other rights. Cypress Semiconductor does not authorize its products for use as critical components in life-support systems where a malfunction or failure may reasonably be expected to result in significant injury to the user. The inclusion of Cypress Semiconductor products in life-support systems application implies that the manufacturer assumes all risk of such use and in doing so indemnifies Cypress Semiconductor against all charges.
Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Document Title: CY3600i FLASH370i™ Programming Kit Document Number: 38-03041				
REV.	**ECN NO.**	**Issue Date**	**Orig. of Change**	**Description of Change**
**	106566	09/15/01	SZV	Change from Spec number: 38-00733 to 38-03041

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

This datasheet has been download from:

www.datasheetcatalog.com

Datasheets for electronics components.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP