

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*

VXI130



VXI130
Differential/Single-Ended TTL VXI Module

Features

- 192 Channel Differential TTL / TLL interface
- 50MHz transfer rate
- Six user loadable FPGAs for automated data processing
- Single slot VXI form factor
- 32-bit VXI/VME bus interface
- Integrated over-voltage protection on all lines

Phillips Aerospace
16125 East Gale Ave.
Industry Ca 91745
www.paero.com • info@paero.com
(626) 855-4600

Summary

Phillips' VXI130 configurable Differential TTL /TTL module interface card is an intelligent digital interface capable of supporting development and validation testing. The VXI130 has 6 on-board field programmable gate arrays (FPGAs) to support bus emulation, protocol simulation, test algorithm generation and other data conversion functions.

The user can configure (on-the-fly) the direction and type of I/O for each pin. Two pins can operate independently as single-ended TTL I/O or together as a true differential TTL I/O high speed pair.

The VXI130's six ACEX1K100s have capacity and memory to support complex operations decoupled from the PCI bus. This allows the VXI130 to operate at high speed without being interrupted by the host controller.

The user can program the FPGAs through the VXI interface, or via on-board EPROM so the board is automatically loaded. Example FPGA code and driver source code are provided with the VXI130.

The VXI130 has a VME32 compatibility mode that allows high speed operation with a VME style real-time host controller instead of a VXI host controller.

Custom versions of the VXI130 are available to our customers. Please contact the factory for further information.

Specifications

Channels:	192 user-defined I/O, direction control for each, two I/O can be combined to operate as a differential pair
Clock Rate:	50MHz max
Output:	H>2V into 50Ohms, L<0.2V Sink 20mA Source 20mA
Input:	H>2V, L<0.8V
Termination:	120Ω (differential mode)
OVP:	Transient suppression on all lines
Clocks:	On-board crystal, DDS
FPGA:	ACEX1K100
Connectors:	Six VHDCI 68-pin female connectors
Power:	+5V @ 6.0A max

Ordering Information

Hardware

335-4113
VXI130 192 channel differential TTL / TTL

335-4112
VXI130 128 channel differential TTL / TTL

335-4111
VXI130 64 channel differential TTL / TTL

Software

VXI-API-QNX
QNX® software support package

VXI-API-WIN
Windows® DLL software package

Accessories

TP-DIN68S
Termination panel, VHDCI receptacle

CBSCSI-6803MM
Cable, shielded, 3-ft, VHDCI plug at both ends

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP