ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction


All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *DDC BU-67107i* at our website: ***Click HERE***


Multi-I/O MIL-STD-1553 & ARINC 429 PMC, PCI, and cPCI/PXI Cards

Product Brief


Models: BU-67107F/M/I/T



BU-67107F



BU-67107T



BU-67107M



BU-67107i

Rugged and reliable, DDC's PMC family of embedded cards are engineered for rugged environments and can be used in conduction cooled or air cooled systems. The Multi-I/O mix on a single card saves space, power, weight, and cost—making this an ideal solution for systems with limited space. The cards are also available in PCI and compact PCI/PXI form factors with a cable assembly for test applications.

Key Features

- Up to 4 Dual Redundant MIL-STD-1553 Channels
  - BC/Monitor or Multi-RT/Monitor per 1553 Channel
  - BC Disable for RT Only Applications
  - TX Inhibit for MT Only Applications
- Up to 16 Receive and 6 Transmit 429 Channels
  - High / Low Speed Operation
  - Supports Multiple ARINC Standards
  - Multiple Reception and Transmission Methods
- ARINC 429 Only Model Available
- Up to 6 Digital Discrete I/O
- Up to 2 RS-232 and 2 RS-422/485 Channels
- IRIG-B Time Code Input
- 48-bit/100ns Time Stamp
- ACEXTREME® - Next generation 1553 Core

Benefits

- Rugged PMC Design for Harsh Environments
- Available in PCI and cPCI/PXI Form Factors with Cable for Test Environment
- Field Proven Reliable Technology Based on over 62 Million Hours of In-Flight Performance
- Unique Multi-I/O Mix Reduces:
  - Space, Power, Weight, Cost
- Shorten Development Cycle and Reduce Risk with Automated Code Generation
- IRIG-106 Chapter 10 On Board Formatting
- On-Board DMA Engine for Low CPU/PCI Utilization

Applications

- Mission Computers
- Displays
- Digital Data Recorders
- Radar Systems/Situational Awareness
- Commercial Aerospace
- Systems Integration Labs
- Simulators
- Production Test Labs
- System Troubleshooting
- New Product Development

For more information: www.ddc-web.com/BU-67107FM | www.ddc-web.com/BU-67107IT

© 2010 Data Device Corporation. All trademarks are the property of their respective owners.

Printed on recycled paper.

Overview

PMC, PCI, and cPCI/PXI Cards

The BU-67107F/M/I/T series contains up to 16 Receive and 6 Transmit ARINC 429 channels that is optionally available with up to four MIL-STD-1553 channels (Multi-IO) for use in systems that interface to both 1553 and 429. The ARINC 429 model is a perfect fit for commercial aerospace applications while the multi-IO model is a perfect fit for military cargo aircraft, helicopters, and other platforms that use both 1553 and 429.

Quick Specs

POWER DISSIPATION (75% Utilization)	MIN	TYP	MAX
BU-67107M100L (2-Ch. 1553 & 6Tx/8Rx 429)	-	4.2 W	-
BU-67107M000L (4-Ch. 1553 & 4Tx/8Rx 429)	-	5.6 W	-
BU-67107M200L (6Tx/16Rx 429)	-	4.0 W	-

THERMAL		MIN	TYP	MAX
Operating Temperature	PMC	-40 °C	-	+85 °C
	PCI/cPCI/PXI	0 °C	-	+55 °C
Storage Temperature	PMC	-65 °C	-	+150 °C

Ordering Information

BU-67107FX00L-2A0X (Front I/O PMC)

N = Acrylic Conformal Coating
U = Polyurethane Conformal Coating
Blank = No Conformal Coating

2A = -40°C to +85°C Rugged Air Cooled Card

I/O Option	Number of Channels: 1553 Ch	429 Ch Rx	429 Ch Tx	RS-232 Ch	RS-422/485 Ch	Discrete I/O Ch	IRIG-B Input
0	4	8	4	2	2	6	1
1	2	8	4	2	2	6	1
2	0	16	4	0	2	6	1

BU-67107MX00L-2X0X (Rear I/O PMC)

N = Acrylic Conformal Coating
U = Polyurethane Conformal Coating
Blank = No Conformal Coating

2A = -40°C to +85°C Rugged Air Cooled Card
2C = -40°C to +85°C Rugged Conduction Cooled Card

I/O Option	Number of Channels: 1553 Ch	429 Ch Rx	429 Ch Tx	RS-232 Ch	RS-422/485 Ch	Discrete I/O Ch	IRIG-B Input
0	4	8	4	1	2	6	1
1	2	8	6	2	2	6	1
2	0	16	6	0	2	6	1

BU-67107XX00L-JL0 (Front I/O PCI, and cPCI/PXI*)

JL = 0°C to +55°C Non-Rugged Card

I/O Option	Number of Channels: 1553 Ch	429 Ch Rx	429 Ch Tx	RS-232 Ch	RS-422/485 Ch	Discrete I/O Ch	IRIG-B Input
0	4	8	4	2	2	6	1
1	2	8	4	2	2	6	1
2	0	16	4	0	2	6	1

I = PCI Card
T = 3U cPCI/PXI Card

*1553 cable interface included with purchase

Included Software:

- 1553 C Software Development Kit (SDK)
- WindowsXP/Vista/7, Linux, and VxWorks support

Optional Software:

BusTRACER Data Bus Analyzer and Monitor Software



- Generate or monitor live MIL-STD-1553 data without writing any code
- Saves time and reduces development costs
- Program in minutes with one-click ANSI 'C' application source code generation
- Rapid creation and setup of custom applications

Model: BU-69066S0-XX0


dataSIMS Avionics Data Bus Test and Analysis Software



- Accelerates development and deployment
- Eliminates cost of learning and maintaining separate software programs
- Easy-to-use and customize
- Supports all data protocols and I/O formats

Model: BU-694X4DS-64VM

LabVIEW® & LabVIEW Real-Time Support



- Simple interface for quick startup and easy programming
- Access real-time 1553/429 data using LabVIEW
- Easily integrate data from different types of instruments and sensors
- Create custom user interface from scratch or by modifying samples provided

Model: BU-69093S0-XX0

Commercial Avionics Utilities



- Graphical ARINC 429 data bus analysis and simulation
- Advanced filtering, message scheduling, and triggering
- Graphical ARINC 615 data loader to load data to and from airborne computers

Model: DD-42999S0-XX0

DATA DEVICE CORPORATION
REGISTERED TO ISO 9001:2008
REGISTERED TO AS9100:2009
FILE NO. A5976



The information in this Product Brief is believed to be accurate; however, no responsibility is assumed by Data Device Corporation for its use, and no license or rights are granted by implication or otherwise in connection therewith. Specifications are subject to change without notice.

For ordering assistance and technical support,
Call: 1-800-DDC-5757
E-mail: service@ddc-web.com
Visit: www.ddc-web.com

Headquarters, N.Y., U.S.A. - Tel: (631) 567-5600, Fax: (631) 567-7358
United Kingdom - Tel: +44-(0)1635-811140, Fax: +44-(0)1635-32264
France - Tel: +33-(0)1-41-16-3424, Fax: +33-(0)1-41-16-3425
Germany - Tel: +49-(0)89-1500-12-11, Fax:+49(0)89-1500 12-22
Japan - Tel: +81-(0)3-3814-7688, Fax: +81-(0)3-3814-7689
Asia - Tel: +65-6489-4801

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP