ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *DDC SCS750G4* at our website: *Click HERE*

SCS750®
Single Board Computers for Space

Connectivity Power Control

Product Brief

Models: SCS750, SCS750G4



DDC's space-proven SCS750® Single Board Computer, featuring the best single event performance, seamless error correction, a wide range of processing power, and the highest design margin, is now available with SpaceWire and NAND Flash. Since inception, more than 20 years ago, our electronic components and single board computers have experienced zero failures in space!

Key Features

- Proven in Space, TRL-9
- Wide Range of Operating Capability
  - 200 to 1800 MIPS
  - 7 to 30 Watts Typical
- Outstanding SBC Radiation Hardness
  - TID Greater than 100krad (Si)
  - SEU Hard; 1 Board Upset Every 80/115 Years (GEO/LEO)
  - SEL Immune
- VxWorks®, RTEMS, and Linux Development Platforms
- 4 SpaceWire Ports (SCS750G4 Only)
  - Up to 200Mbps Each
- Optional 1553 Interface Available
- 64 GBytes of BCH Corrected NAND Flash (SCS750G4 Only)

Custom Design Capability - DDC can customize designs for all cards, ranging from simple modifications of standard products to fully customized solutions for commercial, military, aerospace, and industrial applications.

Benefits

- DDC's SCS750 Products Utilize Reliable Silicon-on-Insulator Power PC Processors, & Radiation Hardened Parts, Including DDC's RAD-PAK® Memories, In Conjunction with Triple Redundant Processing Algorithms that Provide Comprehensive Error Detection and Correction.
- DDC's Single Board Computers Achieve the Best SEE Performance (Less than One Error in 80 years)
- Enables Satellite Design to Dramatically Increase Error-free, On-board Data Processing, Mission Planning, and Critical Decision Making
- Speed and Power Settings Can be Managed via Software in Real Time - No Reboot Required
- DDC's SCS750 has Become the Benchmark Against Which All Space Processor Boards are Measured
- Operates in a cPCI System Targeting High Performance Computing for the most Demanding Space Applications

Applications

- Launchers
- Satellites
- Payload Processing
- Command & Control

For more information: www.ddc-web.com/SCS750 | www.ddc-web.com/SCS750G4

© 2017 Data Device Corporation. All trademarks are the property of their respective owners.

Printed on recycled paper.

Quick Specs

FEATURE	DESCRIPTION
(3) Fully TMR Protected Processors	PowerPC 750FX™ silicon on insulator (SOI), 0.13µm 2.32 Dhrystone MIPS/MHz >1800 Dhrystone MIPS @ 800MHz 400 to 800MHz – Software selectable core clock rate **L1 Cache**: 32Kb instruction with parity, 32Kb Data with parity **L2 Cache**: 512Kb on-chip with ECC @ CPU core clock rate
Memory	**Volatile**: 256 MByte SDRAM – Reed-Solomon protected – Double Device Data Correction
	Non-Volatile: **SCS750 Only: 8 MByte EEPROM – ECC Corrected** 7.0 MByte EEPROM available to user 0.5 MByte Primary SuROM 0.5 MByte Secondary SuROM (autoswap on primary failure) **SCS750G4 Only: 4 MByte EEPROM – ECC Corrected** 3.0 MByte EEPROM available to user 0.5 MByte Primary SuROM 0.5 MByte Secondary SuROM (autoswap on primary failure) **64 GByte NAND Flash BCH – ECC Corrected**
Radiation Tolerance	One board upset every 80 years in GEO orbit and 115 years in LEO orbit **TID**: > 100 krad (Si) – orbit dependent **SEL (th)**: 84 MeV-cm^2/mg (room temp)
Interfaces	**SpaceWire***: 4 active, up to 200Mbps, supports RMAP & DMA/Descriptors **cPCI Bus**: 6U, 3.3V, 32 bit, 33MHz, Master/Target & Syscon/Peripheral **1553**: BC/RT/MT, SEU Immune **Serial**: 2 UART (LVDS or RS422*), 2 Serial Communications Controllers (SCC) - Sync or Asynch (LVDS or RS422*) **Programmable I/O**: 32/64* LVCMOS general purpose I/O (GPIO), Input, Output, or Interrupt Input
Power	8 - 38 watts (typical) dependent on clock rate/MIPS requirements
Operating System	VxWorks®, RTEMS, Linux (contact factory)

FEATURE	DESCRIPTION
Temp Range	-30°C to +65°C Acceptance, -40°C to +70°C Qual
Size/Weight	6u x 160mm / 1.5 Kg (3.3 Lbs.) Max


*Note: Available on G4 version only

Ordering Information

SCS750XX X

- **Configurations:**
  - **F** = Flight Configuration:
    - Rad-Tolerant, Class S or equivalent components
    - Conduction Cooled
    - Flight cPCI Connectors
  - **E** = Engineering Configuration (EM):
    - Parts Identical to Flight, but not screened to flight level
    - Conduction Cooled
    - Flight cPCI Connectors
  - **D** = Engineering Development Configuration (EDM):
    - Commercial Components
    - Full Hardware & Software compatibility with E and F models
    - Conduction or Convection Cooled
  - **P** = Software Development Board:
    - Commercial Components
    - Software Compatibility with E, D, and F Models
    - Convection Cooled
- **Product Versions:**
  - **G4** = SCS750G4 version with SpaceWire and NAND Flash
  - **(blank)** = SCS750 version

Block Diagram



Certified System
Environment
ISO 14001
SAI GLOBAL



The information in this Flyer is believed to be accurate; however, no responsibility is assumed by Data Device Corporation for its use, and no license or rights are granted by implication or otherwise in connection therewith. Specifications are subject to change without notice.

For ordering assistance and technical support,
E-Mail: service@ddc-web.com
Visit: ddc-web.com Data Device Corporation
Call: HQ, N.Y., U.S.A 1-800-DDC-5757 | (631) 567-5600
UK +44-(0)1635-811140
France +33-(0)1-41-16-3424
Germany +49-(0)89-1500-12-11
Japan +81-(0)3-3814-7688
Asia +65-6489-4801
India +91 080 301 10 200

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP