

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions


Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Diagnostic Instruments / SPOT Imaging Solutions 459* at our website: *Click HERE*

Data Sheet





Application

This camera is designed for high-resolution quantitative capture of low light images as well as brightfield images.

This camera is commonly used in low light fluorescence, Dual Phase/fluorescence, Ca++, and GFP applications.


Feature	Benefit
CCD cooled to -5°C from an ambient temperature of 20°C (-25°C differential) ..	Reduces dark noise for long exposure image capture
1600 x 1200 (1.92 Mpixel) image capture ..	Resolves fine detail
Programmable gain (1-32x)	Facilitates live mode previews of low light specimens
12 bit x 6 MHz capture.....	Extra bit depth is ideal for image enhancement
36 MHz live mode (dual channel 18MHz)	High-speed imaging for real time viewing
Interline progressive scan CCD	Electronic shuttering eliminates mechanical shutter shortcomings related to speed, wear, and vibration
PCI Interface.....	Stable, high-speed interface for PC and Mac platforms is over 50% faster than Firewire™ (IEEE 1394)
SPOT™ Software..... Mac® & Windows® operating systems Basic & Advance Applications Twain & Apple Event DLL w/ SDK and Tutorial manual 3rd Party Driver support	Provides essential tools for modern microscopy and is widely supported by 3rd party software companies for high end applications as well as providing DLL with SDK for OEM Driver development

RT™ Monochrome

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Data Sheet

RT™ Monochrome



Captured Frames per Second*

Binning	REGION OF INTEREST		
	1600 X 1200	512 X 512	256 X 256
1 x 1	2.4	10.1	25.3
2 x 2	5.1	20.1	33.4
3 x 3	7.8	25.1	49.9
4 x 4	10.1	33.4	50.4

*.04ms exposure, no post-processing, images saved to RAM on 1.7 GHz P4 running Windows XP

CCD information:
Kodak KAI-2000-M with cover glass
Monochrome progressive scan interline CCD
1600 x 1200, 7.4 µm square pixels
11.8mm x 8.9mm active area
100x minimum anti-blooming

Cooling:
-25˚C differential from ambient via thermoelectric cooler with fan cooled heat sink (-5˚C from an ambient of 20˚C)

Digitization information:
Digitized pixel-by-pixel at CCD sensor
Live mode: 8 bit x 36 MHz (Dual channel 8 bit x 18MHz)
Live image frame rate: 19 frames per second
Capture mode: 12 bit x 6MHz (see chart for frame rate)
A/D Converter full scale set to 31,500 e (Gain=1)
Saved bit depths: 8, 12 or 16 bit BW

Noise specifications:
Read noise: 48 e rms
Dark noise: 0.25 e/p/s mean value

Exposure:
40 microsecond to 536 seconds
Captured and live mode automatic exposure
Captured and live mode manual exposure

Lens mount: C-mount

Sealing window: UBK7 w/ multilayer anti-reflection coating

Computer interface: PCI bus card

External shutter control: BNC TTL level output w/programmable delay

Mechanical:
Tripod mount: 1/4 - 20 UNC
Camera head: 4.94" (126mm) x 4.94" (126mm) x 3.81" (81mm), 2.7 lbs. (1.2 kg)
Power supply: 4.42" (112mm) x 5.25" (133mm) x 3.19" (81mm), 1.46 lbs. (0.66 kg)
Operating environment: 0 to 30˚C ambient, 0-80% relative humidity non-condensing
Power requirements: 85-264 VAC, 47-63 Hz

Certifications: CE, FCC Class A, EN60950

SPOT software features:
Live mode viewing window & controls, auto-exposure live and capture modes, image capture window, predefined and custom image setups, auto white balance, flat field correction, image enhancement tools in three color spaces (RGB, HSL, HSV), pan and zoom windows, annotation, calibration mark, measurement tools, sequential image capture and playback, archiving data base, report generator, interactive print dialog, online help menu

File formats:
BMP, TIFF, TIFF-JPEG, JPEG, JPEG-2000, PICT, AVI

TIFF File sizes:
8 bit BW / 1.83MB
12 bit BW / 2.75 MB
16 bit BW / 3.66 MB

Drivers included:
Twain for supported Windows® operating systems
AppleEvent for supported Mac® operating systems

Native drivers for 3rd party software:
Call or visit our website (www.diaginc.com)

Minimum system requirements:
Full size PCI bus slot or PCMCIA CardBus slot*
*-Requires Magma™ Adapter (sold separately)
PC: Pentium 166 or greater w/
Windows 95, 98, 00, NT, ME, XP
Mac: Power PC, OS 8.6 - OS X
RAM: 64MB minimum, 256MB suggested
Video card: 24 bit RGB @ desired resolution

Items included: Camera head, PCI plug-in board, data cable, power supply cable, power supply, power cord, SPOT software install CD (includes drivers), user guide, 1 year warranty

Catalog Number: RT210

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP