

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Modular GP700

Modular GP700

Two-Position Switch Plug-In

DiCon's Two-Position Switch Plug-In integrates up to four 2x2, 1x2, or On-Off switches. Operating independently of data rate and signal format, the switch uses a moving prism or shutter between fixed collimators to achieve precise channel selection. The Plug-In is designed for easy installation into DiCon's GP700M Modular Mainframe. DiCon's Two-Position Switch Plug-In can be built with Corning SMF-28, Flexcor 1060 or Polarization Maintaining Panda fiber.




Features

- Very low insertion loss
- Precise repeatability
- Low back-reflection
- Flexible fiber types and wavelength ranges

Configurations

2x2 switches provide channel selection from a pair of input fibers to a pair of output fibers.



1x2 switches provide channel selection from one input fiber to two output fibers.



On-Off switches provide channel control from one input fiber to one output fiber.



DiCon FIBEROPTICS, INC


U.S. patented. Specifications subject to change. Copyright ©2001 DiCon Fiberoptics, Inc. All rights reserved.

Specifications[1]

Insertion loss		0.6 dB typ., 1.0 dB max.
Back-reflection	singlemode	-55 dB max.
	multimode	-20 dB typ.
Repeatability[2]		±0.01 dB max.
PDL[3]		0.05 dB max.
Cross-talk		-70 dB max.
Switching time		135 ms max.
Optical power[4]		300 mW max.
Operating temperature		0°C to +40°C max.
Storage temperature		-20°C to +60°C
Humidity		40°C/90%RH/5 days

1. All specifications referenced without connectors.
2. Sequential repeatability for 100 cycles at constant temperature after warm-up.
3. Singlemode only. Measured at 1550 nm.
4. High power version (2W) available as special order.

Housing Dimensions



Units: mm

Ordering Information

PS - [ ] - [ ] - [ ] - [ ] - [ ] - [ ]

Switch Configuration

11	On-Off
12	1x2
22	2x2 non-blocking

Number of Switches

X	Specify quantity (1 to 4)

Fiber Type

9	9/125[1]
50	50/125
62	62.5/125
10	Flexcor 1060[2]
PM	Panda 1300[3]

Wavelength Range[4]

10	960 - 1000 nm[5]
8/13	780 - 1350 nm[6]
13/15	1290 - 1360 nm and 1530 - 1560 nm[7]
13/16	1290 - 1360 nm and 1530 - 1610 nm[7]
15	1530 - 1560 nm[8]
16	1530 - 1610 nm[7]

Adapter Type

FC	FC/SPC
FC/APC	FC/APC
FC/UPC	FC/UPC
SC	SC/SPC
SC/APC	SC/APC
SC/UPC	SC/UPC
ST	ST/SPC
ST/UPC	ST/UPC
LC	LC/UPC

1. Corning fiber SMF-28.
2. Corning Flexcor 1060 fiber with 250um jacket.
3. Corning Panda PM 1300 fiber with 400 um jacket.
4. All wavelengths referenced to vacuum.
5. Flexcor only.
6. Multimode fiber only.
7. 9/125 fiber only.
8. 9/125 fiber and Panda 1300 fiber only.

DiCon Fiberoptics, Inc. 1689 Regatta Blvd. Richmond, CA 94804 Tel. (510)620-5000 Fax. (510)620-4100 www.diconfiber.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP