

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *DiCon PS-12-4-9-13/15-SC* at our website: ***Click HERE***

Variable Attenuator Plug-In

DiCon's Variable Attenuator Plug-In sets attenuation levels in the 0-to-60-dB range with better than 0.15-dB resolution. The Plug-In is designed for easy installation into DiCon's GP700M Modular Mainframe.



Features

- Precise resolution
- Low insertion loss
- Excellent repeatability
- Wide attenuation range
- Low back-reflection

Applications

Motorized variable attenuators automatically adjust power levels in optical measurement systems. Applications include tuning power levels to minimize bit-error rates in WDM systems.

DiCon FIBEROPTICS, INC

U.S. patented. Specifications subject to change. Copyright ©2001 DiCon Fiberoptics, Inc. All rights reserved.


Modular GP700

Specifications[1,4]


Attenuation range[2]	0 - 10 dB	11 - 30 dB	31 - 60 dB
Turning resolution	0.10 dB	0.12 dB	0.15 dB
Repeatability	±0.05 dB	±0.1 dB	±0.1 dB
Absolute accuracy	±0.1 dB	±0.2 dB	±0.25 dB
PDL[3]	0.08 dB	0.1 dB	0.3 dB
Insertion loss	0.6 dB typ., 1.5 dB max.		
Back-reflection	-50 dB max.		
Tuning speed	50 ms min., 1400 ms max.		
Damage threshold	24 dBm min.		
Operating temperature	0°C to +40°C		
Storage temperature	-20°C to +60°C		
Humidity	40°C/90%RH/5 days		

1. All specifications referenced without connectors.
2. Maximum attenuation for multimode components is 30 dB.
3. Singlemode only. Measured at 1550 nm.
4. Performance results may vary depending on multimode launch condition.

Optical Performance



Housing Dimensions



Units: mm

Ordering Information

PA - ☐ - ☐ - ☐

Calibration Wavelength[1]	
8	850.0 nm (multimode)
13	1310.0 nm
15	1550.0 nm

Fiber Type	
9	9/125, SMF-28
50	50/125
62	62.5/125

Adapter Type	
FC	FC/SPC
FC/APC	FC/APC
FC/UPC	FC/UPC
SC	SC/SPC
SC/APC	SC/APC
SC/UPC	SC/UPC
ST	ST/SPC
ST/UPC	ST/UPC
LC	LC/UPC
N	None

1. All wavelengths referenced to vacuum.

DiCon Fiberoptics, Inc. 1689 Regatta Blvd. Richmond, CA 94804 Tel. (510)620-5000 Fax. (510)620-4100 www.diconfiber.com

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

This datasheet has been downloaded from http://www.digchip.com at this page

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP