ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Dynapar E232048XX4X01* at our website: ***Click HERE***

SERIES E23

Dynapar™ brand

Miniature Encoder

Key Features

- **Up to 2540 PPR with Optional Index**
- **Optional Screw Terminal Connections**
- **Standard Size 23 (2.3” diameter)**



CE EN 61326-1

RoHS

SPECIFICATIONS

STANDARD OPERATING CHARACTERISTICS

Code: Incremental, Optical

Resolution: 1 to 2540 PPR (pulses/revolution)

Accuracy: (Worst case any edge to any other edge) ±2.5 arc-min.

Format: Two channel quadrature (AB) with optional Index (Z) outputs

Phase Sense: A leads B for CW or CCW shaft rotation as viewed from the shaft end of the encoder, see Ordering Information

Quadrature Phasing: 90° ± 18° electrical

Symmetry: 180° ± 9° electrical

Index: 180° ± 9° electrical, gated with B

Waveforms: Squarewave with rise and fall times less than 1 microsecond into a load capacitance of 1000 pf

ELECTRICAL

Input Power:
Open Collector or Totem Pole outputs: 5 to 26 VDC. at 200 mA max.;
Line Driver: 5 to 26 VDC at 80 mA max.

Outputs:
7272 Push-Pull: 40mA, sink or source

7272 Differential Line Driver: 40 mA, sink or source

7273 Open Collector: 40mA, sink max

4469 Differential Line Driver: 100 mA, sink or source

Frequency Response: 100 kHz min.

Noise Immunity: Tested to EN61326-1

Electrical Immunity: Reverse polarity and short circuit protected

Termination: Cable, Screw Terminals

Cable: PVC jacket, 105 °C rated, overall foil shield; 3 twisted pairs 26 AWG (output signals), plus 2 twisted pairs 24 AWG (input power)

MECHANICAL

Shaft Size: 1/4”

Shaft Loading: 5 lbs. max. radial and axial

Shaft Speed: 5,000 RPM max.

Starting Torque: 0.2 oz-in max. at 25 °C

Moment of Inertia: 3.7 x 10^{-4} oz–in–sec^2

Housing and Cover: Aluminum

Shaft Material: Stainless Steel

Disc Material: Glass

Weight: 13 oz. max.

ENVIRONMENTAL

Operating Temperature: 0 to +70° C

Storage Temperature: –40 to +80 °C

Shock: 50 G’s for 11 msec duration

Vibration: 5 to 2000 Hz at 2 G’s

Humidity: Up to 98% (non-condensing)

Enclosure Rating: NEMA12/IP54 (dirt tight, splashproof)

ELECTRICAL CONNECTIONS

Note: Wire color codes are referenced here for models that are specified with pre-wired cable.

Single Ended		
Term.	Function (If Used)	Wire Color Code
A	Signal A	BRN
B	Signal B	ORN
C	Signal Z	YEL
D	Power Source	RED
E	No Connection	—
F	Common	BLK
G	Case	GRN

Differential		
Term.	Function (If Used)	Wire Color Code
A	Signal A	BRN
B	Signal B	ORN
C	Signal Z	YEL
D	Power Source	RED
E	No Connection	—
F	Common	BLK
G	Case	GRN
H	Signal $\bar{A}$	BRN/WH
I	Signal $\bar{B}$	ORN/WH
J	Signal $\bar{Z}$	YEL/WH

Dynapar™ brand SERIES E23

Ordering Information

To order, complete the model number with code numbers from the table below:


Code 1: Model	Code 2: Pulses/Rev	Code 3: Mechanical	Code 4: Output	Code 5: Electrical	Code 6: Termination
E23	□□□□	□	□	□	□
E23 Size 23 Enclosed	**0001** **0256** **1024** **0005** **0300** **1200** **0010** **0344** **1250** **0012** **0360** **1270** **0050** **0400** **1500** **0060** **0500** **1600** **0100** **0512** **1800** **0120** **0600** **1968** **0150** **0625** **2000** **0180** **0635** **2048** **0200** **0720** **2400** **0240** **0800** **2500** **0250** **0900** **2540** **1000** For Resolutions above 2540, see Series EC23	**0** 1/4" Shaft, Shielded Bearings **1** 1/4" Shaft, Sealed Bearings	**4** Single Ended, with Index, Format C **5** Differential, with Index, Format C **6** Single Ended, with Index, Format D **7** Differential, with Index, Format D **8** Single Ended, no Index, Format C **9** Differential, no Index, Format C	**0** 5-26V in; 5-26V Open Collector w/2.2kΩ Pullup out **1** 5-26V in; 5-26V Open Collector out **2** 5-26V in; 5V TTL Totem Pole out **3** 5-26V in; 5V Line Driver out (7272) **4** 5-26V in; 5-26V Line Driver out (7272) **5** 5-26V in, 5V Differential Line Driver out (4469) **6** 5-15V in, 5-15V Differential Line Driver out (4469)	**0** 18" Cable **1** 3' Cable **2** 6' Cable **3** 10' Cable **4** 15' Cable **8** Screw Terminals

Dimensions (inches)

Code 6: Termination


0 - 4: Cable

8: Terminals




Code 4: Output

4,5,8,9: Format C



6,7: Format D



Worldwide Brands: NorthStar™ • Dynapar™ • Hengstler™ • Harowe™

DYNAPAR™
INNOVATION - CUSTOMIZATION - DELIVERY

WWW.DYNAPAR.COM

Headquarters: 1675 Delany Road • Gurnee,IL 60031-1282 • USA

Customer Service:
Tel.: +1.800.873.8731
Fax: +1.847.662.4150
custserv@dynapar.com

Technical Support
Tel.: +1.800.234.8731
Fax: +1.847.662.4150
dynapar.techsupport@dynapar.com

European Sales Representitive
Hengstler GmbH
Uhlandstrasse 49, 78554 Aldingen
Germany
www.hengstler.com

Dynapar™ brand is a trademark of DYNAPAR. All rights reserved.
Specifications subject to change without notice.
Document No. 701949-0002, Rev. C ©2016 Dynapar

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP